TRAFFIC IMPACT STUDY

125 ARTHUR STREET

TOWN OF THE BLUE MOUNTAINS GREY COUNTY

PREPARED FOR:
THE BLUE MEADOWS INC.



PREPARED BY:

C.F. CROZIER & ASSOCIATES INC. 1 FIRST STREET, SUITE 200 COLLINGWOOD, ON L9Y 1A1

FEBRUARY 2022

CFCA FILE NO. 2142-6059

The material in this report reflects best judgment in light of the information available at the time of preparation. Any use which a third party makes of this report, or any reliance on or decisions made based on it, are the responsibilities of such third parties. C.F. Crozier & Associates Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.



REVISION NUMBER	DATE	COMMENTS			
Rev. 0	February 24, 2022	Submission to the Town of Blue Mountains			

1.0 EXECUTIVE SUMMARY

C.F. Crozier & Associates Inc. (Crozier) was retained by Blue Meadows Inc. (the Client) to complete a Traffic Impact Study (TIS) in support of the Draft Plan Application for a mixed use commercial and residential development located at 125 Arthur Street (the site) in the Town of the Blue Mountains (Town).

The analysis contained within this report was based on a previous version of the Draft Plan which proposed 125 townhouse units, 58 apartment units, and 2,660 m² (28,632 ft²) of commercial space. The final Draft Plan contains 116 townhouse units, 75 apartment units, and 2,641 m² (28,427 ft²) of commercial space. Both draft plans propose the same full move accesses on Arthur Street and Alice Street and utilize the existing Louisa Street West right-of-way. The revisions to the Draft Plan result in a trip generation increase of 3 and 2 two-way trips in the a.m. and p.m. peak hours, respectively. As such, the findings and conclusions contained within this report remain valid when considering the final Draft Plan prepared by Montgomery Philip King Architect Inc, dated February 16, 2021.

The following intersections were assessed in the TIS:

- Lansdowne Street South and Arthur Street
- Lansdowne Street South and Louisa Street West
- Lansdowne Street South, Beaver Street, and Alice Street
- Alice Street and Peel Street
- The proposed Site Accesses

Intersection analysis of the 2021 existing traffic volumes indicates the following:

- All study intersections are operating at a Level of Service (LOS) "A" during the weekday a.m. and p.m. peak hours with the exception of Lansdowne Street South and Arthur Street which is expected to operate at a LOS of "C".
- Synchro is unable to analyze a 5 legged intersection, so the intersection of Lansdowne Street South, Beaver Street and Alice Street was modeled as a 4 way stop. To do this, volumes on the section of Beaver Street between Alice Street and Louisa Street were redistributed to other applicable legs.

Horizon years of 2026, 2031 and 2041 were assessed, per the agreed upon Terms of Reference. The future background traffic volumes were forecasted based on a growth rate of 2 percent and included site generated traffic from the Towns of Thornbury and the Lora Bay Heights Developments.

Intersection analysis of the 2041 future background traffic volumes indicates the following:

- All study intersections are operating at a Level of Service (LOS) "A" during the weekday a.m.
 and p.m. peak hours with the exception of Lansdowne Street South and Arthur Street which
 is expected to operate at a LOS of "E" and "C" during the weekday a.m. and p.m. peak
 hours, respectively.
- The maximum control delay of 39.2 seconds and volume-to-capacity ratio of 0.33 (NB), both
 forecasted for Arthur Street and Lansdowne Street South in the p.m. peak hour, indicate that
 the boundary road network is operating acceptably with excess capacity for increases in
 traffic volumes.

The development is proposed to generate 115 and 149 two-way external primary trips in the weekday a.m. and p.m. peak hours, respectively, and 27 and 54 two-way pass-by trips in the a.m. and p.m. peak hours, respectively. As noted previously, the trip generation was forecasted based

on a previous version of the Draft Plan. The revised Draft Plan results in 3 and 2 more two-way trips in the a.m. and p.m. peak hours, respectively. As such, the findings and conclusions contained within this report remain valid when considering the final Draft Plan prepared by Montgomery Philip King Architect Inc, dated Februrary 16, 2021.

The requirement for auxiliary left-turn lanes were reviewed for the eastbound and westbound movements on Arthur Street. At the intersection of Lansdowne Street South and Arthur Street both the eastbound and westbound movements warrant left-turn lanes with 25 m of storage under 2041 future background conditions. A westbound left-turn lane with 25 m of storage is also warranted at the intersection of Arthur Street with the proposed site access. The geometric details related to the proposed turn-lanes would be confirmed during detailed design, however it is noted that the westbound left-turn lane at Lansdowne Street South can be accommodated within the existing pavement width.

A signal warrant analysis was undertaken for the intersection of Lansdowne Street South and Arthur Street based on the 2041 future total traffic volumes. The analysis followed the procedures specified in Chapter 4 of the "Ontario Traffic Manual – Book 12", March 2012 for Justifications 1 to 3. Based on this approach, signals are not warranted at the intersection.

Intersection analysis of the 2041 future total traffic volumes indicates the following:

- The study intersections are anticipated to continue operating with a LOS "B" or better in the a.m. and p.m. peak hours, with the exception of the two Arthur Street intersections.
- Lansdowne Street South and Arthur Street is anticipated to operate with a LOS "D" and "F" in the a.m. and p.m. peak hours, respectively. And the proposed Arthur Street site access is anticipated to operate with a LOS "C" and "D" in the weekday a.m. and p.m. peak hours, respectively.
- The above metrics indicate that the increase in traffic volumes on Arthur Street as a result of background traffic growth is anticipated to result in higher delay for the minor road approaches.
 - o This is not atypical, and it is expected that most accesses along Arthur Street would experience similar delays.
- It is recommended that ongoing monitoring of the study intersections should be completed as the future total volumes are based on a 20-year projection. Future consideration for a continuous two-way left-turn lane may be necessary for Arthur Street. This would allow for two-stage gap acceptance.

A sensitivity analysis was completed analyzing the traffic operations assuming all traffic volumes utilize the Arthur Street site access. The sensitivity analysis was completed the 2041 future total traffic volumes and the results indicate the following:

- The elimination of the Alice Street and Lansdowne Street South site accesses is anticipated to have a negligible impact on the operations of the intersection of Lansdowne Street South and Arthur Street.
- The proposed Arthur Street site access is anticipated to operate with a LOS "C" and "E" in the weekday a.m. and p.m. peak hours, respectively. This represents a maximum increase in control delay of 7.0 seconds when compared to the base 2041 future total scenario.

The available sight distances at the proposed site accesses exceed the minimum requirements outlined in the Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads (GDGCR). Accordingly, the proposed site accesses can be supported from a sight distance perspective.

It is concluded that the traffic generated by the 125 Arthur Street development can be supported by the boundary road network, with the noted improvements.

The analysis contained within this report was completed based on a previous version of the Draft Plan. The findings and conclusions contained within this report remain valid when considering the final Draft Plan, as prepared by Montgomery Philip King Architect Inc, dated Februrary 16, 2021. Any minor changes to the Site Plan will not affect the conclusions contained within this report. The proposed Draft Plan Application can be supported from a traffic operations and safety perspective.

TABLE OF CONTENTS

1.0	EXEC	CUTIVE SUMMARY	ii
3.0	INTRO	ODUCTION	
	3.1	Background	
	3.2	Purpose	
	3.3	Development Proposal	
4.0	EXIS1	TING CONDITIONS	2
	4.1	Development Lands	
	4.2	Key Intersections	
	4.3	Boundary Road Network	
	4.4	Active Transportation	
	4.5	Traffic Data	
	4.6	Intersection Operations	
5.0	FUTU	RE BACKGROUND CONDITIONS	5
	5.1	Horizon Years	5
	5.2	Growth Rate	5
	5.3	Roadway Improvements	5
	5.4	Background Development Trip Generation & Assignments	5
	5.5	Intersection Operations	6
6.0	SITE	GENERATED TRAFFIC	8
	6.1	Internal Trip Synergies	9
	6.2	Pass-by Trip Generation	10
	6.3	Trip Distribution	11
7.0	TOTA	AL FUTURE CONDITIONS	11
	7.1	Basis of Assessment	11
	7.2	Auxiliary Lane Warrant Assessment	11
	7.3	Signal Justification	13
	7.4	Intersection Operations	13
8.0	SENS	SITIVITY ANALYSIS: ARTHUR STREET ACCESS ONLY	17
9.0	SIGH	IT DISTANCE ANALYSIS	18
10.0	RECO	OMMENDATIONS	18
110	CON	ICIUSIONS	19

Traffic Impact Study February 2022

List of Tables

Table 1: Boundary Road Network	3
Table 2: Intersection Peak Hours	4
Table 3: 2021 Existing Level of Service	4
Table 4: Towns of Thornbury Trip Generation	6
Table 5: Lora Bay Heights Trip Generation	6
Table 6: 2026 Future Background Volumes	7
Table 7: 2031 Future Background Volumes	7
Table 8: 2041 Future Background Volumes	8
Table 9: Unadjusted Total Trips Generated	9
Table 10: Adjusted (Total) Trip Generation	10
Table 11: Trip Generation	10
Table 12: Auxiliary Turn-Lane Warrants	12
Table 13: Signal Warrant Analysis Results 2041	Traffic Volume Conditions at Lansdowne Street and
Arthur Street	13
Table 14: 2026 Future Total Volumes	14
Table 15: 2031 Future Total Volumes	15
Table 16: 2041 Future Total Volumes	16
Table 17: Sensitivity Analysis 2041 Future Total Vo	lumes 17
Table 18: Minimum Sight Distance Requirements	18

List of Appendices

Appendix A: Terms of Reference Correspondence

Appendix B: Town of the Blue Mountains Official Plan Excerpts

Appendix C: Georgian Trail Map

Appendix D: Transit Maps and Schedules

Appendix E: Traffic Data

Appendix F:Level of Service DefinitionsAppendix G:Detailed Capacity Analysis

Appendix H:Roadway Improvement InformationAppendix I:Background Development ExcerptsAppendix J:ITE 11th Edition Trip Generation Excerpts

Appendix K: Auxiliary Left-Turn Lane Warrants

Appendix L: Signal Warrants

Appendix M: TAC GDGCR Excerpts

List of Figures

Figure 1: Draft Plan (Montgomery Philip King Architect Inc.)

Figure 2: Site Location Plan

Figure 3: Existing Traffic Controls and Lane Configuration

Figure 4: 2021 Traffic Volumes

Figure 5: Towns of Thornbury Trip Assignment

Figure 6: Lora Bay Trip Assignment

Figure 7: Future Background 2026 Traffic Volumes
Figure 8: Future Background 2031 Traffic Volumes
Figure 9: Future Background 2041 Traffic Volumes

Figure 10: Residential Trip Distribution

Figure 11: Commercial Primary Trip Distribution
Figure 12: Commercial Pass-By Trip Distribution

Figure 13: Residential Trip Assignment

Figure 14: Commercial Primary Trip Assignment
Figure 15: Commercial Pass-By Trip Assignment
Figure 16: Future Total 2026 Traffic Volumes
Figure 17: Future Total 2031 Traffic Volumes
Future Total 2041 Traffic Volumes

Figure 19: Sensitivity Analysis Residential Trip Distribution

Figure 20: Sensitivity Analysis Commercial Primary Trip Distribution Sensitivity Analysis Commercial Pass-By Trip Distribution

Figure 22: Sensitivity Analysis Residential Trip Assignment

Figure 23: Sensitivity Analysis Commercial Primary Trip Assignment
Figure 24: Sensitivity Analysis Commercial Pass-By Trip Assignment
Figure 25: Sensitivity Analysis Future Total 2041 Traffic Volumes

3.0 INTRODUCTION

3.1 Background

C.F. Crozier & Associates Inc. (Crozier) was retained by Blue Meadows Inc. (the Client) to complete a Traffic Impact Study (TIS) in support of the Draft Plan Application for a mixed use commercial and residential development located at 125 Arthur Street (the site) in the Town of the Blue Mountains (Town).

3.2 Purpose

The purpose of the Traffic Impact Study is to review the impacts of the proposed development from a transportation engineering perspective by analyzing the following:

- Existing, future background, and future total traffic operations at the study intersections
- Forecasted trip generation of the proposed development
- Sight distance at the site proposed accesses
- Auxiliary Turning Lane Warrants
- Signal Warrants

The TIS has been prepared in accordance with the Terms of Reference established with the Town. **Appendix A** includes correspondence with Town staff.

3.3 Development Proposal

The Draft Plan proposes a combination of commercial and residential development including the following elements:

- 98 standard townhouse units
- 18 townhouse units with ground floor commercial
- 75 apartments above ground floor commercial
- 2,641 m² (28,427 ft²) GFA of commercial space
- 3 site accesses
 - o 1 on Arthur Street (Access A)
 - o 1 on Lansdowne Street South (Existing Louisa Street extension, Access B)
 - o 1 on Alice Street (Access C)

Several residential units are proposed to have driveway accesses on Alice Street and Lansdowne Street South, all site generated traffic was assumed to utilize the proposed site accesses to provide a conservative analysis. **Figure 1** includes the proposed Draft Plan prepared by Montgomery Philip King Architect Inc.

The analysis contained within this report was based on a previous version of the Draft Plan which proposed 125 townhouse units, 58 apartment units, and 2,660 m² (28,632 ft²) of commercial space. The final Draft Plan contains 116 townhouse units, 75 apartment units, and 2,641 m² (28,427 ft²) of commercial space. Both draft plans propose the same full move accesses on Arthur Street and Alice Street and utilize the existing Louisa Street West right-of-way. The revisions to the Draft Plan result in a trip generation increase of 3 and 2 two-way trips in the a.m. and p.m. peak hours, respectively. As such, the findings and conclusions contained within this report remain valid when considering the final Draft Plan prepared by Montgomery Philip King Architect Inc, dated Februrary 16, 2021.

4.0 EXISTING CONDITIONS

4.1 Development Lands

The proposed site is 5.2 ha and consists of open lots and two existing homes. The property is bounded by Arthur Street to the north, Lansdowne Street South to the east, Alice Street to the south, and Little Beaver Creek to the west. **Figure 2** illustrates the location of the site.

4.2 Key Intersections

Key study Intersections are as follows:

- Lansdowne Street South and Arthur Street
- Lansdowne Street South and Louisa Street West
- Lansdowne Street South, Beaver Street, and Alice Street
- Alice Street and Peel Street
- The proposed Site Accesses

Figure 3 illustrates the existing traffic controls.

4.3 Boundary Road Network

Table 1 outlines the boundary road network. The information included below was obtained from the Town of the Blue Mountains Official Plan "Schedule B-2 – Transportation Thornbury Clarksburg", included in **Appendix B. Figure 3** illustrates the existing traffic controls on the boundary road network. With skewed directions, the directional orientation of the road network is ambiguous. To provide clarity throughout this report, Arthur Street, Louisa Street and Alice Street have been given an east-west orientation, while Lansdowne Street South, Peel Street and Beaver Street have been given a north-south orientation.

Table 1: Boundary Road Network

Roadway	Arthur Street	Lansdowne Street South	Alice Street	Louisa Street	Peel Street	Beaver Street
Direction	East-West	North-South	East-West	East-West	North-South	East-West
Classification	Highway	Local	Local	Local	Local	Local
Jurisdiction	Town of the Blue Mountains (MTO Connecting Link)	Town of the Blue Mountains	Town of the Blue Mountains	Town of the Blue Mountains	Town of the Blue Mountains	Town of the Blue Mountains
Posted Speed Limit	50 km/h east of Lansdowne Street South and 70km/h to the west	50 km/h (Assumed)	50 km/h (Assumed)	50 km/h (Assumed)	80 km/h (Assumed)	40 km/h (Posted)
Total Number of Travel Lanes	2	2	2	2	2	2
Transit Facilities	GTR Bus Stop At Foodland	None	None	None	None	None
Pedestrian Facilities	1.8 m sidewalk on south side, east of Lansdowne Street South	None	None	None	None	1.5 m Sidewalk on southern side, south of Alice Street
Cycling Facilities	Georgian Trail (approx. 70 m north of Arthur Street running east-west)	None	None	None	None	None

4.4 Active Transportation

The development proposal includes new sidewalk on Alice Street and Lansdowne Street South along the property frontage, and the extension of the Arthur Street sidewalk to the western limits of the site.

The site is approximately 70 meters south of the Georgian Trail which supports cycling, walking, and running while connecting Meaford to Collingwood. **Appendix C** contains the Town's Georgian Trail map.

Grey Bruce regional transit stop is located at the Thornbury Foodland adjacent to the site. The Route runs from Meaford to the Town of the Blue Mountains with two trips in the A.M peak hour and two trips in the P.M peak hour with further opportunity to connect to Owen Sound and Collingwood. **Appendix D** contains transit maps and schedules.

4.5 Traffic Data

Turning movement counts for the study intersections were undertaken by Spectrum staff from 6:00 a.m. to 10:00 a.m., and 4:00 p.m. to 7:00 p.m. on Thursday, October 14th, 2021. **Appendix E** contains the turning movement counts, and **Figure 4** illustrates the weekday a.m. and p.m. peak hour traffic volumes.

Peak hour factors (PHF) associated with the weekday a.m. and p.m. peak hours were calculated for each intersection based on the existing traffic volumes. **Table 2** outlines the PHFs as calculated and applied to the model for the study intersections.

Table 2: Intersection Peak Hours

Intersection	Peak Hour	Peak Hour Factor
Lansdowne Street South and Arthur	8:45 – 9:45 A.M.	0.86
Street	3:30 – 4:30 P.M.	0.95
Lansdowne Street South and Louisa	8:45 – 9:45 A.M.	0.69
Street West	4:15 – 5:15 P.M.	0.73
Lansdowne Street South, Beaver	8:45 – 9:45 A.M.	0.88
Street, and Alice Street	4:30 – 5:30 P.M.	0.89
Alice Street and Peel Street	9:00 – 10:00 A.M.	0.50
Alice street and Peerstreet	4:15 – 5:15 P.M.	0.56

4.6 Intersection Operations

The operations of the study intersections were analyzed based on the traffic volumes illustrated in **Figure 4. Appendix F and G** contain, Level of Service (LOS) definitions and detailed capacity analysis worksheets, respectively. **Table 3** outlines the existing traffic operations at the study intersections. In order to model the 5-legged intersection of Lansdowne Street South, Beaver Street and Alice Street, volumes were adjusted and merged to create a 4-legged all way stop.

Table 3: 2021 Existing Level of Service

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop	A.M.	С	15.8 s	0.09 (NB)
and Arthur Street	(Two-way)	P.M.	С	17.8 s	0.10 (NB)
Lansdowne Street South	Stop	A.M.	Α	9.7 s	0.01 (WB)
and Louisa Street West	(Two-way)	P.M.	Α	8.5 s	0.00 (WB) ³
Lansdowne Street South,	Stop (All-way)	A.M.	Α	7.0 s	0.03 (SB)
Beaver Street, and Alice Street		P.M.	Α	7.2 s	0.06 (SB)
Alice Street and Peel	Stop (T)	A.M.	Α	8.6 s	0.00 (WB) ³
Street		P.M.	Α	8.6 s	0.00 (WB) ³

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

The metrics above indicate that the intersections operate at a LOS "C" or better under existing traffic volume conditions. The maximum control delay was found to be 17.8 seconds and the maximum volume-to-capacity ratio was found to be 0.10. These metrics are associated with the northbound movements on Lansdowne Street South at the intersection with Arthur Street. These metrics indicate that the study intersections have reserve capacity for future increase in traffic volumes.

5.0 FUTURE BACKGROUND CONDITIONS

5.1 Horizon Years

It is anticipated that the proposed development will be completed by 2026. Accordingly, the horizon years of 2026, 2031, and 2041 have been analyzed, representing full build-out as well as 5 and 15 years beyond full build out, as requested by Town staff.

5.2 Growth Rate

A growth rate of 1.6% was calculated by analyzing MTO Arthur Street AADT data at the intersection with Peel Street from 2010 to 2016. Accordingly, a rate of 2% will be applied.

5.3 Roadway Improvements

The Town is undergoing the "Thornbury West Phase 1 Reconstruction Project". As part of this project, Beaver Street is proposed to be closed between Louisa Street and Victoria Street. A staff report was brought to council on June 15, 2021, which provided options for this closure or partial closure. Further to this report, a draft By-law will be presented to council this year to stop up and close Beaver Street.

As noted previously, in order to model the 5-legged intersection of Lansdowne Street South, Beaver Street and Alice Street, volumes were adjusted and merged to create a 4-legged all-way stop. This adjustment is consistent with the planned closure. **Attachment H** contains the Beaver Street closure plans (Tatham, 2021).

It is noted that based on the projected future background traffic volumes, auxiliary eastbound and westbound left-turn lanes are warranted at the intersection of Lansdowne Street South and Arthur Street. Accordingly, the intersection has been modelled with left-turn lanes through all horizon years in both the future background and future total scenarios. Section 7.2 contains detailed information on the auxiliary lane warrants.

5.4 Background Development Trip Generation & Assignments

5.4.1. Towns of Thornbury Development

Towns of Thornbury is a proposed residential development south of Louisa Street, between Lansdowne Street South and Beaver Street South. The Town provided relevant excerpts from a Traffic Brief prepared by Tatham. The Towns of Thornbury development is proposed to consist of 23 townhouse units. Relevant excerpts have been included in **Appendix I** for reference. The trip generation described in **Table 4** was calculated based on the 11th Edition of the ITE Trip Generation Manual.

Blue Meadows Inc. Traffic Impact Study
125 Arthur Street February 2022

Table 4: Towns of Thornbury Trip Generation

Land Hee	Number of Units	Peak Hour	Number of Trips			
Land Use	und use Nottiber of Offins	reak nooi	Inbound	Outbound	Total	
Townhouse	Townhouse	Weekday A.M.	2	7	9	
(LUC 221)	23	Weekday P.M.	7	5	12	

The trips generated by the Towns of Thornbury development have been assigned to the boundary road network based on the trip distribution described in **Section 5.2** of this report. **Figure 5** illustrates the Towns of Thornbury trip assignment.

5.4.2. Lora Bay Heights Development

Lora Bay Heights is a proposed residential development on the north side of Arthur Street directly east of Peel Street. Per correspondence with Town Staff this development will consist of 2 single detached homes and 22 townhouse units. For the purpose of this analysis, it has been assumed that the development will be built out by 2026. **Table 5** outlines the forecasted trip generation based on the ITE Trip Generation Manual, 11th Edition data.

Table 5: Lora Bay Heights Trip Generation

Land Use	Number of Units	Peak Hour	Number of Trips			
Lana ose		reak nooi	Inbound	Outbound	Total	
Townhouse	Townhouse (LUC 221)	Weekday A.M.	2	7	9	
(LUC 221)		Weekday P.M.	7	4	11	
Single Family	2	Weekday A.M.	0	1	1	
(LUC 210)		Weekday P.M.	1	1	2	
TOTAL		Weekday A.M.	2	8	10	
		Weekday P.M.	8	5	13	

The trips generated by the Towns of Thornbury development have been assigned to the boundary road network based on the trip distribution described in **Section 5.2** of this report. **Appendix A** includes correspondence with the Town confirming unit counts. **Appendix J** contains relevant excerpts from the ITE Trip Generation Manual, 11th Edition. **Figure 6** illustrates the Lora Bay Heights trip assignment.

5.5 Intersection Operations

Figure 7-9 illustrate the 2026, 2031, and 2041 future background traffic volumes, respectively. **Table 6, Table 7, and Table 8** illustrate the 2026, 2031, and 2041 future background operations for each horizon year, respectively. **Appendix F and G** contain the Level of Service (LOS) definitions and detailed capacity analysis worksheets, respectively.

Table 6: 2026 Future Background Volumes

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop	A.M.	C	16.6 s	0.07 (NB)
and Arthur Street	(Two-way)	P.M.	С	20.5 s	0.14 (NB)
Lansdowne Street South	Stop	A.M.	Α	9.8 s	0.01 (WB)
and Louisa Street West	(Two-way)	P.M.	Α	8.5 s	0.00 (WB) ³
Lansdowne Street South,	Stop (All-way)	A.M.	Α	7.0 s	0.03 (NB/SB)
Beaver Street, and Alice Street		P.M.	Α	7.2 s	0.07 (SB)
Alice Street and Peel	Stop (T)	A.M.	Α	8.6 s	0.00 (WB) ³
Street		P.M.	Α	8.6 s	0.00 (WB) ³

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

Table 7: 2031 Future Background Volumes

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop (Two-way)	A.M.	С	18.5 s	0.08 (NB)
and Arthur Street		P.M.	С	24.2 s	0.19 (NB)
Lansdowne Street South	Stop	A.M.	Α	9.8 s	0.01 (WB)
and Louisa Street West	(Two-way)	P.M.	Α	8.5 s	0.00 (WB) ³
Lansdowne Street South,	Stop (All-way)	A.M.	Α	7.0 s	0.04 (NB)
Beaver Street, and Alice Street		P.M.	Α	7.3 s	0.07 (SB)
Alice Street and Peel	Stop (T)	A.M.	Α	8.6 s	0.00 (WB) ³
Street		P.M.	Α	8.6 s	0.00 (WB) ³

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

Table 8: 2041 Future Background Volumes

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop	A.M.	С	23.8 s	0.12 (NB)
and Arthur Street	(Two-way)	P.M.	Е	39.2 s	0.33 (NB)
Lansdowne Street South	Stop	A.M.	Α	9.9 s	0.01 (WB)
and Louisa Street West	(Two-way)	P.M.	Α	8.6 s	0.00 (WB) ³
Lansdowne Street South,	Stop (All-way)	A.M.	Α	7.1 s	0.05 (SB)
Beaver Street, and Alice Street		P.M.	Α	7.4 s	0.09 (SB)
Alice Street and Peel	Stop (T)	A.M.	Α	8.6 s	0.00 (WB) ³
Street		P.M.	Α	8.6 s	0.00 (WB) ³

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

The intersection of Lansdowne Street South and Arthur Street is expected to operate with a LOS "E" or better under 2041 future background traffic volume conditions. The maximum control delay of 39.2 seconds and maximum volume-to-capacity ratio of 0.33 (SB) indicates that the intersection has reserve capacity for increases in traffic volumes.

Other study intersections are expected to operate with a LOS "A" or better under 2041 future background traffic volume conditions. The maximum control delay of 9.9 seconds and maximum volume-to-capacity ratio of 0.09 (SB) indicates that the remaining study intersections are expected to operate well with reserve capacity for increases in traffic volumes.

6.0 SITE GENERATED TRAFFIC

The proposed development will result in additional vehicles on the boundary road network that previously did not exist.

The analysis contained within this report was based on a previous version of the Draft Plan which proposed 125 townhouse units, 58 apartment units, and 2,660 m² (28,632 ft²) of commercial space. The final Draft Plan contains 116 townhouse units, 75 apartment units, and 2,641 m² (28,427 ft²) of commercial space. Both draft plans propose the same full move accesses on Arthur Street and Alice Street and utilize the existing Louisa Street West right-of-way. The revisions to the Draft Plan result in a trip generation increase of 3 and 2 two-way trips in the a.m. and p.m. peak hours, respectively. As such, the findings and conclusions contained within this report remain valid when considering the final Draft Plan prepared by Montgomery Philip King Architect Inc, dated Februrary 16, 2021.

Blue Meadows Inc. Traffic Impact Study
125 Arthur Street February 2022

The unadjusted trip generation of the proposed development was forecasted using the fitted curve equations and average rates provided in the ITE Trip Generation Manual, 11th Edition for the following land uses:

- LUC 220: Multifamily Housing (Low-Rise)
- LUC 221: Multifamily Housing (Mid-Rise)
- LUC 822: Strip Retail Plaza (<40K)

6.1 Internal Trip Synergies

The ITE Trip Generation Handbook, 3rd Edition, provides internal trip synergy rates for individual land uses for mixed-use developments. Internal trip synergy is expected between the retail and residential components of the proposed development. **Appendix J** includes relevant excerpts from the ITE Trip Generation Manual, 11th Edition and Handbook, 3rd Edition, as well as the internal and external trip calculations. **Table 9** summarizes the unadjusted trips forecasted to be generated by the development.

Table 9: Unadjusted Total Trips Generated

llee	Dogle Hour	Number of Trips			
Use	Peak Hour	Inbound	Outbound	Total	
LUC 220: Multifamily Housing (Low-Rise) 125 Dwelling Units	Weekday A.M.	15	47	62	
	Weekday P.M.	47	27	74	
LUC 221: Multifamily Housing (Mid-Rise) 58 Dwelling Units	Weekday A.M.	3	11	14	
	Weekday P.M.	14	9	23	
TOTAL DECIDENTAL	Weekday A.M.	18	58	76	
TOTAL RESIDENTAIL	Weekday P.M.	61	36	97	
LUC 822: Strip retail Plaza (<40,000 ft ²	Weekday A.M.	41	27	68	
GFA) 28,632 ft ² GFA	Weekday P.M.	82	82	164	

Table 10 includes the adjusted trip generation with the internal trip capture and the external trips tabulated separately.

Table 10: Adjusted (Total) Trip Generation

Land Use	Trim Trem a	Domis Hour	Peak Hour		I
Lana use	Trip Type	reak nour	Inbound	Outbound	Total
	Internal	Weekday A.M.	0	1	1
Residential	internal	Weekday P.M.	21	8	29
Residential	Eutoroal	Weekday A.M.	18	57	75
	External	Weekday P.M.	40	28	68
	Internal	Weekday A.M.	1	0	1
Dotail	internal	Weekday P.M.	8	21	29
Retail	Estomod	Weekday A.M.	40	27	67
	External	Weekday P.M.	eekday P.M. 74 61	135	
Total		Weekday A.M.	1	1	2
	Internal	Weekday P.M. 29 29		29	58
	Evtornal	Weekday A.M.	58	84	142
	External	Weekday P.M.	114	89	203

6.2 Pass-by Trip Generation

As defined by the ITE Trip Generation Handbook, 3rd Edition, primary trips are made for the specific purpose of visiting the generator. Pass-by trips are made as intermediate stops on the way from an origin to a primary destination without a route diversion. The Handbook does not provide a rate of LUC 822, but it does provide a rate of 40% based on p.m. peak hour data for LUC 821 "Shopping Plaza (40-150k)". A pass-by rate is not provided for the a.m. peak hour, accordingly the 40% was applied to the a.m. peak hour as well. **Table 11** illustrates the overall site trip generation.

Table 11: Trip Generation

Land Use	Trip Type	Peak Hour	Trips Generated				
			Inbound	Outbound	Total		
	Pass-by	Weekday A.M.	0	0	0		
Desidential	T GSS-Dy	Weekday P.M.	0	0	0		
Residential	Dringan	Weekday A.M.	18	57	75		
	Primary	Weekday P.M.	40	28	68		
	Pass-by	Weekday A.M.	16	11	27 54 40		
Retail	Puss-by	Weekday P.M.	30	24			
Kelali	Drim an (Weekday A.M.	24	16	40		
	Primary	Weekday P.M.	44	37	81		
	Dass by	Weekday A.M.	16	11	27		
Total	Pass-by	Weekday P.M.	30	24	54		
	Drim an t	Weekday A.M.	ay A.M. 42 73	73	115		
	Primary	Weekday P.M.	84	65	149		

6.3 Trip Distribution

The residential and commercial trips generated by the proposed development were distributed to the boundary road network based on existing travel patterns and the location of nearby residential, employment, retail, and service destinations. The downtown core of Thornbury and the Town of Collingwood are east of the site, while Owen Sound and Meaford are to the west of the site. The trips were distributed as follows:

- 55% to/from downtown Thornbury and Collingwood
 - 45% via Arthur Street
 - o 5% via Lansdowne St. South
 - o 5% via Alice Street
- 45% to/from Owen Sound/Meaford Area
 - 40% via Arthur Street
 - 5% via Peel Street

The distribution between the proposed site accesses was selected to reflect the layout and density of residential areas within the site. For a conservative analysis it was assumed that the trips generated by homes on Alice Street would utilize the southern site access (Access C) and the trips generated by homes on Lansdowne Street South would utilize the Louisa Street Access (Access C). The residential trip distribution and corresponding assignment are illustrated in **Figures 9 and 13**, respectively.

The pass-by trips generated by the proposed commercial development were distributed to the boundary road network based on the existing volume of traffic passing the proposed development on Arthur Street. Accordingly, 55 percent of the pass-by trips were assigned to and from the east on Arthur Street and 45 percent were applied to and from the west on Arthur Street. **Figures 11 and 14** illustrates the commercial primary trip distribution and trip assignment, respectively. **Figures 12 and 15** illustrates the pass-by trip distribution and trip assignment, respectively.

7.0 TOTAL FUTURE CONDITIONS

7.1 Basis of Assessment

The traffic impacts arising from the proposed development were assessed on the basis of the site generated traffic illustrated in **Figure 13 to 15** being superimposed on the future background traffic volumes in **Figures 7**, **8**, **and 9**. The resulting total traffic volumes for the weekday a.m. and p.m. peak hours are illustrated in **Figures 16**, **17**, **and 18** for the 2026, 2031, and 2041 horizon years, respectively.

7.2 Auxiliary Lane Warrant Assessment

An auxiliary left-turn lane warrant was completed at the intersection of Arthur Street and the proposed site access and Lansdowne Street South and Arthur Street based on the methodology described in the MTO Design Supplement for the Transportation Association of Canada (TAC) Geometric Design Guide for Canadian Roads (GDGCR). Arthur Street has a posted speed limit of 70 km/h west of Lansdowne Street South, and 50 km/h to the east. Accordingly, design speeds of 60 and 90 km/h were used for the portions of Arthur Street to the east and west of Lansdowne Street South, respectively. **Appendix K** contains auxiliary left-turn lane warrant charts. **Table 12** summarizes the results of the left-turn lane warrants.

Table 12: Auxiliary Turn-Lane Warrants

Intersection & Approach	Horizon Year	Peak Hour	VA	V o	%LT in V _A	Storage	Reference & Design speed
WB - Lansdowne Street		A.M.	335	409	3%	×	Exhibit 9A-7 & 60
South and Arthur Street	2026 Future	P.M.	559	451	3%	√ (15 m)	km/h
EB - Lansdowne Street	Background	A.M.	409	335	1%	×	Exhibit 9A-19 & 90
South and Arthur Street		P.M.	451	559	1%	√ (15 m)	km/h
WB - Lansdowne Street		A.M.	449	550	2%	×	Exhibit 9A-7 & 60
South and Arthur Street	2041 Future	P.M.	750	604	3%	√ (25 m)	km/h
EB - Lansdowne Street	Background	A.M.	550	449	1%	√ (15 m)	Exhibit 9A-19 & 90
South and Arthur Street		P.M.	604	750	1%	√ (25 m)	km/h
WB - Lansdowne Street		A.M.	354	435	5%	×	Exhibit 9A-7 & 60
South and Arthur Street		P.M.	597	479	5%	√ (15 m)	km/h
EB - Lansdowne Street	2026 Future Total	A.M.	435	354	1%	×	
South and Arthur Street		P.M.	479	597	1%	√ (15 m)	Exhibit 9A-19 & 90 km/h
WB - Arthur Street and Site Access		P.M.	599	485	7%	√ (25 m)	
WB - Lansdowne Street South and Arthur Street		A.M.	468	576	4%	√ (15 m)	Exhibit 9A-7 & 60
	2041 Future Total	P.M.	788	632	4%	√ (25 m)	km/h
EB - Lansdowne Street South and Arthur Street		P.M.	632	788	1%	√ (25+ m)	Exhibit 9A-19 & 90 km/h

As summarized, auxiliary left-turn lanes are warranted at Lansdowne Street South and Arthur Street in the 2026 future background horizon year. It is noted that Arthur Street was previously widened to Lansdowne Street to accommodate the Foodland left-turn lanes. Accordingly, a westbound left-turn lane at Lansdowne Street South and Arthur Street can be accommodated within the existing pavement width through pavement marking adjustments.

The proposed Arthur Street site access is approximately 90 m west of Lansdowne Street. Accordingly, the eastbound left-turn lane at Lansdowne Street and the westbound left-turn lane at the proposed site access will be designed as back-to-back left-turn lanes. Geometric design elements will be confirmed during detailed design.

The turn-lane warrant described above accounts for the speed limit increase from 50 km/h to 70 km/h at Lansdowne Street. It is recommended that a speed limit reduction to the west limits of the site be considered given the proposed residential and commercial units. Regardless of a speed limit reduction, a westbound left-turn lane would be warranted at the proposed Arthur Street site access.

Blue Meadows Inc. Traffic Impact Study
125 Arthur Street February 2022

7.3 Signal Justification

A signal warrant analysis was undertaken for the intersection of Lansdowne Street South and Arthur Street based on the 2041 future total traffic volumes. The analysis followed the procedures specified in Chapter 4 of the "Ontario Traffic Manual – Book 12", March 2012 for Justifications 1 (Minimum Vehicle Volume), 2 (Delay to Cross Traffic) and 3 (Volume/Delay Combination). The future total peak hour volumes were assigned to the 8-hours based on the percentage of the peak hour traffic volumes established from the existing 8-hour traffic data.

The results of the signal warrant analyses are summarized in **Table 13** the warrant sheets have been included in **Appendix L**. Signals are not warranted the intersection of Lansdowne Street South and Arthur Street under 2041 future total traffic volume conditions. The requirement for signals should continue to be monitored by the Town as new developments are constructed and occupied within the study area.

Table 13: Signal Warrant Analysis Results
2041 Traffic Volume Conditions at Lansdowne Street and Arthur Street

Justifica	tion	Section Percent	Signal Justified
1. Minimum Vehicular	A. Total Volume	94%	No
Volume	B. Crossing volume	31%	No
2 Dolay to Cross Traffic	A. Main Road	93%	No
2. Delay to Cross Traffic	B. Crossing Road	40%	No
3. Combination	A. Justification 1	31%	No
3. Combination	B. Justification 2	40%	No

7.4 Intersection Operations

The 2026, 2036, and 2041 future total traffic operations are summarized in **Table 14**, **Table 15**, and **Table 16**, respectively. The operations were based on the future background traffic volumes illustrated in **Figures 16**, **17**, and **18**. This analysis assumed the construction of the warranted left-hand turning lanes. **Appendix F and G** contain, Level of Service (LOS) definitions and detailed capacity analysis worksheets, respectively.

Table 14: 2026 Future Total Volumes

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop	A.M.	С	17.6 s	0.13 (NB)
and Arthur Street	(Two-way)	P.M.	С	23.6 s	0.22 (NB)
Lansdowne Street South	Stop	A.M.	В	10.1 s	0.04 (EB)
and Louisa Street West/Site Access B	(Two-way)	P.M.	Α	9.2 s	0.04(EB)
Lansdowne Street South,	Stop	A.M.	Α	7.1 s	0.04 (SB)
Beaver Street, and Alice Street	(All-way)	P.M.	Α	7.3 s	0.08 (SB)
Alice Street and Peel Street	Stop	A.M.	Α	8.6 s	0.01 (WB)
Alice sireer and reerstreer	(T)	P.M.	Α	8.6 s	0.01 (WB)
Arthur Street and Site	Stop	A.M.	С	15.7 s	0.16 (NB)
Access A	(Two-way)	P.M.	С	19.9 s	0.22 (NB)
Alice Street and Site Access	Stop	A.M.	Α	8.5 s	0.01 (SB)
С	(Two-way)	P.M.	Α	8.5 s	0.00 (SB)

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

Table 15: 2031 Future Total Volumes

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop	A.M.	С	19.7 s	0.15 (NB)
and Arthur Street	(Two-way)	P.M.	D	28.8 s	0.29 (NB)
Lansdowne Street South	Stop	A.M.	В	10.1 s	0.04 (EB)
and Louisa Street West/Site Access B	(Two-way)	P.M.	Α	9.2 s	0.04 (EB)
Lansdowne Street South, Beaver Street, and Alice Street	Stop	A.M.	Α	7.1 s	0.04 (SB)
	(All-way)	P.M.	Α	7.3 s	0.08 (SB)
Alice Street and Peel	Stop	A.M.	Α	8.6 s	0.01 (WB)
Street	(T)	P.M.	Α	8.6 s	0.01 (WB)
Arthur Street and Site	Stop	A.M.	С	17.1 s	0.18 (NB)
Access A	(Two-way)	P.M.	С	22.7 s	0.25 (NB)
Alice Street and Site Access C	Stop	A.M.	Α	8.5 s	0.01 (SB)
	(Two-way)	P.M.	Α	8.5 s	0.00 (SB)

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

Table 16: 2041 Future Total Volumes

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²
Lansdowne Street South	Stop	A.M.	D	26.2 s	0.22 (NB)
and Arthur Street	(Two-way)	P.M.	F	53.5 s	0.49 (NB)
Lansdowne Street South	Stop	A.M.	В	10.2 s	0.04 (EB)
and Louisa Street West/Site Access B	(Two-way)	P.M.	Α	9.3 s	0.04 (EB)
Lansdowne Street South,	Stop	A.M.	Α	7.1 s	0.05 (SB)
Beaver Street, and Alice Street	(All-way)	P.M.	Α	7.4 s	0.10 (SB)
Alice Street and Peel	Stop	A.M.	Α	8.6 s	0.01 (WB)
Street	(T)	P.M.	Α	8.6 s	0.01 (WB)
Arthur Street and Site	Stop	A.M.	С	21.4 s	0.22 (NB)
Access A	(Two-way)	P.M.	D	32.4 s	0.34 (NB)
Alice Street and Site Access C	Stop	A.M.	Α	8.5 s	0.01 (SB)
	(Two-way)	P.M.	Α	8.5 s	0.00 (SB)

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note2: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note³: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

The study intersections are anticipated to continue operating with an LOS "B" or better in the a.m. and p.m. peak hours, with the exception of Lansdowne Street South and Arthur Street which is anticipated to operate at a LOS "F" in the p.m. peak hour. The site generated traffic is anticipated to result in a maximum increase in control delay of 14.3 seconds and a maximum increase of volume-to-capacity ratio of 0.16 at the intersection of Lansdowne Street South and Arthur Street.

The Alice Street site access is anticipated to operate at a LOS "A" and minimal control delay. The Arthur Street site access is anticipated to operate at a LOS "D" or better, with a maximum control delay of 32.4 seconds and a maximum volume-to-capacity ratio of 0.34. It is noted that a departure taper will be constructed opposite the westbound left-turn lane. This can allow for 2-stage gap acceptance which could reduce the delay for the northbound left-turn movement.

The above metrics indicate that the increase in traffic volumes on Arthur Street as a result of background traffic growth is anticipated to result in higher delay for the minor road approaches. This is not atypical, and it is expected that most accesses along Arthur Street would experience similar delays. It is recommended that ongoing monitoring of the study intersections should be completed as the future total volumes are based on a 20-year projection. Future consideration for a continuous two-way left-turn lane may be necessary for Arthur Street. This would allow for two-stage gap acceptance.

Blue Meadows Inc. Traffic Impact Study
125 Arthur Street February 2022

8.0 SENSITIVITY ANALYSIS: ARTHUR STREET ACCESS ONLY

As requested, by Town staff, a sensitivity analysis was completed analyzing the traffic operations assuming all traffic volumes utilize the Arthur Street site access. For consistency, the turn-lane dimensions utilized in the future total analysis were maintained for the sensitivity analysis.

Figures 19, 20 and 21 illustrate the sensitivity analysis trip distribution, trip assignment and 2041 future total traffic volumes, respectively. The 2041 future total traffic operations are summarized in **Table 17**. **Appendix F and G** contain, Level of Service (LOS) definitions and detailed capacity analysis worksheets, respectively.

Intersection	Control	Peak Hour	Level of Service ¹	Control Delay	Maximum v/c ratio²		
Lansdowne Street South	Stop	A.M.	D	27.7 s	0.16 (NB)		
and Arthur Street	(Two-way)	P.M.	F	54.2 s	0.45 (NB)		
Lansdowne Street South and Louisa Street West	Stop	A.M.	Α	9.9 s	0.04 (EB)		
	(Two-way)	P.M.	Α	8.6 s	0.04 (EB)		
Lansdowne Street South, Beaver Street, and Alice Street	Stop	A.M.	Α	7.1 s	0.05 (SB)		
	(All-way)	P.M.	Α	7.4 s	0.10 (SB)		
Alice Street and Peel Street	Stop	A.M.	Α	8.6 s	0.01 (NB)		
	(T) [.]	P.M.	Α	8.6 s	0.01 (WB)		
Arthur Street and Site Access A	Stop	A.M.	С	24.4 s	0.35 (NB)		
	(Two-way)	P.M.	Е	39.4 s	0.47 (NB)		

Table 17: Sensitivity Analysis 2041 Future Total Volumes

Note: The Level of Service of a stop-controlled intersection is based on the delay associated with the critical minor road approach. The Level of Service of all-way stop-controlled intersection is based on the average delay per vehicle.

Note²: The maximum v/c ratio for two-way stop-controlled and all-way stop controlled intersections represents the maximum v/c for the minor road approach movements at the intersection.

Note3: Low approach volumes caused the volume-to-capacity ratio to round to 0.00.

The intersection of Lansdowne Street South and Arthur Street is anticipated to continue operating at a LOS "F" in the p.m. peak hour. Compared to the base 2041 future total scenario operations summarized in **Table 16**, these operations represent an increase in control delay of 0.7 seconds and no change to the volume-to-capacity ratio.

The Arthur Street site access is anticipated to operate at a LOS "E" or better under 2041 future total traffic volume conditions. The Arthur Street site access is anticipated to operate with a maximum control delay of 39.4 s and a maximum volume-to-capacity ratio of 0.47. Compared to the base 2041 future total scenario operations described in **Table 16**, these operations represent an increase in control delay of 7.0 seconds and a change in volume-to-capacity ratio of 0.13.

These metrics indicate that the proposed development can be supported based on the single access scenario.

9.0 SIGHT DISTANCE ANALYSIS

A sight distance assessment was completed to demonstrate that the proposed site accesses to Alice Street and Arthur Street provide sufficient stopping and intersection sight distance. The minimum stopping sight distance requirements were obtained from the Transportation Association of Canada's (TAC) Geometric Design Guide for Canadian Roads (GDGCR). All streets have either an assumed or posted speed limit of 50 or 70 km/h, which corresponds to a design speed of 60 or 90 km/h.

Section 2.5 of the TAC GDGCR provides stopping sight distances for various design speeds on level roadways. For design speeds of 60 km/h and 90km/h, stopping sight distances of 85 meters and 160 meters are required, respectively.

Section 9.9 of the TAC GDGCR provides intersection sight distance for different intersection control types. For these accesses, the applicable case "Case B1 – Left turns from the minor road" has the greatest sight distance requirement of 130 metres for 60 km/h design speed roads and 190 meters for 90 km/h roads.

Relevant excerpts from TAC GDGCR have been included as **Appendix M**. The minimum and available sight distances are summarized in **Table 18**.

Proposed Design		Oncoming	Stopping Sig	ht Distance	Intersection Sight Distance		
Access	Speed	Traffic	Minimum Standard	Available Distance	Minimum Standard	Available Distance	
Authoriz Ctro ot		Eastbound	160 m	+200 m	190 m	+200 m	
Arthur Street 90 km/h	Westbound	160 m	+200 m	190 m	+200 m		
Alice Street 60 km/h	Eastbound	85 m	+200m	130 m	+200m		
	Westbound	85 m	+200 m	130 m	+200 m		

Table 18: Minimum Sight Distance Requirements

Based on the above, the proposed Alice Street and Arthur Street entrances can be supported from a sight distance perspective.

10.0 RECOMMENDATIONS

The enclosed analysis results in the following key recommendations:

- Construct eastbound and westbound left-turn lanes at Arthur Street and Lansdowne Street
- Construct a westbound left turn lane at the proposed Arthur Street site access
- Consider extending the 50 km/h speed limit zone to the western limits of the proposed development
- Ongoing monitoring of intersection operations along Arthur Street and future consideration for a two-way centre left-turn lane to allow for two-stage gap acceptance.

11.0 CONCLUSIONS

The analysis contained within this report has resulted in the following key findings:

- Intersection analysis of the 2021 existing traffic volumes indicates the following:
 - All study intersections are operating at a Level of Service (LOS) "A" during the weekday a.m. and p.m. peak hours with the exception of Lansdowne Street South and Arthur Street which is expected to operate at a LOS of "C".
 - Synchro is unable to analyze a 5 legged intersection, so the intersection of Lansdowne Street South, Beaver Street and Alice Street was modeled as a 4 way stop. To do this, volumes on the section of Beaver Street between Alice Street and Louisa Street were redistributed to other applicable legs.
- Intersection analysis of the 2026 through 2041 future background traffic volumes indicates the following:
 - All study intersections are operating at a Level of Service (LOS) "A" during the weekday a.m. and p.m. peak hours with the exception of Lansdowne Street South and Arthur Street which is expected to operate at a LOS of "E" and "C" during the weekday a.m. and p.m. peak hours, respectively.
 - The maximum control delay of 39.2 seconds and volume-to-capacity ratio of 0.33 (NB), both forecasted for Arthur Street and Lansdowne Street South in the p.m. peak hour, indicate that the boundary road network is operating acceptably with excess capacity for increases in traffic volumes.
- The development is proposed to generate 115 and 149 two-way external primary trips in the weekday a.m. and p.m. peak hours, respectively, and 27 and 54 two-way pass-by trips in the a.m. and p.m. peak hours, respectively. As noted previously, the trip generation calculations were based on a previous version of the Draft Plan, which resulted in a forecasted trip generation of 3 and 2 less two-way trips in the a.m. and p.m. peak hours, respectively. As such, the findings and conclusions contained within this report remain valid when considering the final Draft Plan prepared by Montgomery Philip King Architect Inc, dated Februrary16, 2021.
- The requirement for auxiliary left-turn lanes were reviewed for the eastbound and westbound movements on Arthur Street. At the intersection of Lansdowne Street South and Arthur Street both the eastbound and westbound movements warrant left-turn lanes with 25 m of storage under 2041 future background conditions. A westbound left-turn lane with 25 m of storage is also warranted at the intersection of Arthur Street with the proposed site access. The geometric details related to the proposed turn-lanes would be confirmed during detailed design, however it is noted that the westbound left-turn lane at Lansdowne Street South can be accommodated within the existing pavement width.
- A signal warrant analysis was undertaken for the intersection of Lansdowne Street South and Arthur Street based on the 2041 future total traffic volumes. The analysis followed the procedures specified in Chapter 4 of the "Ontario Traffic Manual – Book 12", March 2012 for Justifications 1 to 3. Based on this approach, signals are not warranted at the intersection.
- Intersection analysis of the 2041 future total traffic volumes indicates the following:
 - o The study intersections are anticipated to continue operating with a LOS "B" or better in the a.m. and p.m. peak hours, with the exception of the two Arthur Street intersections.

- Lansdowne Street South and Arthur Street is anticipated to operate with a LOS "D" and "F" in the a.m. and p.m. peak hours, respectively. And the proposed Arthur Street site access is anticipated to operate with a LOS "C" and "D" in the weekday a.m. and p.m. peak hours, respectively.
- The above metrics indicate that the increase in traffic volumes on Arthur Street as a result of background traffic growth is anticipated to result in higher delay for the minor road approaches.
 - This is not atypical, and it is expected that most accesses along Arthur Street would experience similar delays.
- o It is recommended that ongoing monitoring of the study intersections should be completed as the future total volumes are based on a 20-year projection. Future consideration for a continuous two-way left-turn lane may be necessary for Arthur Street. This would allow for two-stage gap acceptance.
- A sensitivity analysis was completed analyzing the traffic operations assuming all traffic volumes utilize the Arthur Street site access. The sensitivity analysis was completed the 2041 future total traffic volumes and the results indicate the following:
 - The elimination of the Alice Street and Lansdowne Street South site accesses is anticipated to have a negligible impact on the operations of the intersection of Lansdowne Street South and Arthur Street.
 - o The proposed Arthur Street site access is anticipated to operate with a LOS "C" and "E" in the weekday a.m. and p.m. peak hours, respectively. This represents a maximum increase in control delay of 7.0 seconds when compared to the base 2041 future total scenario.
- The available sight distances at the proposed site accesses exceed the minimum requirements outlined in the Transportation Association of Canaa (TAC) Geometric Design Guide for Canadian Roads (GDGCR). Accordingly, the proposed site accesses can be supported from a sight distance perspective.

It is concluded that the traffic generated by the 125 Arthur Street development can be supported by the boundary road network, with the noted improvements.

The analysis contained within this report was completed based on a previous version of the Draft Plan. The findings and conclusions contained within this report remain valid when considering the final Draft Plan, as prepared by Montgomery Philip King Architect Inc, dated Februrary 16, 2021. The proposed Draft Plan Application can be supported from a traffic operations and safety

Prepared by,

C.F. CROZIER & ASSOCIATES INC.

Emma Howlett, E.I.T.
Engineering Intern, Transportation

C.F. CROZIER & ASSOCIATES INC.

Madeleine Ferguson, P.Eng. Manager of Transportation

MF/eh

J:\2100\2142-The Blue Meadows Inc\6059-125 Arthur St, TOBM\Reports\Traffic\2022.02.24_6059_TIS.docx

Traffic Impact Study February 2022

APPENDIX A

Terms of Reference Correspondence

Emma Howlett

From: Shaquille Cousins <scousins@thebluemountains.ca>

Sent: July 26, 2021 3:44 PM
To: Emma Howlett

Cc: Deanna Vickery; Madeleine Ferguson **Subject:** Terms of Reference: 125 Arthur Street

Attachments: Traffic Brief 1 of 4.PNG; Traffic Brief 2 of 4.PNG; Traffic Brief 3 of 4.PNG; Traffic Brief 4 of

4.PNG

Good Afternoon Emma,

Please see my responses to your inquiries below in red.

Study intersections

The TIS will review the following intersections:

- Lansdowne Street South and Arthur Street:
- Lansdowne Street South and Louisa Street West; and
- the Site Accesses

Note the 5-legged intersection of Beaver Street, Lansdowne St S and Alice St W cannot be analyzed with the Highway Capacity Manual therefore has been omitted from this study. We will commission turning movement counts from a specialty traffic counting firm. The cameras will be deployed on private property owned by the Client.

- -Please include the intersection of Alice Street/Peel Street in your review. With an additional entrance proposed on Alice Street please review and consider any upgrades that may be required at the afore mentioned intersection due to the increased traffic from the proposed site.
- -As the 5-legged intersection of Beaver Street, Lansdowne St S and Alice St W will not be included in the modelling, traffic is not to be considered as traveling there... volumes are to be shown travelling along other routes.

Analysis Periods and Scenarios

- Analysis of weekday A.M. and P.M. peak hours will be used to capture the peak hours associated with the proposed use.
- It is assumed that the development will be constructed within 5-years. Accordingly, horizon years of full build-out (2026) and 5 years beyond (2031) will be assessed.
- A growth rate of 1.62%, and 1% was established by studying MTO AADT and SADT data, respectively, on Highway 26 at Peel Street from 2010 to 2016. Accordingly, a growth rate of 1.5% compounded annually will be used to establish the future background traffic volumes.
- Please advise of any nearby developments that we should account for in our assessment.
- -Please extend the horizon year analysis to include 15 years beyond the assumed full build-out (2041).
- -Based on recent local growth it may be more appropriate to assume a 2% annual growth rate as opposed to the 1.5% suggested.
- -Please include the Towns of Thornbury development in your assessment (see attached excerpts from traffic brief for information purposes).
- -Please include the Lora Bay Heights development full buildout in the ultimate buildout scenario.
- -Please include a scenario that analyzes traffic movements solely entering and exiting the site from the proposed Arthur Street entrance.

Please be aware that although the section of Arthur Street adjacent to the project site is owned by The Town of the Blue Mountains, an MTO encroachment permit and general approval will likely be required.

Feel free to reach out to me if you had any additional questions.

Best Regards,



Shaquille Cousins, C.Tech

Development Engineering Reviewer Town of The Blue Mountains, 32 Mill Street, P.O. Box 310, Thornbury, ON NOH 2PO

Tel: 519-599-3131 ext. 279 | Fax: 519-599-7723

Email: scousins@thebluemountains.ca | Website: www.thebluemountains.ca | Website:

IMPORTANT INFORMATION


The Town of The Blue Mountains has reopened Town Hall to the public from 8:30 a.m. to 4:30 p.m. Monday to Friday. Customers are reminded that for in-depth service needs, such as planning services, building services, applying for a marriage license and the commissioning of documents, appointments are required. Appointments will need to be scheduled in advance by contacting the appropriate department. To contact a staff member, please call 519-599-3131 or email the appropriate department as listed on the staff directory of the Town website: www.thebluemountains.ca/staff-directory.cfm. Online services can also be accessed 24/7 by visiting: www.thebluemountains.ca/online-services.cfm. Council and Committee meetings will continue to take place virtually

until further notice.

Traffic Impact Study February 2022

APPENDIX B

Town of the Blue Mountains Official Plan Excerpts



APPENDIX C

Georgian Trail Map



APPENDIX D

Transit Maps and Schedules





Route 3 & 4 Highway 26

Owen Sound to The Blue Mountains

Adult (18+): \$5.00

Adult (55+) and student (6-17):

Children 5 and under: Free

Operating:

Wednesday to Sunday

Telephone Number: 226-910-1001 Website: www.grey.ca/gtr

Grey Transit Route - Schedules

ROUTE 1 SOUTHBOU	ND
(Owen Sound to Dund	alk)

Monday - Friday

Owen Sound Transit Terminal 1020 3rd Ave E, Owen Sound	Departure 6:45 AM	Departure 10:44 AM	Departure 5:47 PM
Stone Tree 318085 Hwy 6-10, Owen Sound	6:54 AM	10:53 AM	5:56 PM
Chatsworth Arena 5Toronto St., Chatsworth	7:08 AM	11:07 AM	6:10 PM
King Edward Park 75 Walker St, Markdale	7:32 AM	11:31 AM	6:34 PM
Trail Parking Lot Main St West, @ Scotland St, Markdale	7:39 AM	11:38 AM	6:41 PM
Grey Gables 206 Toronto St S, Markdale	7:46 AM	11:45 AM	6:48 PM
Huron Bay Co-Operative 774794 ON-10, Flesherton	7:54 AM	11:53 AM	6:56 PM
Flesherton Arena 103 ON-10, Flesherton	8:05 AM	12:04 PM	7:07 PM
Dundalk Arena 550 Main St E, Dundalk	Arrival 8:19 AM	Arrival 12:18 PM	Arrival 7:21 PM

ROUTE 1 NORTHBOUND (Dundalk to Owen Sound)

Monday - Friday

	wonday - Friday		
Dundalk Arena 550 Main St E, Dundalk	Departure 8:34 AM	Departure 12:22 PM	Departure 7:25 PM
Flesherton Arena 103 ON-10, Flesherton	8:52 AM	12:40 PM	7:43 PM
Huron Bay Co-Operative 774794 ON-10, Flesherton	9:03 AM	12:51 PM	7:54 PM
Grey Gables 206 Toronto St S, Markdale	9:11 AM	12:59 PM	8:02 PM
Trail Parking Lot Main St West, @ Scotland St, Markdale	9:18 AM	1:06 PM	8:09 PM
King Edward Park 75 Walker St, Markdale	9:25 AM	1:13 PM	8:16 PM
Chatsworth Arena 5 Toronto St., Chatsworth	9:49 AM	1:37 PM	8:40 PM
Stone Tree 318085 Hwy 6-10, Owen Sound	10:03 AM	1:51 PM	8:54 PM
Owen Sound Transit Terminal 1020 3rd Ave E, Owen Sound	Arrival 10:08 AM	Arrival 1:56 PM	Arrival 8:59 PM

Book your ride with GTR | Call 226-910-1001 to reserve your ticket or book online.

All rides must be booked in advance to ensure capacity and safety.

https://www.grey.ca/grey-transit-route | https://driverseatinc.com/greytransitroute/

ROUTE 2 SOUTHBOUND (Dundalk to Orangeville)

Monday - Friday

Dundalk Arena 550 Main St E, Dundalk	Departure 6:30 AM	Departure 8:34 AM	Departure 12:22 PM	Departure 5:21 PM
Fiddle Park Ln @ Greenwood Crescent, Shelburne	6:49 AM	8:53 AM	12:41 PM	5:40 PM
Victoria St. @ Red Front Store Ln. Shelburne	6:56 AM	9:00 AM	12:48 PM	5:47 PM
Hansen Blvd. @ First St. (Orangeville Mall & GO Bus) Orangeville	7:22 AM	9:26 AM	1:14 PM	6:13 PM
Broadway & Fourth Street (Transit Transfer Station) Orangeville	Arrival 7:28 AM	Arrival 9:32 AM	Arrival 1:20 PM	Arrival 6:19 PM

ROUTE 2 NORTHBOUND (Orangeville to Dundalk)

Monday - Friday

Broadway & Fourth Street (Transit Transfer Station) Orangeville	Departure 7:32 AM	Departure 9:36 AM	Departure 1:24 PM	Departure 6:23 PM
Hansen Blvd. @ First St. (Orangeville Mall & GO Bus) Orangeville	7:42 AM	9:46 AM	1:34 PM	6:33 PM
Victoria St. @ Red Front Store Ln. Shelburne	8:08 AM	10:12 AM	2:00 PM	6:59 PM
Fiddle Park Ln @ Greenwood Crescent Shelburne	8:15 AM	10:19 AM	2:07 PM	7:06 PM
Dundalk Arena 550 Main St. E., Dundalk	Arrival 8:30 AM	Arrival 10:34 AM	Arrival 2:22 PM	Arrival 7:21 PM



ROUTE 3 EASTBOUND (Owen Sound to Meaford)

Wednesday - Sunday

Owen Sound Transit Terminal	Departure	Departure	Departure	Departure	Departure	Departure
1020 3rd Ave. E., Owen Sound	6:30 AM	8:06 AM	9:39 AM	11:21 AM	4:30 PM	6:06 PM
Woodford Community Center 107 Woodford Cres, Owen Sound	express (no stop)	8:27 AM	10:00 AM	express (no stop)	express (no stop)	6:27 PM
Don Bumstead & Family Medical Clinic 206106, ON-26, Meaford	express (no stop)	8:39 AM	10:12 AM	express (no stop)	express (no stop)	6:39 PM
N Sykes St. @ Nelson St W,	Arrival	Arrival	Arrival	Arrival	Arrival	Arrival
Meaford	7:00 AM	8:42 AM	10:15 AM	11:51 AM	5:00 PM	6:42 PM

ROUTE 3 WESTBOUND (Meaford to Owen Sound)

Wednesday - Sunday

		-	-		
N Sykes St. @ Nelson St W, Meaford	Departure 8:46 AM	Departure 10:28 AM	Departure 11:55 AM	No Stop	Departure 6:46 PM
Don Bumstead & Family Medical Centre 206106, ON-26, Meaford	8:53 AM	10:35 AM	12:02 PM	No Stop	6:53 PM
Smart Centres Bus Stop 16th St E @ 18th Ave E, Owen Sound	9:16 AM	10:58 AM	12:25 PM	Pick Up Only 4:15 PM	7:16 PM
Grey Bruce Health Services Owen Sound Hospital 1800 8th St E, Owen Sound	9:23 AM	11:05 AM	12:32 PM	Pick Up Only 4:18 PM	7:23 PM
Georgian College 8th St. E., Owen Sound	9:30 AM	11:12 AM	12:39 PM	Pick Up Only 4:21 PM	7:30 PM
Owen Sound Transit Terminal 1020 3rd Ave. E., Owen Sound	Arrival 9:35 AM	Arrival 11:17 AM	Arrival 12:44 PM	Arrival 4:26 PM	Arrival 7:35 PM

Book your ride with GTR | Call 226-910-1001 to reserve your ticket or book online.

All rides must be booked in advance to ensure capacity and safety.

https://www.grey.ca/grey-transit-route | https://driverseatinc.com/greytransitroute/

ROUTE 4 EASTBOUND (Meaford to Town of the Blue Mountains)

Wednesday - Sunday

Downtown Meaford N Sykes St. @ Nelson St W, Meaford	Departure 7:04 AM	Departure 8:46 AM	Departure 5:04 PM	Departure 6:46 PM
Masse's Independent 206497 ON-26, Meaford	7:11 AM	8:53 AM	5:11 PM	6:53 PM
Thornbury Foodland 105 Arthur St W, Thombury	7:21 AM	9:03 AM	5:21 PM	7:03 PM
Town of Blue Mountains Municipal Office 32 Mill St, The Blue Mountains	7:27 AM	9:09 AM	5:27 PM	7:09 PM
Blue Mountain Community Health Centre 78 King St E, Thornbury	7:34 AM	9:16 AM	5:34 PM	7:16 PM
Blue Mountain Village 156 Jozo Weider Blvd.	Arrival 7:51 AM	Arrival 9:33 AM	Arrival 5:51 PM	Arrival 7:33 PM

ROUTE 4 WESTBOUND (Town of the Blue Mountains to Meaford)

Wednesday - Sunday

Blue Mountain Village 156 Jozo Weider Blvd.	Departure 7:55 AM	Departure 9:37 AM	Departure 5:55 PM	Departure 7:37 PM
Blue Mountain Community Health Centre 78 King St E, Thornbury	8:16 AM	9:58 AM	6:16 PM	7:58 PM
Town of Blue Mountains Municipal Office 32 Mill St, The Blue Mountains	8:23 AM	10:05 AM	6:23 PM	8:05 PM
Thornbury Foodland 105 Arthur St W, Thornbury	8:29 AM	10:11 AM	6:29 PM	8:11 PM
Masse's Independent 206497 ON-26, Meaford	8:39 AM	10:21 AM	6:39 PM	8:21 PM
Downtown Meaford N Sykes St. @ Nelson St W, Meaford	Arrival 8:42 AM	Arrival 10:24 AM	Arrival 6:42 PM	8:28 PM
Owen Sound Transit Terminal 1020 3rd Ave. E., Owen Sound				Arrival 8:58 PM



ROUTE 5 NORTHBOUND (Owen Sound to Wiarton to Sauble Beach)

Friday – Monday (May 21 to September 6, 2021 *Including Holiday Mondays*)

Owen Sound Transit Terminal 1020 3rd Ave E, Owen Sound	Departure 7:17 AM	Departure 12:17 PM	Departure 8:17 PM
Bergen's No Frills 1020 10th St W, Owen Sound	7:27 AM	12:27 PM	8:27 PM
Shallow Lake & District Community Centre 550 Princess St, Shallow Lake	7:41 AM	12:41 PM	8:41 PM
South Bruce Peninsula Visitor Centre 50 ON-6, Hepworth	7:47 AM	12:47 PM	8:47 PM
Wiarton Foodland 425 Berford St, Wiarton	7:59 AM	12:59 PM	express (no stop)
Downtown Wiarton Louisa St, @ George St, Wiarton	8:07 AM	1:07 PM	express (no stop)
Sauble Beach 104 2nd Ave N, Sauble Beach	Arrival 8:31 AM	Arrival 1:31 PM	Arrival 9:02 PM

ROUTE 5 SOUTHBOUND (Sauble Beach to Wiarton to Owen Sound)

Friday – Monday (May 21 to September 6, 2021 *Including Holiday Mondays*)

Sauble Beach 104 2nd Ave N, Sauble Beach	Departure 8:33 AM	Departure 1:33 PM	Departure 9:04 PM
Downtown Wiarton Louisa St, @ George St, Wiarton	express (no stop)	1:59 PM	9:30 PM
Wiarton Foodland 425 Berford St, Wiarton	express (no stop)	2:07 PM	9:38 PM
South Bruce Peninsula Visitor Centre 50 ON-6, Hepworth	8:45 AM	2:19 PM	9:50 PM
Shallow Lake & District Community Centre 550 Princess St, Shallow Lake	8:51 AM	2:25 PM	9:56 PM
Bergen's No Frills 1020 10th St W, Owen Sound	9:05 AM	2:39 PM	10:10 PM
Owen Sound Transit Terminal 1020 3rd Ave E, Owen Sound	Arrival 9:13 AM	Arrival 2:47 PM	Arrival 10:18 PM

Book your ride with GTR | Call 226-910-1001 to reserve your ticket or book online.

All rides must be booked in advance to ensure capacity and safety.

https://www.grey.ca/grey-transit-route | https://driverseatinc.com/greytransitroute/

ROUTE 6 WESTBOUND (Flesherton / Durham - Walkerton)

Monday and Friday

Flesherton Arena	Departure	Departure	Departure
103 ON-10, Flesherton	8:05 AM	12:41 PM	5:04 PM
Durham Credit Union 118 Queen St S, Durham	8:29 AM	1:05 PM	5:25 PM
Hanover Municipal Office 341 10th St, Hanover	8:50 AM	1:26 PM	5:46 PM
Downtown Walkerton	Arrival	Arrival	Arrival
306 Scott St, Walkerton	9:03 AM	1:39 PM	5:59 PM

ROUTE 6 EASTBOUND (Walkerton - Durham / Flesherton)

Monday and Friday

Downtown Walkerton	Departure	Departure	Departure	Departure
306 Scott St, Walkerton	7:03 AM	9:07 AM	1:43 PM	6:03 PM
Hanover Municipal Office 341 10th St, Hanover	7:20 AM	9:24 AM	2:00 PM	6:20 PM
Durham Credit Union 118 Queen St S, Durham	7:41 AM	9:45 AM	2:21 PM	6:41 PM
Flesherton Arena	Arrival	Arrival	Arrival	Arrival
103 ON-10, Flesherton	8:01 AM	10:05 AM	2:41 PM	7:01 PM



Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX E

Traffic Data

													Turnin	g Movem	ent C	ount (3	3 . ALICI	EST&	BEA	VER ST / LAN	SDOWN	ST S)														
Chart Time			LA	N Approa	ach NE ST S					NE	Approac EAVER ST	h Г					E Appro	ach ST						W Approx	ach ST						SW Approa				Int. Total (15 min)	Int. Total (1 hr)
Start Time	Right N:W	Bear Right N:SW	Bear Left N:NE	Left N:E	UTurn N:N	Peds N:	Approach Total	Hard Right NE:W	Bear Right NE:N	Thru NE:SW	Hard Left NE:E	UTurn Pe NE:NE N		Hard Right E:NE	Right E:N	Thru E:W	Hard Left E:SW	UTurn E:E	Peds E:	Approach Total	Hard Right W:SW	Thru W:E	Left W:N	Hard Left W:NE	UTurn W:W		Approach Total	Hard Right SW:E	Thru SW:NE	Bear Left SW:N	Hard Left SW:W	UTurn SW:SW		Approach Total		
06:00:00	0	0	0	0	0	0	0	0	0	0	0	0 0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	1	0	0	0	1	2	
06:15:00	0	0	1	0	0	0	1	0	0	0	0	0 0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	0	2	3	
06:30:00	0	1	0	0	0	0	1	1	0	0	0	0 0	1	0	1	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	0	0	1	4	
06:45:00	0	1	0	0	0	0	1	0	0	1	0	0 0	1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	1	0	0	1	2	4	13
07:00:00	0	0	0	1	0	0	1	0	0	2	0	0 0	2	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	1	4	15
07:15:00	0	1	1	0	0	0	2	0	0	3	0	0 0	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	0	0	0	0	4	9	21
07:30:00	0	0	1	1	0	0	2	0	0	6	0	0 0	6	1	1	2	1	0	0	5	0	0	0	0	0	0	0	1	2	0	0	0	1	3	16	33
07:45:00	0	1	0	0	0	0	1	0	0	3	0	0 1	3	1	0	0	0	0	1	1	0	0	0	0	0	0	0	2	1	0	0	0	1	3	8	37
08:00:00	0	0	0	1	0	2	1	0	0	2	0	0 2	2	0	0	2	1	0	1	3	0	0	0	0	0	0	0	0	3	0	0	0	0	3	9	42
08:15:00	0	2	0	1	0	3	3	0	1	2	0	0 6	3	1	0	0	1	0	1	2	0	2	0	0	0	0	2	1	2	1	1	0	1	5	15	48
08:30:00	0	0	0	0	0	1	0	0	0	6	0	0 1	6	1	0	1	1	0	1	3	0	1	0	0	0	0	1	0	3	1	0	0	0	4	14	46
08:45:00	0	1	1	2	0	0	4	0	0	3	0	0 2	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	3	2	0	0	1	6	13	51
09:00:00	0	1	0	1	0	0	2	0	0	3	0	0 3	3	0	1	2	1	0	2	4	0	0	0	0	0	2	0	2	1	0	0	0	0	3	12	54
09:15:00	0	1	1	2	0	0	4	0	0	3	0	0 0	3	0	0	0	1	0	0	1	0	1	0	0	0	0	1	1	4	1	0	0	0	6	15	54
09:30:00	1	1	0	1	0	0	3	0	0	2	0	0 2	2	1	1	0	0	0	1	2	2	1	1	0	0	0	4	3	1	1	0	0	0	5	16	56
09:45:00	0	2	0	0	0	0	2	1	0	1	0	0 2	2	0	0	0	0	0	2	0	0	0	0	0	0	0	0	2	5	0	0	0	0	7	11	54
***BREAK	***																																			
15:00:00	1	6	0	1	0	0	8	0	0	4	0	0 0	4	1	0	1	1	0	0	3	0	1	0	0	0	0	1	1	6	1	0	0	0	8	24	
15:15:00	0	6	0	1	0	0	7	0	0	4	1	0 0	5	1	2	1	1	0	0	5	0	0	0	0	0	0	0	1	3	3	0	0	0	7	24	
15:30:00	0	3	0	0	0	0	3	0	0	2	0	0 0		0	0	3	1	0	3	4	0	1	0	1	0	3	2	1	4	5	0	0	0	10	21	
15:45:00	0	7	0	0	0	0	7	0	0	7	0	0 0		0	2	0	3	0	0	5	0	1	0	0	0	0	1	2	1	3	0	0	0	6	26	95
16:00:00	0	1	0	2	0	0	3	1	0	5	1	0 0		0	4	2	3	0	2	9	0	0	1	0	0	0	1	0	5	0	1	0	1	6	26	97
16:15:00	0	4	0	0	0	0	4	0	2	2	0	0 1		1	1	2	1	0	1	5	0	0	0	0	0	0	0	2	4	3	0	0	2	9	22	95
16:30:00	0	1	0	0	0	2	1	0	0	4	1	0 2		0	1	1	4	0	1	6	0	0	0	0	0	0	0	0	4	3	0	0	0	7	19	93
16:45:00	0	4	0	1	0	2	5	1	0	5	1	0 0		2	1	0	1	0	1	4	0	0	0	0	0	0	0	1	7	4	0	0	1	12	28	95
17:00:00	1	4	0	2	0	0	7	0	0	5	0	0 2		0	2	2	1	0	0	5	0	0	0	0	0	0	0	0	3	5	0	0	0	8	25	94
17:15:00	0	2	0	2	0	1	4	0	0	13	2	0 0		1	0	1	1	0	0	3	0	1	0	0	0	0	1	2	3	0	0	0	1	5	28	100
17:30:00	1	3	0	2	0	0	6	0	0	2	0	0 0		1	0	0	0	0	0	1	0	0	0	0	0	0	0	1	2	1	0	1	0	5	14	95
17:45:00	0	4	0	0	0	2	4	0	0	1 -	0	0 2		0	0	1	1	0	0	2	0	0	0	0	0	0	0	0	0	1	0	0	0	1	8	75
18:00:00	0	1	0	1	0	0	2	0	0	5	0	0 0		0	2	0	2	0	0	4	0	0	0	0	0	0	0	0	2	2	0	0	0	4	15	65
18:15:00	0	2		2	_	0	4	0	0	7	0	0 0		1	0		3	0		4	0	2		0		0	2	0	5	2	0	0	0	7	24	61
18:30:00	0	2	0	0	_	0	2	0	0	3	1	0 1		1	1		0	0		2	0	0	0	0	0	0	0	1	3	0	0	0	0	4	12	59
18:45:00	0	2	0	0		2	2	0	0	2	0	0 4		0	0		1	0		2	0	0	0	0		0	0	0	4	1	0	0	0	5	11	62
Grand Total				24		15	97	4	3	108		0 3	122	14		23		0	18	87	2		2	1		5	16	26	88	43	2	1	10	160	482	-
Approach%				24.7%			-	3.3%	2.5%	88.5%	5.7%	0%	-				34.5%	0%		-			12.5%		0%		-	16.3%	55%	26.9%	1.3%	0.6%		-	-	-
Totals %		13.3%	1%	5%	0%		20.1%	0.8%	0.6%	22.4%	1.5%	0%	25.3%	2.9%		4.8%		0%		18%	0.4%	2.3%		0.2%	0%		3.3%	5.4%	18.3%	8.9%	0.4%	0.2%		33.2%	-	-
Heavy	0	2 10/	3	1			-	1	0	4 2 70/	0	0	-	7 19/	0	1	0	0		-	0	1	0	0	0		-	2 7 79/	6	0	1	0		=	-	=
Heavy %	0%	3.1%	60%	4.2%			-	25%	0%	3.7%	0%	0%	-	7.1%	0%	4.3%	0%	0%		-	0%	9.1%	0%	0%	0%		-	7.7%	6.8%	0%	50%	0%		-	-	-
Bicycles Bicycle %	-	-	-	-			-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-	-		-	-	-	-	-	-		-	-	-
Bicycle %	-	-	-	-	-		-	-	-	-	-	-	-	-	-	-	-	-		-	-	-	-	-	-		-	-	-	-	-	-		-	-	-

Crozier & Associates SUITE 301 40 HURON STREET COLLINGWOOD ONTARIO, L9Y 4R3 CANADA

CRA21P9B

													Р	Peak Hour: (08:45 AM	- 09:4	5 AM	Weath	er: Bro	ken Cl	ouds (15.17	°C)														
Start Time			LAN	N Appro	ach NE ST S					N	IE Approa	ch ST						E Appro	ach ST						W Appr ALICE	oach					,	SW Approa	ach ST			Int. Total (15 min)
	Right	Bear Right	Bear Left	Left	UTurn	Peds Approa	ch Total	Hard Right	Bear Right	Thru	Hard Left	UTurn	Peds A	Approach Total	Hard Right	Right	Thru	Hard Left	UTurn	Peds	Approach Total	Hard Right	Thru	Left	Hard Left	UTurn	Peds	Approach Total	Hard Right	Thru	Bear Left	Hard Lef	t UTurn	Peds Appr	oach Total	
08:45:00	0	1	1	2	0	0	1	0	0	3	0	0	2	3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1	3	2	0	0	1	6	13
09:00:00	0	1	0	1	0	0	2	0	0	3	0	0	3	3	0	1	2	1	0	2	4	0	0	0	0	0	2	0	2	1	0	0	0	0	3	12
09:15:00	0	1	1	2	0	0	1	0	0	3	0	0	0	3	0	0	0	1	0	0	1	0	1	0	0	0	0	1	1	4	1	0	0	0	6	15
09:30:00	1	1	0	1	0	0	3	0	0	2	0	0	2	2	1	1	0	0	0	1	2	2	1	1	0	0	0	4	3	1	1	0	0	0	5	16
Grand Total	1	4	2	6	0	0	3	0	0	11	0	0	7	11	1	2	2	2	0	3	7	2	2	1	0	0	2	5	7	9	4	0	0	1	20	56
Approach%	7.7%	30.8%	15.4%	46.2%	0%		-	0%	0%	100%	0%	0%		-	14.3%	28.6%	28.6%	28.6%	0%		-	40%	40%	20%	0%	0%		-	35%	45%	20%	0%	0%		-	-
Totals %	1.8%	7.1%	3.6%	10.7%	0%	23	2%	0%	0%	19.6%	0%	0%		19.6%	1.8%	3.6%	3.6%	3.6%	0%		12.5%	3.6%	3.6%	1.8%	0%	0%		8.9%	12.5%	16.1%	7.1%	0%	0%	:	35.7%	-
PHF	0.25	1	0.5	0.75	0	0	81	0	0	0.92	0	0		0.92	0.25	0.5	0.25	0.5	0		0.44	0.25	0.5	0.25	0	0		0.31	0.58	0.56	0.5	0	0		0.83	-
Heavy		1	2	0	0		3	0	0	0	0	0		0	0	0		0	0		0		<u>-</u> -		0	0		1	1	0	0		0		1	
Heavy %	0%	25%	100%	0%	0%		1%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	50%	0%	0%	0%		20%	14.3%	0%	0%	0%	0%		5%	-
Lights	1	3	0	6	0		0	0	0	11	0	0		11	1	2	2	2	0		7	1	1	1	0	0		3	6	8	3	0	0		17	
Lights %	100%	75%	0%	100%	0%	76	9%	0%	0%	100%	0%	0%		100%	100%	100%	100%	100%	0%		100%	50%	50%	100%	0%	0%		60%	85.7%	88.9%	75%	0%	0%		85%	-
Single-Unit Trucks	0	1	2	0	0		3	0	0	0	0	0		0	0	0	0	0	0		0	0	1	0	0	0		1	0	0	0	0	0		0	-
Single-Unit Trucks %	0%	25%	100%	0%	0%	23	1%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	50%	0%	0%	0%		20%	0%	0%	0%	0%	0%		0%	-
Buses	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	1	0	0	0	0		1	-
Buses %	0%	0%	0%	0%	0%	(%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	14.3%	0%	0%	0%	0%		5%	-
Articulated Trucks	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	-
Articulated Trucks %	0%	0%	0%	0%	0%	(%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	-
Bicycles on Road	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	1	0	0	0	0		1	0	1	1	0	0		2	-
Bicycles on Road %	0%	0%	0%	0%	0%	(%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	50%	0%	0%	0%	0%		20%	0%	11.1%	25%	0%	0%		10%	-
Pedestrians	-	-	-	-	-	0	-	-	-	-	-	-	7	-	-	-	-	-	-	3	-	-	-	-	-	-	2	-	-	-	-	-	-	1	-	-
Pedestrians%	-	-	-	-	-	0%		-	-	-	-	- 5	53.8%		-	-	-	-	-	23.1%		-	-	-	-	-	15.4%		-	-	-	-	-	7.7%		-

Crozier & Associates SUITE 301 40 HURON STREET COLLINGWOOD ONTARIO, L9Y 4R3 CANADA

															1:30 PM -							•													
start Time			LA	N Appro	oach NE ST S	3				N	IE Approac BEAVER S	eh T						E Approa	ich ST						W Appro	ach ST					SW Appro	ach ST			In (1
	Right	Bear Right	Bear Left	Left	UTurr	n Peds	Approach Total	Hard Right	Bear Right	Thru	Hard Left	UTurn	Peds /	Approach Total	Hard Right	Right	Thru	Hard Left	UTurn	Peds	Approach Total	Hard Right	Thru	Left F	Hard Left	UTurn	Peds Approach Total	Hard Right	Thru	Bear Left	Hard Left	UTurn	Peds	Approach Total	.1
16:30:00	0	1	0	0	0	2	1	0	0	4	1	0	2	5	0	1	1	4	0	1	6	0	0	0	0	0	0 0	0	4	3	0	0	0	7	\top
16:45:00	0	4	0	1	0	2	5	1	0	5	1	0	0	7	2	1	0	1	0	1	4	0	0	0	0	0	0 0	1	7	4	0	0	1	12	T
17:00:00	1	4	0	2	0	0	7	0	0	5	0	0	2	5	0	2	2	1	0	0	5	0	0	0	0	0	0 0	0	3	5	0	0	0	8	T
17:15:00	0	2	0	2	0	1	4	0	0	13	2	0	0	15	1	0	1	1	0	0	3	0	1	0	0	0	0 1	2	3	0	0	0	1	5	\top
rand Total	1	11	0	5	0	5	17	1	0	27	4	0	4	32	3	4	4	7	0	2	18	0	1	0	0	0	0 1	3	17	12	0	0	2	32	
proach%	5.9%	64.7%	0%	29.4%	0%		-	3.1%	0%	84.4%	12.5%	0%		-	16.7%	22.2%	22.2%	38.9%	0%		-	0%	100%	0%	0%	0%	-	9.4%	53.1%	37.5%	0%	0%		-	
otals %	1%	11%	0%	5%	0%		17%	1%	0%	27%	4%	0%		32%	3%	4%	4%	7%	0%		18%	0%	1%	0%	0%	0%	1%	3%	17%	12%	0%	0%		32%	
PHF	0.25	0.69	0	0.63	0		0.61	0.25	0	0.52	0.5	0		0.53	0.38	0.5	0.5	0.44	0		0.75	0	0.25	0	0	0	0.25	0.38	0.61	0.6	0	0		0.67	
Heavy	0	1	0	0	0		1	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0	0	0	1	0	0	0		1	
leavy %	0%	9.1%	0%	0%	0%		5.9%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%	0%	0%	5.9%	0%	0%	0%		3.1%	
Lights	1	10	0	5	0		16	1	0	27	4	0		32	3	4	4	6	0		17	0	0	0	0	0	0	3	16	12	0	0		31	-
ights %	100%	90.9%	0%	100%	0%		94.1%	100%	0%	100%	100%	0%		100%	100%	100%	100%	85.7%	0%		94.4%	0%	0%	0%	0%	0%	0%	100%	94.1%	100%	0%	0%		96.9%	
-Unit Trucks	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0	0		0	
Unit Trucks %	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%		0%	
Buses	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0	0	0	0	0	0	0		0	
Buses %	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%	0%		0%	
lated Trucks	0	1	0	0	0		1	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	0	0	0	0	1	0	0	0		1	
ated Trucks %	0%	9.1%	0%	0%	0%		5.9%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	0%	0%	0%	0%	5.9%	0%	0%	0%		3.1%	
les on Road	0	0	0	0	0		0	0	0	0	0	0		0	0	0	0	1	0		1	0	1	0	0	0	1	0	0	0	0	0		0	
es on Road % destrians	0%	0%	0%	0%	0%	5	0%	0%	0%	0%	0%	0%		0%	0%	0%	0%	14.3%	0%		5.6%	0%	100%	0%	0%	0%	100%	0%	0%	0%	0%	0%		0%	


- - - - - 15.4%





Page 4 of 5





Crozier & Associates SUITE 301 40 HURON STREET COLLINGWOOD ONTARIO, L9Y 4R3 CANADA

Turning Movement Count (4 . ALICE ST & PEEL ST)

Start Time			N Ap PE	proach EL ST				E A _I	oproach CE ST W				S App	oroach EL ST		Int. Total (15 min)	Int. Total (1 hr)
Start Time	Thru N:S	Left N:E	UTurn N:N	Peds N:	Approach Total	Right E:N	Left E:S	UTurn E:E	Peds E:	Approach Total	Right S:E	Thru S:N	UTurn S:S	Peds S:	Approach Total		
06:00:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
06:15:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
06:30:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
06:45:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
07:00:00	0	0	0	0	0	0	0	0	1	0	0	0	0	0	0	0	0
07:15:00	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	1
07:30:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	1
07:45:00	0	0	0	0	0	0	0	0	0	0	1	2	0	0	3	3	4
08:00:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4
08:15:00	1	0	0	0	1	0	0	0	0	0	0	1	0	0	1	2	5
08:30:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5
08:45:00	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	3
09:00:00	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	4
09:15:00	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	3
09:30:00	1	0	0	0	1	0	1	0	1	1	1	0	0	0	1	3	6
09:45:00	1	0	0	0	1	0	0	0	2	0	0	0	0	0	0	1	6
***BREAK	***					-											
15:00:00	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0	1	
15:15:00	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	
15:30:00	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	1	
15:45:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	3
16:00:00	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1	3
16:15:00	1	0	1	0	2	0	0	0	0	0	0	1	0	0	1	3	5
16:30:00	0	0	0	0	0	0	1	0	0	1	0	1	0	0	1	2	6
16:45:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	6
17:00:00	2	0	0	0	2	0	1	0	0	1	0	1	0	0	1	4	9
17:15:00	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	7
17:30:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5
17:45:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	5
18:00:00	0	0	0	0	0	0	0	0	0	0	0	2	0	0	2	2	3
18:15:00	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	1	3
18:30:00	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	4
18:45:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4




Grand Total	10	1	1	0	12	0	3	0	4	3	4	12	0	0	16	31	-
Approach%	83.3%	8.3%	8.3%		-	0%	100%	0%		-	25%	75%	0%		-	-	-
Totals %	32.3%	3.2%	3.2%		38.7%	0%	9.7%	0%		9.7%	12.9%	38.7%	0%		51.6%	-	-
Heavy	0	0	0		-	0	0	0		-	0	2	0		-	-	-
Heavy %	0%	0%	0%		-	0%	0%	0%		-	0%	16.7%	0%		-	-	-
Bicycles	-	-	-		-	-	-	-		-	-	-	-		-	-	-
Bicycle %	-	-	-		-	-	-	_		-	-	-	-		-	-	-

					Peak Hour: 0	9:00 AM	- 10:00 A	M Wea	ather: Br	oken Clouds (15.17	7 °C)					
Start Time				pproach EEL ST					proach CE ST W					oroach EL ST		Int. Total (15 min)
	Thru	Left	UTurn	Peds	Approach Total	Right	Left	UTurn	Peds	Approach Total	Right	Thru	UTurn	Peds	Approach Total	
09:00:00	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1
09:15:00	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	1
09:30:00	1	0	0	0	1	0	1	0	1	1	1	0	0	0	1	3
09:45:00	1	0	0	0	1	0	0	0	2	0	0	0	0	0	0	1
Grand Total	2	0	0	0	2	0	1	0	3	1	1	2	0	0	3	6
Approach%	100%	0%	0%		-	0%	100%	0%		-	33.3%	66.7%	0%	'	-	-
Totals %	33.3%	0%	0%		33.3%	0%	16.7%	0%		16.7%	16.7%	33.3%	0%		50%	-
PHF	0.5	0	0		0.5	0	0.25	0		0.25	0.25	0.5	0		0.75	-
Heavy	0	0	0		0	0	0	0		0	0	1	0		1	
Heavy %	0%	0%	0%		0%	0%	0%	0%		0%	0%	50%	0%		33.3%	-
Lights	2	0	0		2	0	1	0		1	0	1	0		1	
Lights %	100%	0%	0%		100%	0%	100%	0%		100%	0%	50%	0%		33.3%	-
Single-Unit Trucks	0	0	0		0	0	0	0		0	0	1	0		1	-
Single-Unit Trucks %	0%	0%	0%		0%	0%	0%	0%		0%	0%	50%	0%		33.3%	-
Buses	0	0	0		0	0	0	0		0	0	0	0		0	-
Buses %	0%	0%	0%		0%	0%	0%	0%		0%	0%	0%	0%		0%	-
Bicycles on Road	0	0	0		0	0	0	0		0	1	0	0		1	-
Bicycles on Road %	0%	0%	0%		0%	0%	0%	0%		0%	100%	0%	0%		33.3%	-
Pedestrians	-	-	-	0	-	-	-	-	3	-	-	-	-	0	-	-
Pedestrians%	-	-	-	0%		-	-	-	100%		-	-	-	0%		-

					Peak Hour: 04:	15 PM -	05:15 PM	Weath	ner: Ove	rcast Clouds (22.45	5 °C)					
Start Time			N A	pproach EL ST					proach E ST W					proach EL ST		Int. Tota (15 min
	Thru	Left	UTurn	Peds	Approach Total	Right	Left	UTurn	Peds	Approach Total	Right	Thru	UTurn	Peds	Approach Total	
16:15:00	1	0	1	0	2	0	0	0	0	0	0	1	0	0	1	3
16:30:00	0	0	0	0	0	0	1	0	0	1	0	1	0	0	1	2
16:45:00	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
17:00:00	2	0	0	0	2	0	1	0	0	1	0	1	0	0	1	4
Grand Total	3	0	1	0	4	0	2	0	0	2	0	3	0	0	3	9
Approach%	75%	0%	25%		-	0%	100%	0%			0%	100%	0%			-
Totals %	33.3%	0%	11.1%		44.4%	0%	22.2%	0%		22.2%	0%	33.3%	0%		33.3%	-
PHF	0.38	0	0.25		0.5	0	0.5	0		0.5	0	0.75	0		0.75	-
Heavy	0	0	0		0	0	0	0		0	0	0	0		0	
Heavy %	0%	0%	0%		0%	0%	0%	0%		0%	0%	0%	0%		0%	-
Lights	3	0	1		4	0	2	0		2	0	3	0		3	
Lights %	100%	0%	100%		100%	0%	100%	0%		100%	0%	100%	0%		100%	-
Single-Unit Trucks	0	0	0		0	0	0	0		0	0	0	0		0	-
Single-Unit Trucks %	0%	0%	0%		0%	0%	0%	0%		0%	0%	0%	0%		0%	-
Buses	0	0	0		0	0	0	0		0	0	0	0		0	-
Buses %	0%	0%	0%		0%	0%	0%	0%		0%	0%	0%	0%		0%	-
Bicycles on Road	0	0	0		0	0	0	0		0	0	0	0		0	-
Bicycles on Road %	0%	0%	0%		0%	0%	0%	0%		0%	0%	0%	0%		0%	-
Pedestrians	-	-	-	0	-	-	-	-	0	-	-	-	-	0	-	-
Pedestrians%	-	-	-	0%		-	-	-	0%		-	-	-	0%		-


Crozier & Associates SUITE 301 40 HURON STREET COLLINGWOOD ONTARIO, L9Y 4R3 CANADA

Peak Hour: 09:00 AM - 10:00 AM Weather: Broken Clouds (15.17 °C)



Crozier & Associates SUITE 301 40 HURON STREET COLLINGWOOD ONTARIO, L9Y 4R3 CANADA

Peak Hour: 04:15 PM - 05:15 PM Weather: Overcast Clouds (22.45 °C)



Turning Movement Count Location Name: ARTHUR ST (HWY 26) & LANSDOWNE ST Date: Thu, Oct 14, 2021 Deployment Lead: Theo Daglis

									Tur	ning Mo	oveme	nt Count (1 . AF	THUR	ST (HW	/Y 26) 8	LANS	OOWN	E ST)								
Start Time			LA	N Approac	h STS				ART	E Approac HUR ST (H	h WY 26)				LA	S Approad	ch STS				ART	W Approac	ch WY 26)		Int. Total (15 min)	Int. Total (1 hr)
Start Time	Right N:W	Thru N:S	Left N:E	UTurn N:N	Peds N:	Approach Total	Right E:N	Thru E:W	Left E:S	UTurn E:E	Peds E:	Approach Total	Right S:E	Thru S:N	Left S:W	UTurn S:S	Peds S:	Approach Total	Right W:S	Thru W:E	Left W:N	UTurn W:W	Peds W:	Approach Total		
06:00:00	0	0	1	0	0	1	0	12	0	0	0	12	0	0	0	0	0	0	0	21	0	0	0	21	34	
06:15:00	0	0	0	0	0	0	0	8	2	0	0	10	1	0	1	0	0	2	1	29	0	0	0	30	42	
06:30:00	0	0	0	0	0	0	0	26	1	0	0	27	1	0	1	0	0	2	1	37	0	0	1	38	67	
06:45:00	1	0	0	0	0	1	0	24	0	0	0	24	0	1	0	0	0	1	3	49	0	0	0	52	78	221
07:00:00	0	0	1	0	0	1	0	35	1	0	0	36	0	0	1	0	0	1	3	61	1	0	0	65	103	290
07:15:00	0	0	2	0	0	2	1	52	1	0	0	54	2	0	0	0	0	2	1	77	0	0	0	78	136	384
07:30:00	0	0	0	0	0	0	4	57	1	0	0	62	1	0	1	0	0	2	0	81	0	0	1	81	145	462
07:45:00	0	0	1	0	1	1	1	63	1	0	1	65	0	0	0	0	0	0	1	103	1	0	1	105	171	555
08:00:00	0	0	2	0	0	2	0	71	0	0	0	71	0	0	0	0	0	0	0	80	1	0	0	81	154	606
08:15:00	1	0	1	0	0	2	0	57	0	0	2	57	1	1	0	0	0	2	1	91	0	0	0	92	153	623
08:30:00	1	0	2	0	0	3	1	66	1	0	1	68	0	0	1	0	0	1	0	82	1	0	0	83	155	633
08:45:00	4	1	2	0	0	7	0	84	1	0	0	85	1	3	1	0	0	5	1	102	0	0	0	103	200	662
09:00:00	1	1	0	0	0	2	3	64	1	0	0	68	0	1	1	0	0	2	0	84	0	0	0	84	156	664
09:15:00	0	0	1	0	0	1	1	73	3	0	0	77	0	0	0	0	0	0	1	90	2	0	0	93	171	682
09:30:00	1	0	1	0	0	2	2	67	1	0	2	70	1	2	1	0	0	4	1	84	2	0	0	87	163	690
09:45:00	2	0	1	0	1	3	4	81	1	0	0	86	0	0	2	0	0	2	2	87	1	0	1	90	181	671
***BREAK	***																									
15:00:00	2	0	4	0	0	6	1	86	5	0	0	92	1	0	2	0	0	3	1	94	4	0	0	99	200	
15:15:00	1	1	2	0	0	4	1	92	4	0	0	97	0	2	4	0	0	6	2	111	1	0	0	114	221	
15:30:00	1	1	4	0	0	6	0	122	2	0	0	124	2	1	1	0	0	4	1	92	2	0	0	95	229	
15:45:00	2	0	2	0	0	4	2	122	5	0	0	129	2	1	1	0	0	4	1	102	0	0	0	103	240	890
16:00:00	6	4	2	0	0	12	4	128	2	0	0	134	5	1	6	0	0	12	2	91	0	0	0	93	251	941
16:15:00	2	1	1	0	0	4	0	111	1	0	0	112	4	0	6	0	0	10	2	109	1	0	2	112	238	958
16:30:00	1	0	0	0	0	1	1	124	3	0	0	128	0	1	4	0	0	5	0	85	2	0	0	87	221	950
16:45:00	3	2	0	0	0	5	0	127	4	0	0	131	2	1	6	0	2	9	0	97	1	0	2	98	243	953
17:00:00	2	1	0	0	0	3	2	131	3	0	1	136	1	1	5	0	0	7	1	90	1	0	0	92	238	940
17:15:00	1	0	0	0	1	1	1	128	1	0	0	130	0	0	2	0	0	2	1	86	1	0	0	88	221	923
17:30:00	1	1	0	0	0	2	1	89	3	0	0	93	1	0	2	0	0	3	1	64	1	0	0	66	164	866
17:45:00	1	2	0	0	0	3	1	92	1	0	0	94	0	1	0	0	0	1	1	59	0	0	0	60	158	781
18:00:00	0	0	0	0	0	0	1	55	1	0	0	57	1	2	1	0	0	4	0	53	0	0	0	53	114	657
18:15:00	1	0	1	0	0	2	4	68	1	0	1	73	0	1	3	0	0	4	0	53	0	0	0	53	132	568
18:30:00	0	0	1	0	1	1	2	61	0	0	0	63	0	0	1	0	0	1	1	38	0	0	1	39	104	508
18:45:00	2	0	3	0	0	5	0	58	0	0	0	58	2	0	2	0	0	4	0	41	1	0	2	42	109	459
Grand Total	37	15	35	0	4	87	38	2434	51	0	8	2523	29	20	56	0	2	105	30	2423	24	0	11	2477	5192	-
Approach%	42.5%	17.2%	40.2%	0%		-	1.5%	96.5%	2%	0%		-	27.6%	19%	53.3%	0%		-	1.2%	97.8%	1%	0%		-	-	-
Totals %	0.7%	0.3%	0.7%	0%		1.7%	0.7%	46.9%	1%	0%		48.6%	0.6%	0.4%	1.1%	0%		2%	0.6%	46.7%	0.5%	0%		47.7%	-	-
Heavy	0	0	3	0		-	6	121	6	0		-	5	0	5	0		-	8	116	1	0		-	-	-
Heavy %	0%	0%	8.6%	0%		-	15.8%	5%	11.8%	0%		-	17.2%	0%	8.9%	0%		-	26.7%	4.8%	4.2%	0%		-	-	-
Bicycles	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-
Bicycle %	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-


Turning Movement Count Location Name: ARTHUR ST (HWY 26) & LANSDOWNE ST Date: Thu, Oct 14, 2021 Deployment Lead: Theo Daglis

								Pe	ak Hou	r: 08:45	AM - 0	9:45 AM We	ather: B	roken C	louds (15.17 °C	(ز								
Start Time			LAI	N Approac	sh STS				ART	E Approac HUR ST (H)	h WY 26)				LAI	S Approach	h ST S				ART	W Approac	ch WY 26)		Int. T (15 n
	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	
08:45:00	4	1	2	0	0	7	0	84	1	0	0	85	1	3	1	0	0	5	1	102	0	0	0	103	20
09:00:00	1	1	0	0	0	2	3	64	1	0	0	68	0	1	1	0	0	2	0	84	0	0	0	84	1
09:15:00	0	0	1	0	0	1	1	73	3	0	0	77	0	0	0	0	0	0	1	90	2	0	0	93	
09:30:00	1	0	1	0	0	2	2	67	1	0	2	70	1	2	1	0	0	4	1	84	2	0	0	87	
Grand Total	6	2	4	0	0	12	6	288	6	0	2	300	2	6	3	0	0	11	3	360	4	0	0	367	
Approach%	50%	16.7%	33.3%	0%		-	2%	96%	2%	0%		-	18.2%	54.5%	27.3%	0%		-	0.8%	98.1%	1.1%	0%		-	
Totals %	0.9%	0.3%	0.6%	0%		1.7%	0.9%	41.7%	0.9%	0%		43.5%	0.3%	0.9%	0.4%	0%		1.6%	0.4%	52.2%	0.6%	0%		53.2%	
PHF	0.38	0.5	0.5	0		0.43	0.5	0.86	0.5	0		0.88	0.5	0.5	0.75	0		0.55	0.75	0.88	0.5	0		0.89	
Heavy	0	0	1	0		1	2	22	1	0		25	0	0	0	0		0	1	18	0	0		19	. —
Heavy %	0%	0%	25%	0%		8.3%	33.3%	7.6%	16.7%	0%		8.3%	0%	0%	0%	0%		0%	33.3%	5%	0%	0%		5.2%	
Lights	6	2	3	0		11	4	266	5	0		275	2	4	3	0		9	2	342	4	0		348	
Lights %	100%	100%	75%	0%		91.7%	66.7%	92.4%	83.3%	0%		91.7%	100%	66.7%	100%	0%		81.8%	66.7%	95%	100%	0%		94.8%	
ingle-Unit Trucks	0	0	0	0		0	1	16	1	0		18	0	0	0	0		0	1	11	0	0		12	
gle-Unit Trucks %	0%	0%	0%	0%		0%	16.7%	5.6%	16.7%	0%		6%	0%	0%	0%	0%		0%	33.3%	3.1%	0%	0%		3.3%	
Buses	0	0	0	0		0	0	2	0	0		2	0	0	0	0		0	0	2	0	0		2	
Buses %	0%	0%	0%	0%		0%	0%	0.7%	0%	0%		0.7%	0%	0%	0%	0%		0%	0%	0.6%	0%	0%		0.5%	
rticulated Trucks	0	0	1	0		1	1	4	0	0		5	0	0	0	0		0	0	5	0	0		5	
iculated Trucks %	0%	0%	25%	0%		8.3%	16.7%	1.4%	0%	0%		1.7%	0%	0%	0%	0%		0%	0%	1.4%	0%	0%		1.4%	
Bicycles on Road	0	0	0	0		0	0	0	0	0		0	0	2	0	0		2	0	0	0	0		0	
cycles on Road %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	33.3%	0%	0%		18.2%	0%	0%	0%	0%		0%	
Pedestrians	-	-	-	-	0	-	-	-	-	-	2	-	-	-	-	-	0	-	-	-	-	-	0	-	


Turning Movement Count Location Name: ARTHUR ST (HWY 26) & LANSDOWNE ST Date: Thu, Oct 14, 2021 Deployment Lead: Theo Daglis

								Pea	k Hour	: 03:30	PM - 0	4:30 PM Wea	ther: O	ercast/	Clouds	(22.45	C)								
Start Time			LAI	N Approac	h STS				ART	E Approac	th WY 26)				LAI	S Approac	h ST S				AR	W Approad	ch WY 26)		Int. Total (15 min)
	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTum	Peds	Approach Total	Right	Thru	Left	UTum	Peds	Approach Total	
15:30:00	1	1	4	0	0	6	0	122	2	0	0	124	2	1	1	0	0	4	1	92	2	0	0	95	229
15:45:00	2	0	2	0	0	4	2	122	5	0	0	129	2	1	1	0	0	4	1	102	0	0	0	103	240
16:00:00	6	4	2	0	0	12	4	128	2	0	0	134	5	1	6	0	0	12	2	91	0	0	0	93	251
16:15:00	2	1	1	0	0	4	0	111	1	0	0	112	4	0	6	0	0	10	2	109	1	0	2	112	238
Grand Total	11	6	9	0	0	26	6	483	10	0	0	499	13	3	14	0	0	30	6	394	3	0	2	403	958
Approach%	42.3%	23.1%	34.6%	0%		-	1.2%	96.8%	2%	0%		-	43.3%	10%	46.7%	0%		-	1.5%	97.8%	0.7%	0%		-	
Totals %	1.1%	0.6%	0.9%	0%		2.7%	0.6%	50.4%	1%	0%		52.1%	1.4%	0.3%	1.5%	0%		3.1%	0.6%	41.1%	0.3%	0%		42.1%	
PHF	0.46	0.38	0.56	0		0.54	0.38	0.94	0.5	0		0.93	0.65	0.75	0.58	0		0.63	0.75	0.9	0.38	0		0.9	
Heavy	0	0	0	0		0	0	23	0	0		23	2	0	0	0		2	1	20	0	0		21	
Heavy %	0%	0%	0%	0%		0%	0%	4.8%	0%	0%		4.6%	15.4%	0%	0%	0%		6.7%	16.7%	5.1%	0%	0%		5.2%	
Lights	11	6	9	0		26	6	460	10	0		476	11	1	14	0		26	5	374	3	0		382	
Lights %	100%	100%	100%	0%		100%	100%	95.2%	100%	0%		95.4%	84.6%	33.3%	100%	0%		86.7%	83.3%	94.9%	100%	0%		94.8%	
Single-Unit Trucks	0	0	0	0		0	0	15	0	0		15	2	0	0	0		2	1	14	0	0		15	
Single-Unit Trucks %	0%	0%	0%	0%		0%	0%	3.1%	0%	0%		3%	15.4%	0%	0%	0%		6.7%	16.7%	3.6%	0%	0%		3.7%	
Buses	0	0	0	0		0	0	2	0	0		2	0	0	0	0		0	0	4	0	0		4	
Buses %	0%	0%	0%	0%		0%	0%	0.4%	0%	0%		0.4%	0%	0%	0%	0%		0%	0%	1%	0%	0%		1%	•
Articulated Trucks	0	0	0	0		0	0	6	0	0		6	0	0	0	0		0	0	2	0	0		2	
Articulated Trucks %	0%	0%	0%	0%		0%	0%	1.2%	0%	0%		1.2%	0%	0%	0%	0%		0%	0%	0.5%	0%	0%		0.5%	
Bicycles on Road	0	0	0	0		0	0	0	0	0		0	0	2	0	0		2	0	0	0	0		0	
Bicycles on Road %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	66.7%	0%	0%		6.7%	0%	0%	0%	0%		0%	-
Pedestrians	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	0	-	-	-	-	-	2	-	
Podostrians%					ner.						ner.						ner.						1009/		









										Tur	ning M	ovement Count	(2 . LOL	JISA ST	& LAI	NSDOW	NE ST)									
				N Approa	ach NE ST					E Approa	ch ST					S Approa	ach NE ST					W Appro	oach A ST		Int. Total (15 min)	Int. Total (1 hr)
Start Time	Right N:W	Thru N:S	Left N:E	UTurn N:N	Peds N:	Approach Total	Right E:N	Thru E:W	Left E:S	UTurn E:E	Peds E:	Approach Total	Right S:E	Thru S:N	Left S:W	UTurn S:S	Peds S:	Approach Total	Right W:S	Thru W:E	Left W:N	UTurn W:W	Peds W:	Approach Total		
06:00:00	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	1	
06:15:00	0	1	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	2	
06:30:00	0	1	0	0	0	1	0	0	0	0	0	0	0	2	0	0	0	2	0	0	0	0	1	0	3	
06:45:00	0	1	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	2	8
07:00:00	0	3	0	0	0	3	0	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	4	11
07:15:00	0	0	0	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	1	10
07:30:00	0	1	0	0	0	1	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	1	0	2	9
07:45:00	0	1	0	0	0	1	0	0	0	0	0	0	0	0	0	0	1	0	0	0	0	0	1	0	1	8
08:00:00	0	0	0	0	0	0	0	0	1	0	0	1	0	0	0	0	0	0	0	0	0	0	0	0	1	5
08:15:00	0	2	0	0	0	2	0	0	0	0	5	0	0	2	0	0	0	2	0	0	0	0	0	0	4	8
08:30:00	0	0	0	0	0	0	0	0	0	0	1	0	0	2	0	0	0	2	0	0	0	0	0	0	2	8
08:45:00	0	3	0	0	0	3	0	0	1	0	1	1	1	3	0	0	0	4	0	0	0	0	1	0	8	15
09:00:00	0	2	0	0	0	2	0	0	1	0	0	1	0	2	0	0	0	2	0	0	0	0	0	0	5	19
09:15:00	0	1	0	0	0	1	0	0	1	0	2	1	0	1	0	0	0	1	0	0	0	0	0	0	3	18
09:30:00	0	3	0	0	0	3	0	0	0	0	0	0	0	3	0	0	0	3	0	0	0	0	0	0	6	22
09:45:00	0	2	0	0	0	2	0	0	2	0	0	2	0	0	0	0	0	0	0	0	0	0	2	0	4	18
BREAK*		************************************										T						······								
15:00:00	0	8	0	0	0	8	1	0	0	0	0	1	0	1	0	0	0	1	0	0	0	0	0	0	10	
15:15:00	0	7	0	0	0	7	0	0	0	0	0	0	0	4	0	0	0	4	0	0	0	0	2	0	11	
15:30:00	0	3	0	0	0	3	0	0	0	0	0	0	0	5	0	0	0	5	0	0	0	0	0	0	8	
15:45:00	0	7	0	0	0	7	1	0	0	0	0	1	0	5	0	0	0	5	0	0	0	0	0	0	13	42
16:00:00	0	3	0	0	0	3	0	0	0	0	0	0	0	5	0	0	0	5	0	0	0	0	0	0	8	40
16:15:00	0	5	0	0	0	5	0	0	0	0	0	0	0	6	0	0	0	6	0	0	0	0	2	0	11	40
16:30:00	0	2	0	0	0	2	1	0	0	0	0	1	0	4	0	0	0	4	0	0	0	0	0	0	7	39
16:45:00	0	8	0	0	0	6	0	0	0	0	3	0	0	7	0	0	0	7	0	0	0	0	0	0	11	37
		6	0		0	6	<u> </u>		-		-				0	0		1	<u> </u>	-	0		0	0		
17:15:00	0	4	0	0	0	4	0	0	0	0	0	0	0	1	-	0	0	1	0	0	0	0	0	0	7 5	40 38
17:30:00	0	4	0	0	0	4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	4	38
18:00:00	0	3	0	0	0	3	0	0	0	0	0	0	0	5	0	0	0	5	0	0	0	0	0	0	8	24
18:15:00	0	3	0	0	0	3	0	0	0	0	1	0	0	2	0	0	0	2	0	0	0	0	0	0	5	22
18:30:00	0	2	0	0	0	2	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	0	3	20
18:45:00	0	2	0	0	0	2	0	0	0	0	1	0	0	2	0	0	0	2	0	0	0	0	2	0	4	20
Grand Total	0	94	0	0	0	94	3	0	7	0	16	10	1	74	0	0	1	75	0	0	0	0	12	0	179	-
Approach%	0%	100%	0%	0%		-	30%	0%	70%	0%	10	-	1.3%	98.7%	0%	0%		- ,5	0%	0%	0%	0%	12	-	-	-
Totals %	0%	52.5%	0%	0%		52.5%	1.7%	0%	3.9%	0%		5.6%	0.6%	41.3%	0%	0%		41.9%	0%	0%	0%	0%		0%		-
Heavy	0	4	0	0		-	0	0	5	0		-	1	1	0	0		-	0	0	0	0		-		-
Heavy %	0%	4.3%	0%	0%		-	0%	0%	71.4%	0%		-	100%	1.4%	0%	0%		-	0%	0%	0%	0%		-	-	-
Bicycles	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-
Bicycle %	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-	-	-	-	-		-		-




Pedestrians%

Turning Movement Count Location Name: LOUISA ST & LANSDOWNE ST Date: Thu, Oct 14, 2021 Deployment Lead: Theo Daglis

								Pe	ak Hour	: 08:45	AM - 09	:45 AM Weatl	ner: Bro	ken Clo	uds (15.17 °C	;)								
Start Time				N Appro	ach NE ST					E Approa	ch ST					S Approa	i ch NE ST					W Appr LOUIS	oach A ST		Int. Tota (15 min)
	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	
08:45:00	0	3	0	0	0	3	0	0	1	0	1	1	1	3	0	0	0	4	0	0	0	0	1	0	8
09:00:00	0	2	0	0	0	2	0	0	1	0	0	1	0	2	0	0	0	2	0	0	0	0	0	0	5
09:15:00	0	1	0	0	0	1	0	0	1	0	2	1	0	1	0	0	0	1	0	0	0	0	0	0	3
09:30:00	0	3	0	0	0	3	0	0	0	0	0	0	0	3	0	0	0	3	0	0	0	0	0	0	6
Grand Total	0	9	0	0	0	9	0	0	3	0	3	3	1	9	0	0	0	10	0	0	0	0	1	0	22
Approach%	0%	100%	0%	0%		-	0%	0%	100%	0%		-	10%	90%	0%	0%		-	0%	0%	0%	0%		-	-
Totals %	0%	40.9%	0%	0%		40.9%	0%	0%	13.6%	0%		13.6%	4.5%	40.9%	0%	0%		45.5%	0%	0%	0%	0%		0%	-
PHF	0	0.75	0	0		0.75	0	0	0.75	0		0.75	0.25	0.75	0	0		0.63	0	0	0	0		0	-
Heavy	0	0	0	0		0	0	0	3	0		3	1	0	0	0		1	0	0	0	0		0	
Heavy %	0%	0%	0%	0%		0%	0%	0%	100%	0%		100%	100%	0%	0%	0%		10%	0%	0%	0%	0%		0%	-
Lights	0	9	0	0		9	0	0	0	0		0	0	7	0	0		7	0	0	0	0		0	-
Lights %	0%	100%	0%	0%		100%	0%	0%	0%	0%		0%	0%	77.8%	0%	0%		70%	0%	0%	0%	0%		0%	-
Single-Unit Trucks	0	0	0	0		0	0	0	3	0		3	1	0	0	0		1	0	0	0	0		0	-
Single-Unit Trucks %	0%	0%	0%	0%		0%	0%	0%	100%	0%		100%	100%	0%	0%	0%		10%	0%	0%	0%	0%		0%	-
Buses	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	-
Buses %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	•
Articulated Trucks Articulated Trucks %	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	-
Bicycles on Road	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0% 2	0%	0%	0%	0%		0%	-
Bicycles on Road %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	22.2%	0%	0%		20%	0%	0%	0%	0%		0%	-
Pedestrians	0 /0	0 /0	U /0	U /0	0	0 /0	U /0	U /0	0 /0	0 /0		U/0	0 /0	۷۵.۵ /۵	0 /0	0 /0		20 /0	0 /0	U /0	0 /0	0 /0		0 /0	-


								rea	K HOU	1.04.10) FW - 00	5:15 PM Weatl	ier. Ove	i cast (Jiouu.	5 (22.40	٠,								
Start Time				N Approx	nch NE ST					E Appr	oach A ST					S Appro LANSDOW	ach NE ST					W App LOUIS	roach SA ST		Int. Tota (15 min
	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTum	Peds	Approach Total	Right	Thru	Left	UTurn	Peds	Approach Total	Right	Thru	Left	UTum	Peds	Approach Total	
16:15:00	0	5	0	0	0	5	0	0	0	0	0	0	0	6	0	0	0	6	0	0	0	0	2	0	11
16:30:00	0	2	0	0	0	2	1	0	0	0	0	1	0	4	0	0	0	4	0	0	0	0	0	0	7
16:45:00	0	6	0	0	0	6	0	0	0	0	2	0	0	5	0	0	0	5	0	0	0	0	0	0	11
17:00:00	0	8	0	0	0	8	0	0	0	0	3	0	0	7	0	0	0	7	0	0	0	0	0	0	15
Grand Total	0	21	0	0	0	21	1	0	0	0	5	1	0	22	0	0	0	22	0	0	0	0	2	0	44
Approach%	0%	100%	0%	0%		-	100%	0%	0%	0%		-	0%	100%	0%	0%			0%	0%	0%	0%		-	-
Totals %	0%	47.7%	0%	0%		47.7%	2.3%	0%	0%	0%		2.3%	0%	50%	0%	0%		50%	0%	0%	0%	0%		0%	
PHF	0	0.66	0	0		0.66	0.25	0	0	0		0.25	0	0.79	0	0		0.79	0	0	0	0		0	
Heavy	0	1	0	0		1	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	
Heavy %	0%	4.8%	0%	0%		4.8%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	
Lights	0	20	0	0		20	1	0	0	0		1	0	22	0	0		22	0	0	0	0		0	
Lights %	0%	95.2%	0%	0%		95.2%	100%	0%	0%	0%		100%	0%	100%	0%	0%		100%	0%	0%	0%	0%		0%	
Single-Unit Trucks	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	-
Single-Unit Trucks %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	
Buses	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	
Buses %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	
Articulated Trucks	0	1	0	0		1	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	
Articulated Trucks %	0%	4.8%	0%	0%		4.8%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	-
Bicycles on Road	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	0	0	0	0		0	-
Bicycles on Road %	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	0%	0%	0%	0%		0%	-
Pedestrians	-	-	-	-	0	-	-	-	-	-	5	-	-	-	-	-	0	-	-		-	-	2	-	-

Peak Hour: 08:45 AM - 09:45 AM Weather: Broken Clouds (15.17 °C)



CRA21P9B

Peak Hour: 04:15 PM - 05:15 PM Weather: Overcast Clouds (22.45 °C)



Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX F

Level of Service Definitions

Level of Service Definitions

Two-Way Stop Controlled Intersections

Level of Service	Control Delay per Vehicle (seconds)	Interpretation
А	≤ 10	EXCELLENT. Large and frequent gaps in traffic on the main roadway. Queuing on the minor street is rare.
В	> 10 and ≤ 15	VERY GOOD. Many gaps exist in traffic on the main roadway. Queuing on the minor street is minimal.
С	> 15 and ≤ 25	GOOD. Fewer gaps exist in traffic on the main roadway. Delay on minor approach becomes more noticeable.
D	> 25 and ≤ 35	FAIR. Infrequent and shorter gaps in traffic on the main roadway. Queue lengths develop on the minor street.
Е	> 35 and ≤ 50	POOR. Very infrequent gaps in traffic on the main roadway. Queue lengths become noticeable.
F	> 50	UNSATISFACTORY. Very few gaps in traffic on the main roadway. Excessive delay with significant queue lengths on the minor street.

Adapted from Highway Capacity Manual 2000, Transportation Research Board

Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX G

Detailed Capacity Analysis

	۶	-	•	•	—	•	1	†	/	/	ţ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	f)		7	1>			₽			4	
Traffic Volume (veh/h)	4	360	3	6	288	6	3	6	2	4	2	6
Future Volume (Veh/h)	4	360	3	6	288	6	3	6	2	4	2	6
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	5	419	3	7	335	7	3	7	2	5	2	7
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	342			422			788	786	422	789	784	338
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	342			422			788	786	422	789	784	338
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF(s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			99			99	98	100	98	99	99
cM capacity (veh/h)	1228			1061			304	323	635	302	324	708
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	5	422	7	342	12	14						
Volume Left	5	0	7	0	3	5						
Volume Right	0	3	0	7	2	7						
cSH	1228	1700	1061	1700	346	429						
Volume to Capacity	0.00	0.25	0.01	0.20	0.03	0.03						
Queue Length 95th (m)	0.1	0.0	0.2	0.0	0.9	0.8						
Control Delay (s)	7.9	0.0	8.4	0.0	15.8	13.7						
Lane LOS	Α		Α		С	В						
Approach Delay (s)	0.1		0.2		15.8	13.7						
Approach LOS					С	В						
Intersection Summary												
Average Delay			0.6									
Intersection Capacity Utilizati	on		29.8%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report C.F Crozier & Associates Page 1

	۶	→	•	•	—	•	1	†	<i>></i>	/	+	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			44			4			4	
Traffic Volume (veh/h)	0	0	0	3	0	0	0	9	1	0	9	0
Future Volume (Veh/h)	0	0	0	3	0	0	0	9	1	0	9	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	0	0	0	4	0	0	0	13	1	0	13	0
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	28	31	14	30	30	16	14			17		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	28	31	14	30	30	16	14			17		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	99	100	100	100			100		
cM capacity (veh/h)	979	859	1065	776	859	1066	1616			1609		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	4	14	13								
Volume Left	0	4	0	0								
Volume Right	0	0	1	0								
cSH	1700	776	1616	1609								
Volume to Capacity	0.00	0.01	0.00	0.00								
Queue Length 95th (m)	0.0	0.1	0.0	0.0								
Control Delay (s)	0.0	9.7	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	9.7	0.0	0.0								
Approach LOS	А	Α										
Intersection Summary												
Average Delay			1.2									
Intersection Capacity Utiliza	ation		14.3%	IC	U Level	of Service			Α			
Analysis Period (min)			15		2 23.01	22,			, , , , , , , , , , , , , , , , , , ,			
			, ,									

Synchro 11 Light Report Page 2 C.F Crozier & Associates

	۶	→	•	•	•	•	•	†	<i>></i>	\	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	1	2	2	2	2	3	0	13	7	8	15	1
Future Volume (vph)	1	2	2	2	2	3	0	13	7	8	15	1
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	1	2	2	2	2	3	0	15	8	9	17	1
Direction, Lane#	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	5	7	23	27								
Volume Left (vph)	1	2	0	9								
Volume Right (vph)	2	3	8	1								
Hadj (s)	-0.17	-0.17	-0.17	0.08								
Departure Headway (s)	3.8	3.8	3.8	4.0								
Degree Utilization, x	0.01	0.01	0.02	0.03								
Capacity (veh/h)	918	919	946	886								
Control Delay (s)	6.9	6.9	6.9	7.1								
Approach Delay (s)	6.9	6.9	6.9	7.1								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.0									_
Level of Service			Α									
Intersection Capacity Utilization	on		20.0%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report Page 3 C.F Crozier & Associates

	•	•	†	/	\	ţ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		f)			4
Traffic Volume (veh/h)	1	0	2	1	0	2
Future Volume (Veh/h)	1	0	2	1	0	2
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50
Hourly flow rate (vph)	2	0	4	2	0	4
Pedestrians	3					
Lane Width (m)	3.6					
Walking Speed (m/s)	1.2					
Percent Blockage	0					
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	12	8			9	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	12	8			9	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1010	1077			1620	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	2	6	4			
	2					
Volume Left		0	0			
Volume Right	1010	1700	1600			
cSH	1010	1700	1620			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	A					
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	Α					
Intersection Summary						
Average Delay			1.4			
Intersection Capacity Utiliza	ntion		14.3%	IC	U Level o	f Service
Analysis Period (min)			15			

Synchro 11 Light Report C.F Crozier & Associates Page 4

	۶	→	•	•	—	•	1	†	<i>></i>	/	ţ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ř	f)		7	f)			4			4	
Traffic Volume (veh/h)	3	394	6	10	483	6	14	3	13	9	6	11
Future Volume (Veh/h)	3	394	6	10	483	6	14	3	13	9	6	11
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	3	415	6	11	508	6	15	3	14	9	6	12
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	514			421			971	960	418	970	960	513
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	514			421			971	960	418	970	960	513
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			99			93	99	98	96	98	98
cM capacity (veh/h)	1062			1149			223	255	608	225	255	564
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	3	421	11	514	32	27						
Volume Left	3	0	11	0	15	9						
Volume Right	0	6	0	6	14	12						
cSH	1062	1700	1149	1700	313	319						
Volume to Capacity	0.00	0.25	0.01	0.30	0.10	0.08						
Queue Length 95th (m)	0.1	0.0	0.2	0.0	2.7	2.2						
Control Delay (s)	8.4	0.0	8.2	0.0	17.8	17.3						
Lane LOS	Α		Α		С	С						
Approach Delay (s)	0.1		0.2		17.8	17.3						
Approach LOS					С	С						
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utilizati	on		36.4%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	—	•	•	†	<i>></i>	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	0	0	1	0	22	0	0	21	0
Future Volume (Veh/h)	0	0	0	0	0	1	0	22	0	0	21	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	0	0	0	0	0	1	0	30	0	0	29	0
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	62	66	31	64	66	35	31			35		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	62	66	31	64	66	35	31			35		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	100	100	100	100			100		
cM capacity (veh/h)	926	820	1041	927	820	1039	1579			1570		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	1	30	29								
Volume Left	0	0	0	0								
Volume Right	0	1	0	0								
cSH	1700	1039	1579	1570								
Volume to Capacity	0.00	0.00	0.00	0.00								
Queue Length 95th (m)	0.0	0.0	0.0	0.0								
Control Delay (s)	0.0	8.5	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	8.5	0.0	0.0								
Approach LOS	А	Α										
Intersection Summary												
Average Delay			0.1									
Intersection Capacity Utiliza	ation		14.9%	IC	U Level	of Service			Α			
Analysis Period (min)	.		15		2 = 3.01							
) old (.,									

Synchro 11 Light Report Page 2 C.F. Crozier & Associates

	۶	→	•	•	•	•	•	†	<i>></i>	\	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	0	1	0	7	4	8	0	29	3	9	38	1
Future Volume (vph)	0	1	0	7	4	8	0	29	3	9	38	1
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	0	1	0	8	4	9	0	33	3	10	43	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	1	21	36	54								
Volume Left (vph)	0	8	0	10								
Volume Right (vph)	0	9	3	1								
Hadj (s)	0.03	-0.15	-0.02	0.06								
Departure Headway (s)	4.1	3.9	4.0	4.0								
Degree Utilization, x	0.00	0.02	0.04	0.06								
Capacity (veh/h)	844	888	885	880								
Control Delay (s)	7.2	7.0	7.1	7.3								
Approach Delay (s)	7.2	7.0	7.1	7.3								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.2									
Level of Service			Α									
Intersection Capacity Utilization	n		25.1%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report Page 3 C.F. Crozier & Associates

	•	•	†	/	/	ţ	
Movement	WBL	WBR	NBT	NBR	SBL	SBT	
Lane Configurations	W		f)			र्स	
Traffic Volume (veh/h)	2	0	3	0	0	3	
Future Volume (Veh/h)	2	0	3	0	0	3	
Sign Control	Stop		Free			Free	
Grade	0%		0%			0%	
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56	
Hourly flow rate (vph)	4	0	5	0	0	5	
Pedestrians							
Lane Width (m)							
Walking Speed (m/s)							
Percent Blockage							
Right turn flare (veh)							
Median type			None			None	
Median storage veh)							
Upstream signal (m)							
pX, platoon unblocked							
vC, conflicting volume	10	5			5		
vC1, stage 1 conf vol							
vC2, stage 2 conf vol							
vCu, unblocked vol	10	5			5		
tC, single (s)	6.4	6.2			4.1		
tC, 2 stage (s)							
tF (s)	3.5	3.3			2.2		
p0 queue free %	100	100			100		
cM capacity (veh/h)	1015	1084			1630		
Direction, Lane #	WB 1	NB 1	SB 1				
Volume Total	4	5	5				
Volume Left	4	0	0				
Volume Right	0	0	0				
cSH	1015	1700	1630				
Volume to Capacity	0.00	0.00	0.00				
Queue Length 95th (m)	0.1	0.0	0.0				
Control Delay (s)	8.6	0.0	0.0				
Lane LOS	Α						
Approach Delay (s)	8.6	0.0	0.0				
Approach LOS	Α						
Intersection Summary							
Average Delay			2.4				
Intersection Capacity Utiliz	ation		13.3%	IC	U Level o	of Service	
Analysis Period (min)			15				

C.F. Crozier & Associates

Synchro 11 Light Report
Page 4

	۶	→	*	•	←	•	•	†	<i>></i>	/	ţ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		7	₽			4			4	
Traffic Volume (veh/h)	4	401	4	9	319	7	6	7	6	4	2	7
Future Volume (Veh/h)	4	401	4	9	319	7	6	7	6	4	2	7
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	5	466	5	10	371	8	7	8	7	5	2	8
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	379			471			878	878	470	884	876	375
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	379			471			878	878	470	884	876	375
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			99			97	97	99	98	99	99
cM capacity (veh/h)	1191			1017			263	285	596	256	285	676
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	5	471	10	379	22	15						
Volume Left	5	0	10	0	7	5						
Volume Right	0	5	0	8	7	8						
cSH	1191	1700	1017	1700	331	391						
Volume to Capacity	0.00	0.28	0.01	0.22	0.07	0.04						
Queue Length 95th (m)	0.1	0.0	0.2	0.0	1.7	1.0						
Control Delay (s)	8.0	0.0	8.6	0.0	16.6	14.6						
Lane LOS	Α		Α		С	В						
Approach Delay (s)	0.1		0.2		16.6	14.6						
Approach LOS					С	В						
Intersection Summary												
Average Delay			0.8									
Intersection Capacity Utilizat	ion		32.0%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

C. F. Crozier & Associates

Synchro 11 Light Report
Page 1

	۶	→	•	•	←	•	1	†	<i>></i>	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	3	0	0	0	17	1	0	12	0
Future Volume (Veh/h)	0	0	0	3	0	0	0	17	1	0	12	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	0	0	0	4	0	0	0	25	1	0	17	0
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	44	47	18	46	46	28	18			29		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	44	47	18	46	46	28	18			29		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	99	100	100	100			100		
cM capacity (veh/h)	956	842	1060	755	842	1050	1611			1593		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	4	26	17								
Volume Left	0	4	0	0								
Volume Right	0	0	1	0								
cSH	1700	755	1611	1593								
Volume to Capacity	0.00	0.01	0.00	0.00								
Queue Length 95th (m)	0.0	0.1	0.0	0.0								
Control Delay (s)	0.0	9.8	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	9.8	0.0	0.0								
Approach LOS	Α	Α										
Intersection Summary												
Average Delay			0.8									
Intersection Capacity Utilizat	tion		14.3%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

C. F. Crozier & Associates

Synchro 11 Light Report
Page 2

	•	→	•	•	←	•	4	†	<i>></i>	>	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	1	2	2	2	2	3	0	14	8	9	17	1
Future Volume (vph)	1	2	2	2	2	3	0	14	8	9	17	1
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	1	2	2	2	2	3	0	16	9	10	19	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	5	7	25	30								
Volume Left (vph)	1	2	0	10								
Volume Right (vph)	2	3	9	1								
Hadj (s)	-0.17	-0.17	-0.18	0.08								
Departure Headway (s)	3.9	3.9	3.8	4.0								
Degree Utilization, x	0.01	0.01	0.03	0.03								
Capacity (veh/h)	914	916	947	885								
Control Delay (s)	6.9	6.9	6.9	7.2								
Approach Delay (s)	6.9	6.9	6.9	7.2								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.0									
Level of Service			Α									
Intersection Capacity Utilizati	on		20.2%	IC	U Level c	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report Page 3 C. F. Crozier & Associates

	•	•	†	/	\	↓
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		f)			4
Traffic Volume (veh/h)	1	0	2	1	0	2
Future Volume (Veh/h)	1	0	2	1	0	2
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50
Hourly flow rate (vph)	2	0	4	2	0	4
Pedestrians	3					
Lane Width (m)	3.6					
Walking Speed (m/s)	1.2					
Percent Blockage	0					
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	12	8			9	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	12	8			9	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1010	1077			1620	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	2	6	4			
Volume Left	2	0	0			
Volume Right	0	2	0			
cSH	1010	1700	1620			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.00	0.00	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	0.0 A	0.0	0.0			
	8.6	0.0	0.0			
Approach Delay (s) Approach LOS	0.0 A	0.0	0.0			
••	A					
Intersection Summary						
Average Delay			1.4			
Intersection Capacity Utiliz	zation		14.3%	IC	U Level o	f Service
Analysis Period (min)			15			

	۶	→	•	•	—	4	1	†	~	/	+	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	1>		ሻ	ĵ₃			4			4	
Traffic Volume (veh/h)	3	438	10	15	537	7	17	3	17	10	7	12
Future Volume (Veh/h)	3	438	10	15	537	7	17	3	17	10	7	12
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	3	461	11	16	565	7	18	3	18	11	7	13
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	572			472			1088	1076	466	1087	1078	570
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	572			472			1088	1076	466	1087	1078	570
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			99			90	99	97	94	97	98
cM capacity (veh/h)	1011			1100			183	217	570	185	216	524
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	3	472	16	572	39	31						
Volume Left	3	0	16	0	18	11						
	0	11	0	7	18	13						
Volume Right cSH	1011		1100	1700	271	266						
		1700	0.01	0.34	0.14	0.12						
Volume to Capacity	0.00	0.28			4.0	3.1						
Queue Length 95th (m)		0.0	0.4	0.0								
Control Delay (s)	8.6	0.0	8.3	0.0	20.5	20.3						
Lane LOS	Α		A		C	C						
Approach Delay (s)	0.1		0.2		20.5	20.3						
Approach LOS					С	С						
Intersection Summary												
Average Delay			1.4									
Intersection Capacity Utiliza	ation		39.3%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

	۶	-	•	•	←	•	4	†	/	/	ţ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	0	0	1	0	29	0	0	30	0
Future Volume (Veh/h)	0	0	0	0	0	1	0	29	0	0	30	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	0	0	0	0	0	1	0	40	0	0	41	0
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	84	88	43	86	88	45	43			45		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	84	88	43	86	88	45	43			45		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	100	100	100	100			100		
cM capacity (veh/h)	896	797	1026	897	797	1026	1563			1557		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	1	40	41								
Volume Left	0	0	0	0								
Volume Right	0	1	0	0								
cSH	1700	1026	1563	1557								
Volume to Capacity	0.00	0.00	0.00	0.00								
Queue Length 95th (m)	0.0	0.0	0.0	0.0								
Control Delay (s)	0.0	8.5	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	8.5	0.0	0.0								
Approach LOS	А	Α										
Intersection Summary												
Average Delay			0.1									
Intersection Capacity Utiliza	ation		14.9%	IC	U Level	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	•	•	4	†	/	/	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	0	1	0	8	4	9	0	32	3	10	42	1
Future Volume (vph)	0	1	0	8	4	9	0	32	3	10	42	1
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	0	1	0	9	4	10	0	36	3	11	47	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	1	23	39	59								
Volume Left (vph)	0	9	0	11								
Volume Right (vph)	0	10	3	1								
Hadj (s)	0.03	-0.15	-0.01	0.06								
Departure Headway (s)	4.2	4.0	4.0	4.0								
Degree Utilization, x	0.00	0.03	0.04	0.07								
Capacity (veh/h)	838	883	881	878								
Control Delay (s)	7.2	7.1	7.2	7.3								
Approach Delay (s)	7.2	7.1	7.2	7.3								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.2									
Level of Service			Α									
Intersection Capacity Utilization	on		25.7%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	~	>	ţ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		f)			ર્ન
Traffic Volume (veh/h)	2	0	3	0	0	3
Future Volume (Veh/h)	2	0	3	0	0	3
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56
Hourly flow rate (vph)	4	0	5	0	0	5
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	10	5			5	
vC1, stage 1 conf vol	. •					
vC2, stage 2 conf vol						
vCu, unblocked vol	10	5			5	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	2 . 1					
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1015	1084			1630	
			25.4		1000	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	4	5	5			
Volume Left	4	0	0			
Volume Right	0	0	0			
cSH	1015	1700	1630			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.1	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	Α					
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	Α					
Intersection Summary						
Average Delay			2.4			
Intersection Capacity Utiliz	ation		13.3%	IC	U Level o	f Service
Analysis Period (min)			15	.0	2 201010	. 55, 1100
Analysis i Gilou (IIIII)			10			

	۶	→	*	•	—	4	1	†	~	/	+	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		ሻ	ĵ₃			4			4	
Traffic Volume (veh/h)	4	483	10	16	593	7	19	4	19	11	7	13
Future Volume (Veh/h)	4	483	10	16	593	7	19	4	19	11	7	13
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	4	508	11	17	624	7	20	4	20	12	7	14
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	631			519			1199	1186	514	1200	1188	630
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	631			519			1199	1186	514	1200	1188	630
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			98			87	98	96	92	96	97
cM capacity (veh/h)	961			1057			152	186	536	153	186	485
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	4	519	17	631	44	33						
Volume Left	4	0	17		20	12						
	0	11		0 7	20	14						
Volume Right cSH	961		0 1057	1700	231	227						
		1700 0.31	0.02	0.37		0.15						
Volume to Capacity	0.00				0.19 5.5	4.0						
Queue Length 95th (m)	0.1	0.0	0.4	0.0								
Control Delay (s)	8.8	0.0	8.5	0.0	24.2	23.5						
Lane LOS	A		A		C	C						
Approach Delay (s)	0.1		0.2		24.2	23.5						
Approach LOS					С	С						
Intersection Summary												
Average Delay			1.6									
Intersection Capacity Utilizat	ion		42.3%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	+	•	•	†	<i>></i>	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	0	0	1	0	32	0	0	33	0
Future Volume (Veh/h)	0	0	0	0	0	1	0	32	0	0	33	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	0	0	0	0	0	1	0	44	0	0	45	0
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	92	96	47	94	96	49	47			49		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	92	96	47	94	96	49	47			49		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF(s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	100	100	100	100			100		
cM capacity (veh/h)	886	789	1020	886	789	1021	1558			1551		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	1	44	45								
Volume Left	0	0	0	0								
Volume Right	0	1	0	0								
cSH	1700	1021	1558	1551								
Volume to Capacity	0.00	0.00	0.00	0.00								
Queue Length 95th (m)	0.0	0.00	0.00	0.00								
	0.0	8.5	0.0	0.0								
Control Delay (s) Lane LOS	0.0 A	0.5 A	0.0	0.0								
Approach Delay (s)	0.0	8.5	0.0	0.0								
Approach LOS	0.0 A	0.5 A	0.0	0.0								
••	A	A										
Intersection Summary			0.4									
Average Delay	·		0.1	,,								
Intersection Capacity Utiliza	ation		14.9%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	←	•	4	†	<i>></i>	/	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	0	1	0	9	5	10	0	35	4	11	46	1
Future Volume (vph)	0	1	0	9	5	10	0	35	4	11	46	1
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	0	1	0	10	6	11	0	39	4	12	52	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	1	27	43	65								
Volume Left (vph)	0	10	0	12								
Volume Right (vph)	0	11	4	1								
Hadj (s)	0.03	-0.14	-0.02	0.06								
Departure Headway (s)	4.2	4.0	4.0	4.1								
Degree Utilization, x	0.00	0.03	0.05	0.07								
Capacity (veh/h)	831	874	879	874								
Control Delay (s)	7.2	7.1	7.2	7.4								
Approach Delay (s)	7.2	7.1	7.2	7.4								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.3									
Level of Service			Α									
Intersection Capacity Utilizati	on		26.1%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	/	/	↓
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		1>			सी
Traffic Volume (veh/h)	2	0	4	0	0	4
Future Volume (Veh/h)	2	0	4	0	0	4
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56
Hourly flow rate (vph)	4	0	7	0	0	7
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	14	7			7	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	14	7			7	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1010	1081			1627	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	4	7	7			
Volume Left	4	0	0			
Volume Right	0	0	0			
cSH	1010	1700	1627			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.1	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	A	0.0	0.0			
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	A	0.0	0.0			
Intersection Summary						
Average Delay			1.9			
Intersection Capacity Utiliza	ation		13.3%	IC	U Level of	Service
Analysis Period (min)			15			22
, and your office (fillin)			10			

	۶	→	•	•	←	•	•	†	<i>></i>	/	ţ	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	₽		7	₽			4			4	
Traffic Volume (veh/h)	5	443	5	9	352	7	7	7	6	5	2	7
Future Volume (Veh/h)	5	443	5	9	352	7	7	7	6	5	2	7
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	6	515	6	10	409	8	8	8	7	6	2	8
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	417			521			968	967	520	973	966	413
vC1, stage 1 conf vol				V								
vC2, stage 2 conf vol												
vCu, unblocked vol	417			521			968	967	520	973	966	413
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)								0.0	V		0.0	V
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			99			96	97	99	97	99	99
cM capacity (veh/h)	1153			973			228	252	559	222	253	643
		ED 0	MD 4		ND 4	00.4	220	202			200	010
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	6	521	10	417	23	16						
Volume Left	6	0	10	0	8	6						
Volume Right	0	6	0	8	7	8						
cSH	1153	1700	973	1700	290	338						
Volume to Capacity	0.01	0.31	0.01	0.25	0.08	0.05						
Queue Length 95th (m)	0.1	0.0	0.2	0.0	2.1	1.2						
Control Delay (s)	8.1	0.0	8.7	0.0	18.5	16.2						
Lane LOS	Α		Α		С	С						
Approach Delay (s)	0.1		0.2		18.5	16.2						
Approach LOS					С	С						
Intersection Summary												
Average Delay			0.8									
Intersection Capacity Utilizat	tion		34.3%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									
,												

	۶	→	•	•	+	•	•	†	<i>></i>	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	4	0	0	0	18	1	0	13	0
Future Volume (Veh/h)	0	0	0	4	0	0	0	18	1	0	13	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	0	0	0	6	0	0	0	26	1	0	19	0
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	46	50	20	48	50	30	20			30		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	46	50	20	48	50	30	20			30		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	99	100	100	100			100		
cM capacity (veh/h)	952	839	1057	752	839	1048	1608			1592		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	6	27	19								
Volume Left	0	6	0	0								
Volume Right	0	0	1	0								
cSH	1700	752	1608	1592								
Volume to Capacity	0.00	0.01	0.00	0.00								
Queue Length 95th (m)	0.00	0.01	0.00	0.00								
	0.0	9.8	0.0	0.0								
Control Delay (s)			0.0	0.0								
Lane LOS	A	A	0.0	0.0								
Approach LOS	0.0	9.8	0.0	0.0								
Approach LOS	A	Α										
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utiliza	tion		14.3%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	→	•	•	←	•	4	†	/	>	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	1	2	2	2	2	4	0	16	9	10	18	1
Future Volume (vph)	1	2	2	2	2	4	0	16	9	10	18	1
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	1	2	2	2	2	5	0	18	10	11	20	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	5	9	28	32								
Volume Left (vph)	1	2	0	11								
Volume Right (vph)	2	5	10	1								
Hadj (s)	-0.17	-0.25	-0.18	0.08								
Departure Headway (s)	3.9	3.8	3.8	4.0								
Degree Utilization, x	0.01	0.01	0.03	0.04								
Capacity (veh/h)	910	933	944	883								
Control Delay (s)	6.9	6.8	6.9	7.2								
Approach Delay (s)	6.9	6.8	6.9	7.2								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.0									
Level of Service			Α									
Intersection Capacity Utilizat	ion		20.3%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	/	\	↓
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		f)			4
Traffic Volume (veh/h)	1	0	2	1	0	2
Future Volume (Veh/h)	1	0	2	1	0	2
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50
Hourly flow rate (vph)	2	0	4	2	0	4
Pedestrians	3					
Lane Width (m)	3.6					
Walking Speed (m/s)	1.2					
Percent Blockage	0					
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	12	8			9	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	12	8			9	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1010	1077			1620	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	2	6	4			
Volume Left	2	0	0			
Volume Right	0	2	0			
cSH	1010	1700	1620			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.00	0.00	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	0.0 A	0.0	0.0			
	8.6	0.0	0.0			
Approach Delay (s) Approach LOS	0.0 A	0.0	0.0			
••	A					
Intersection Summary						
Average Delay			1.4			
Intersection Capacity Utiliz	zation		14.3%	IC	U Level o	f Service
Analysis Period (min)			15			

	•	→	*	•	+	•	1	†	~	/	↓	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		7	ĵ»			4			4	
Traffic Volume (veh/h)	6	539	5	11	429	9	7	9	7	6	3	9
Future Volume (Veh/h)	6	539	5	11	429	9	7	9	7	6	3	9
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	7	627	6	13	499	10	8	10	8	7	3	10
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	509			633			1180	1179	632	1186	1177	504
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	509			633			1180	1179	632	1186	1177	504
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			99			95	95	98	95	98	98
cM capacity (veh/h)	1066			882			161	188	483	155	189	572
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	7	633	13	509	26	20						
Volume Left	7	0	13	0	8	7						
Volume Right	0	6	0	10	8	10						
cSH	1066	1700	882	1700	218	254						
Volume to Capacity	0.01	0.37	0.01	0.30	0.12	0.08						
Queue Length 95th (m)	0.2	0.0	0.4	0.0	3.2	2.0						
Control Delay (s)	8.4	0.0	9.1	0.0	23.8	20.4						
Lane LOS	A	0.0	A	0.0	C	C						
Approach Delay (s)	0.1		0.2		23.8	20.4						
Approach LOS	0.1		0.2		C	C						
Intersection Summary												
Average Delay			1.0									
Intersection Capacity Utiliza	ation		39.3%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

C.F Crozier & Associates

Synchro 11 Light Report
Page 1

	۶	→	•	•	←	•	•	†	<i>></i>	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	4	0	0	0	20	1	0	15	0
Future Volume (Veh/h)	0	0	0	4	0	0	0	20	1	0	15	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	0	0	0	6	0	0	0	29	1	0	22	0
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	52	56	23	54	56	32	23			33		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	52	56	23	54	56	32	23			33		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	99	100	100	100			100		
cM capacity (veh/h)	943	832	1053	744	833	1044	1604			1588		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	6	30	22								
Volume Left	0	6	0	0								
Volume Right	0	0	1	0								
cSH	1700	744	1604	1588								
Volume to Capacity	0.00	0.01	0.00	0.00								
Queue Length 95th (m)	0.0	0.2	0.0	0.0								
Control Delay (s)	0.0	9.9	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	9.9	0.0	0.0								
Approach LOS	Α	Α										
Intersection Summary												
Average Delay			1.0									
Intersection Capacity Utiliza	tion		14.3%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	→	•	•	•	•	4	†	<i>></i>	>	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	1	3	3	3	3	4	0	19	10	12	22	1
Future Volume (vph)	1	3	3	3	3	4	0	19	10	12	22	1
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	1	3	3	3	3	5	0	22	11	14	25	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	7	11	33	40								
Volume Left (vph)	1	3	0	14								
Volume Right (vph)	3	5	11	1								
Hadj (s)	-0.19	-0.18	-0.17	0.09								
Departure Headway (s)	3.9	3.9	3.8	4.1								
Degree Utilization, x	0.01	0.01	0.03	0.05								
Capacity (veh/h)	907	907	936	878								
Control Delay (s)	6.9	6.9	6.9	7.2								
Approach Delay (s)	6.9	6.9	6.9	7.2								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.1									
Level of Service			Α									
Intersection Capacity Utilizat	ion		20.6%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	/	>	ļ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		f)			ર્ન
Traffic Volume (veh/h)	1	0	3	1	0	3
Future Volume (Veh/h)	1	0	3	1	0	3
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50
Hourly flow rate (vph)	2	0	6	2	0	6
Pedestrians	3					
Lane Width (m)	3.6					
Walking Speed (m/s)	1.2					
Percent Blockage	0					
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	16	10			11	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	16	10			11	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1005	1075			1617	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	2	8	6			
Volume Left	2	0	0			
Volume Right	0	2	0			
cSH	1005	1700	1617			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	A		,,,			
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	A		3.0			
Intersection Summary						
Average Delay			1.1			
Intersection Capacity Utiliza	ation		14.3%	IC	U Level c	f Service
Analysis Period (min)			15			

	۶	→	•	•	—	4	1	†	~	/	+	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	ሻ	1>		ሻ	ĵ₃			4			4	
Traffic Volume (veh/h)	4	588	12	19	722	9	23	4	22	13	9	16
Future Volume (Veh/h)	4	588	12	19	722	9	23	4	22	13	9	16
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	4	619	13	20	760	9	24	4	23	14	9	17
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	769			632			1457	1442	626	1456	1444	766
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	769			632			1457	1442	626	1456	1444	766
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			98			75	97	95	86	93	96
cM capacity (veh/h)	854			960			97	130	462	99	130	405
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	4	632	20	769	51	40						
Volume Left	4	032	20	0	24	14						
	0	13	0	9	23	17						
Volume Right cSH	854	1700	960	1700	155	158						
		0.37		0.45		0.25						
Volume to Capacity	0.00	0.57	0.02	0.45	0.33 10.7	7.6						
Queue Length 95th (m)												
Control Delay (s)	9.2	0.0	8.8	0.0	39.2	35.3						
Lane LOS	A		A		E	E 25.0						
Approach LOS	0.1		0.2		39.2	35.3						
Approach LOS					Е	Е						
Intersection Summary												
Average Delay			2.4									
Intersection Capacity Utilizat	tion		49.5%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

C.F Crozier & Associates

Synchro 11 Light Report

Page 1

	•	→	•	•	+	•	•	†	/	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	0	0	1	0	38	0	0	38	0
Future Volume (Veh/h)	0	0	0	0	0	1	0	38	0	0	38	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	0	0	0	0	0	1	0	52	0	0	52	0
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	107	111	54	109	111	57	54			57		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	107	111	54	109	111	57	54			57		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	100	100	100	100			100		
cM capacity (veh/h)	866	775	1011	867	775	1011	1549			1541		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	1	52	52								
Volume Left	0	0	0	0								
	0	1	0	0								
Volume Right cSH												
	1700	1011	1549	1541								
Volume to Capacity	0.00	0.00	0.00	0.00								
Queue Length 95th (m)	0.0	0.0	0.0	0.0								
Control Delay (s)	0.0	8.6	0.0	0.0								
Lane LOS	A	A	0.0	0.0								
Approach Delay (s)	0.0	8.6	0.0	0.0								
Approach LOS	А	Α										
Intersection Summary												
Average Delay			0.1						_			
Intersection Capacity Utiliza	ation		14.9%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

C.F Crozier & Associates

Synchro 11 Light Report
Page 2

	۶	→	•	•	←	•	4	†	/	\	ţ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	0	1	0	10	6	12	0	43	4	13	56	1
Future Volume (vph)	0	1	0	10	6	12	0	43	4	13	56	1
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	0	1	0	11	7	13	0	48	4	15	63	1
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	1	31	52	79								
Volume Left (vph)	0	11	0	15								
Volume Right (vph)	0	13	4	1								
Hadj (s)	0.03	-0.15	-0.01	0.06								
Departure Headway (s)	4.2	4.0	4.0	4.1								
Degree Utilization, x	0.00	0.03	0.06	0.09								
Capacity (veh/h)	816	861	871	869								
Control Delay (s)	7.3	7.2	7.3	7.5								
Approach Delay (s)	7.3	7.2	7.3	7.5								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.4									
Level of Service			Α									
Intersection Capacity Utilization	n		26.9%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	~	\	ţ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		f)			ર્ન
Traffic Volume (veh/h)	3	0	4	0	0	4
Future Volume (Veh/h)	3	0	4	0	0	4
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56
Hourly flow rate (vph)	5	0	7	0	0	7
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	14	7			7	
vC1, stage 1 conf vol	• • •	•			•	
vC2, stage 2 conf vol						
vCu, unblocked vol	14	7			7	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	V. 1	0.2				
tF (s)	3.5	3.3			2.2	
p0 queue free %	100	100			100	
cM capacity (veh/h)	1010	1081			1627	
					1021	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	5	7	7			
Volume Left	5	0	0			
Volume Right	0	0	0			
cSH	1010	1700	1627			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.1	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	Α					
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	Α					
Intersection Summary						
Average Delay			2.3			
Intersection Capacity Utiliza	ation		13.3%	IC	U Level o	f Service
Analysis Period (min)	adon		15.5 %	10	O LOVEI U	1 OCIVICE
Alialysis Fellou (IIIIII)			10			

	۶	→	•	•	—	4	1	†	<i>></i>	/	†	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		7	î»			4			4	
Traffic Volume (veh/h)	4	423	8	16	331	7	14	7	16	4	2	7
Future Volume (Veh/h)	4	423	8	16	331	7	14	7	16	4	2	7
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	5	492	9	19	385	8	16	8	19	5	2	8
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	393			501			938	938	498	954	938	389
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	393			501			938	938	498	954	938	389
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												0.=
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	100			98			93	97	97	98	99	99
cM capacity (veh/h)	1177			990			238	260	575	223	260	664
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	5	501	19	393	43	15						
Volume Left	5	0	19	0	16	5						
Volume Right	0	9	0	8	19	8						
cSH	1177	1700	990	1700	328	355						
Volume to Capacity	0.00	0.29	0.02	0.23	0.13	0.04						
Queue Length 95th (m)	0.00	0.29	0.02	0.23	3.6	1.1						
Control Delay (s)	8.1	0.0	8.7	0.0	17.6	15.6						
Lane LOS	Α	0.0	Α	0.0	17.0	C						
Approach Delay (s)	0.1		0.4		17.6	15.6						
Approach LOS	0.1		0.4		17.0	C						
••					U	U						
Intersection Summary			4.0									
Average Delay	.t'		1.2	1,0	NIII.				Α.			
Intersection Capacity Utiliza	ation		33.4%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

C. F. Crozier & Associates

Synchro 11 Light Report
Page 1

	۶	→	•	•	←	•	•	†	/	/	↓	✓
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	18	0	6	3	0	0	4	17	1	0	12	11
Future Volume (Veh/h)	18	0	6	3	0	0	4	17	1	0	12	11
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	26	0	9	4	0	0	6	25	1	0	17	16
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	64	67	26	74	74	28	34			29		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	64	67	26	74	74	28	34			29		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	97	100	99	99	100	100	100			100		
cM capacity (veh/h)	925	818	1049	712	810	1050	1589			1593		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	35	4	32	33								
Volume Left	26	4	6	0								
Volume Right	9	0	1	16								
cSH	954	712	1589	1593								
Volume to Capacity	0.04	0.01	0.00	0.00								
Queue Length 95th (m)	0.9	0.1	0.1	0.0								
Control Delay (s)	8.9	10.1	1.4	0.0								
Lane LOS	Α	В	Α									
Approach Delay (s)	8.9	10.1	1.4	0.0								
Approach LOS	Α	В										
Intersection Summary												
Average Delay			3.8									
Intersection Capacity Utilizat	tion		15.3%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report Page 2 C. F. Crozier & Associates

	۶	→	•	•	←	•	4	†	/	>	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↔			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	5	2	2	3	4	0	16	8	10	21	2
Future Volume (vph)	2	5	2	2	3	4	0	16	8	10	21	2
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	2	6	2	2	3	5	0	18	9	11	24	2
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	10	10	27	37								
Volume Left (vph)	2	2	0	11								
Volume Right (vph)	2	5	9	2								
Hadj (s)	-0.05	-0.23	-0.17	0.06								
Departure Headway (s)	4.0	3.8	3.8	4.0								
Degree Utilization, x	0.01	0.01	0.03	0.04								
Capacity (veh/h)	880	922	935	884								
Control Delay (s)	7.0	6.9	6.9	7.2								
Approach Delay (s)	7.0	6.9	6.9	7.2								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.1									
Level of Service			Α									
Intersection Capacity Utilizat	ion		20.5%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report Page 3 C. F. Crozier & Associates

	•	•	†	~	>	ţ	_
Movement	WBL	WBR	NBT	NBR	SBL	SBT	
Lane Configurations	W		f)			ર્ન	
Traffic Volume (veh/h)	5	0	2	3	0	2	
Future Volume (Veh/h)	5	0	2	3	0	2	
Sign Control	Stop		Free			Free	
Grade	0%		0%			0%	
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50	
Hourly flow rate (vph)	10	0	4	6	0	4	
Pedestrians	3						
Lane Width (m)	3.6						
Walking Speed (m/s)	1.2						
Percent Blockage	0						
Right turn flare (veh)							
Median type			None			None	
Median storage veh)							
Upstream signal (m)							
pX, platoon unblocked							
vC, conflicting volume	14	10			13		
vC1, stage 1 conf vol							
vC2, stage 2 conf vol							
vCu, unblocked vol	14	10			13		
tC, single (s)	6.4	6.2			4.1		
tC, 2 stage (s)							
tF (s)	3.5	3.3			2.2		
p0 queue free %	99	100			100		
cM capacity (veh/h)	1008	1075			1615		
Direction, Lane #	WB 1	NB 1	SB 1				
Volume Total	10	10	4				
Volume Left	10	0	0				
Volume Right	0	6	0				
cSH	1008	1700	1615				
Volume to Capacity	0.01	0.01	0.00				
Queue Length 95th (m)	0.2	0.0	0.0				
Control Delay (s)	8.6	0.0	0.0				
Lane LOS	A		2.0				
Approach Delay (s)	8.6	0.0	0.0				
Approach LOS	A		<i>5.0</i>				
Intersection Summary							
Average Delay			3.6				
Intersection Capacity Utiliz	ation		14.3%	IC	U Level o	f Service	
Analysis Period (min)			15				
,							

	-	\rightarrow	•	←	•	/
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	f)		ሻ		*/*	
Traffic Volume (veh/h)	407	20	21	331	26	28
Future Volume (Veh/h)	407	20	21	331	26	28
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	473	23	24	385	30	33
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume			496		918	484
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			496		918	484
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					3. .	
tF (s)			2.2		3.5	3.3
p0 queue free %			98		90	94
cM capacity (veh/h)			1068		295	582
	ED 4	14/D 4		ND 4		
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	496	24	385	63		
Volume Left	0	24	0	30		
Volume Right	23	0	0	33		
cSH	1700	1068	1700	398		
Volume to Capacity	0.29	0.02	0.23	0.16		
Queue Length 95th (m)	0.0	0.6	0.0	4.5		
Control Delay (s)	0.0	8.4	0.0	15.7		
Lane LOS		Α		С		
Approach Delay (s)	0.0	0.5		15.7		
Approach LOS				С		
Intersection Summary						
Average Delay			1.2			
Intersection Capacity Utiliza	ation		32.6%	IC	U Level o	f Service
Analysis Period (min)			15			

Synchro 11 Light Report Page 5 C. F. Crozier & Associates

	•	→	+	•	\	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		4	1>		**	
Traffic Volume (veh/h)	1	7	4	1	3	3
Future Volume (Veh/h)	1	7	4	1	3	3
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	1	8	5	1	3	3
Pedestrians		-		-	-	
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)		110110	140110			
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	6				16	6
vC1, stage 1 conf vol	0				10	0
vC2, stage 2 conf vol						
vCu, unblocked vol	6				16	6
tC, single (s)	4.1				6.4	6.2
tC, 2 stage (s)	7.1				0.4	0.2
tF (s)	2.2				3.5	3.3
p0 queue free %	100				100	100
cM capacity (veh/h)	1615				1002	1077
					1002	1011
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	9	6	6			
Volume Left	1	0	3			
Volume Right	0	1	3			
cSH	1615	1700	1039			
Volume to Capacity	0.00	0.00	0.01			
Queue Length 95th (m)	0.0	0.0	0.1			
Control Delay (s)	0.8	0.0	8.5			
Lane LOS	Α		Α			
Approach Delay (s)	0.8	0.0	8.5			
Approach LOS			Α			
Intersection Summary						
Average Delay			2.8			
Intersection Capacity Utiliza	ation		13.3%	IC	III evel d	of Service
Analysis Period (min)	ation		15.570	10	O LOVOI C	/ OCI VICC
Alialysis i cliou (IIIII)			10			

	۶	-	•	•	—	•	•	†	<i>></i>	/	ļ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	¥	f)		7	f)			4			4	
Traffic Volume (veh/h)	3	458	18	28	562	7	24	3	26	10	7	12
Future Volume (Veh/h)	3	458	18	28	562	7	24	3	26	10	7	12
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	3	482	19	29	592	7	25	3	27	11	7	13
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	599			501			1166	1154	492	1170	1160	598
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	599			501			1166	1154	492	1170	1160	598
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			97			84	98	95	93	96	97
cM capacity (veh/h)	988			1074			159	193	552	157	191	505
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	3	501	29	599	55	31						
Volume Left	3	0	29	0	25	11						
Volume Right	0	19	0	7	27	13						
cSH	988	1700	1074	1700	248	234						
Volume to Capacity	0.00	0.29	0.03	0.35	0.22	0.13						
Queue Length 95th (m)	0.1	0.0	0.7	0.0	6.6	3.6						
Control Delay (s)	8.7	0.0	8.4	0.0	23.6	22.7						
Lane LOS	Α		Α		С	С						
Approach Delay (s)	0.1		0.4		23.6	22.7						
Approach LOS					С	С						
Intersection Summary												
Average Delay			1.9									
Intersection Capacity Utilization	1		41.2%	IC	CU Level o	f Service			Α			
Analysis Period (min)			15									

	۶	→	•	€	+	•	•	†	<i>></i>	/	↓	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	16	0	7	0	0	1	8	29	0	0	30	21
Future Volume (Veh/h)	16	0	7	0	0	1	8	29	0	0	30	21
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	22	0	10	0	0	1	11	40	0	0	41	29
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	120	124	58	132	139	45	72			45		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	120	124	58	132	139	45	72			45		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	97	100	99	100	100	100	99			100		
cM capacity (veh/h)	844	756	1007	824	742	1026	1526			1557		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	32	1	51	70								
Volume Left	22	0	11	0								
Volume Right	10	1	0	29								
cSH	889	1026	1526	1557								
Volume to Capacity	0.04	0.00	0.01	0.00								
Queue Length 95th (m)	0.9	0.0	0.2	0.0								
Control Delay (s)	9.2	8.5	1.6	0.0								
Lane LOS	Α.Δ	Α	Α	0.0								
Approach Delay (s)	9.2	8.5	1.6	0.0								
Approach LOS	Α.Δ	Α	1.0	0.0								
Intersection Summary												
Average Delay			2.5									
Intersection Capacity Utilizat	tion			10	و امریما و	of Service			٨			
	UUII		23.9%	IC	O Level (JI SELVICE			A			
Analysis Period (min)			15									

	ၨ	→	•	•	•	•	•	†	<i>></i>	\	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	2	0	8	6	11	0	36	3	12	45	3
Future Volume (vph)	2	2	0	8	6	11	0	36	3	12	45	3
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	2	2	0	9	7	12	0	40	3	13	51	3
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	4	28	43	67								
Volume Left (vph)	2	9	0	13								
Volume Right (vph)	0	12	3	3								
Hadj (s)	0.13	-0.16	-0.01	0.05								
Departure Headway (s)	4.3	4.0	4.0	4.1								
Degree Utilization, x	0.00	0.03	0.05	0.08								
Capacity (veh/h)	811	876	873	875								
Control Delay (s)	7.3	7.1	7.2	7.4								
Approach Delay (s)	7.3	7.1	7.2	7.4								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.3									
Level of Service			Α									
Intersection Capacity Utilization	n		22.5%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	~	>	ţ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		f)			ર્ન
Traffic Volume (veh/h)	5	0	3	4	0	3
Future Volume (Veh/h)	5	0	3	4	0	3
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56
Hourly flow rate (vph)	9	0	5	7	0	5
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)			•			
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	14	8			12	
vC1, stage 1 conf vol	• • •					
vC2, stage 2 conf vol						
vCu, unblocked vol	14	8			12	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)	V. 1	0.2				
tF (s)	3.5	3.3			2.2	
p0 queue free %	99	100			100	
cM capacity (veh/h)	1011	1079			1620	
					1020	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	9	12	5			
Volume Left	9	0	0			
Volume Right	0	7	0			
cSH	1011	1700	1620			
Volume to Capacity	0.01	0.01	0.00			
Queue Length 95th (m)	0.2	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	Α					
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	Α					
Intersection Summary						
Average Delay			3.0			
Intersection Capacity Utiliza	ation		13.3%	IC	U Level o	f Service
Analysis Period (min)	adon		15.5 %	10	O LOVEI U	1 OCT VICE
Alialysis Fellou (IIIIII)			10			

	-	•	•	←	•	~	
Movement	EBT	EBR	WBL	WBT	NBL	NBR	
Lane Configurations	<u> </u>		ሻ	<u> </u>	¥		
Traffic Volume (veh/h)	445	40	41	558	31	33	
Future Volume (Veh/h)	445	40	41	558	31	33	
Sign Control	Free			Free	Stop		
Grade	0%			0%	0%		
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	
Hourly flow rate (vph)	468	42	43	587	33	35	
Pedestrians							
Lane Width (m)							
Walking Speed (m/s)							
Percent Blockage							
Right turn flare (veh)							
Median type	None			None			
Median storage veh)							
Upstream signal (m)							
pX, platoon unblocked							
vC, conflicting volume			510		1162	489	
vC1, stage 1 conf vol							
vC2, stage 2 conf vol							
vCu, unblocked vol			510		1162	489	
tC, single (s)			4.1		6.4	6.2	
tC, 2 stage (s)							
tF (s)			2.2		3.5	3.3	
p0 queue free %			96		84	94	
cM capacity (veh/h)			1055		207	579	
Direction, Lane #	EB 1	WB 1	WB 2	NB 1			
Volume Total	510	43	587	68			
Volume Left	0	43	0	33			
Volume Right	42	0	0	35			
cSH	1700	1055	1700	309			
Volume to Capacity	0.30	0.04	0.35	0.22			
Queue Length 95th (m)	0.0	1.0	0.0	6.6			
Control Delay (s)	0.0	8.6	0.0	19.9			
Lane LOS		Α		С			
Approach Delay (s)	0.0	0.6		19.9			
Approach LOS				С			
Intersection Summary							
Average Delay			1.4				
Intersection Capacity Utilization	ation		42.9%	IC	U Level c	of Service	
Analysis Period (min)			15				
,							

	•	→	+	•	\	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		ર્ન	ĵ»		W	
Traffic Volume (veh/h)	2	3	8	2	1	1
Future Volume (Veh/h)	2	3	8	2	1	1
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	2	3	8	2	1	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)		140110	140110			
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	10				16	9
vC1, stage 1 conf vol	10				10	3
vC2, stage 2 conf vol						
vCu, unblocked vol	10				16	9
tC, single (s)	4.1				6.4	6.2
	4.1				0.4	0.2
tC, 2 stage (s)	2.2				3.5	3.3
tF (s)	100				100	100
p0 queue free %						
cM capacity (veh/h)	1610				1001	1073
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	5	10	2			
Volume Left	2	0	1			
Volume Right	0	2	1			
cSH	1610	1700	1036			
Volume to Capacity	0.00	0.01	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	2.9	0.0	8.5			
Lane LOS	Α		Α			
Approach Delay (s)	2.9	0.0	8.5			
Approach LOS			Α			
Intersection Summary						
Average Delay			1.9			
Intersection Capacity Utiliza	ation		13.3%	IC		of Service
Analysis Period (min)	ation		15.5 / 15	10	O Level C	JI OCI VICE
Alialysis Fellou (IIIIII)			13			

	۶	→	•	•	←	•	•	†	~	/	ţ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	1>		ሻ	f.			4			4	
Traffic Volume (veh/h)	5	465	9	16	364	7	15	7	16	5	2	7
Future Volume (Veh/h)	5	465	9	16	364	7	15	7	16	5	2	7
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	6	541	10	19	423	8	17	8	19	6	2	8
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	431			551			1028	1027	548	1043	1028	427
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	431			551			1028	1027	548	1043	1028	427
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			98			92	97	96	97	99	99
cM capacity (veh/h)	1139			948			206	230	539	192	230	632
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	6	551	19	431	44	16						
Volume Left	6	0	19	0	17	6						
Volume Right	0	10	0	8	19	8						
cSH	1139	1700	948	1700	289	305						
Volume to Capacity	0.01	0.32	0.02	0.25	0.15	0.05						
Queue Length 95th (m)	0.1	0.0	0.5	0.0	4.2	1.3						
Control Delay (s)	8.2	0.0	8.9	0.0	19.7	17.5						
Lane LOS	Α	0.0	A	0.0	C	C						
Approach Delay (s)	0.1		0.4		19.7	17.5						
Approach LOS	0.1		0.1		C	C						
Intersection Summary												
Average Delay			1.3									
Intersection Capacity Utiliza	tion		35.7%	IC	CU Level c	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	←	•	•	†	/	/	↓	√
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	18	0	6	4	0	0	4	18	1	0	13	11
Future Volume (Veh/h)	18	0	6	4	0	0	4	18	1	0	13	11
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	26	0	9	6	0	0	6	26	1	0	19	16
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	66	70	28	78	78	30	36			30		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	66	70	28	78	78	30	36			30		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	97	100	99	99	100	100	100			100		
cM capacity (veh/h)	921	815	1046	708	807	1048	1587			1592		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	35	6	33	35								
Volume Left	26	6	6	0								
Volume Right	9	0	1	16								
cSH	950	708	1587	1592								
Volume to Capacity	0.04	0.01	0.00	0.00								
Queue Length 95th (m)	0.04	0.01	0.00	0.0								
Control Delay (s)	8.9	10.1	1.3	0.0								
Lane LOS	0.5 A	В	Α	0.0								
Approach Delay (s)	8.9	10.1	1.3	0.0								
Approach LOS	0.9 A	В	1.0	0.0								
• •	A	ט										
Intersection Summary			2.0									
Average Delay	t:		3.8	10	المنتمالة	4 Carrie			Λ			
Intersection Capacity Utiliza	แงก		15.3%	IC	U Level (of Service			Α			
Analysis Period (min)			15									

C.F Crozier & Associates

Synchro 11 Light Report
Page 2

	۶	→	•	•	•	•	•	†	<i>></i>	\	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	5	2	2	3	5	0	18	9	11	22	2
Future Volume (vph)	2	5	2	2	3	5	0	18	9	11	22	2
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	2	6	2	2	3	6	0	20	10	12	25	2
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	10	11	30	39								
Volume Left (vph)	2	2	0	12								
Volume Right (vph)	2	6	10	2								
Hadj (s)	-0.05	-0.26	-0.17	0.06								
Departure Headway (s)	4.0	3.8	3.8	4.0								
Degree Utilization, x	0.01	0.01	0.03	0.04								
Capacity (veh/h)	877	926	924	882								
Control Delay (s)	7.1	6.8	6.9	7.2								
Approach Delay (s)	7.1	6.8	6.9	7.2								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.1									_
Level of Service			Α									
Intersection Capacity Utilization	on		20.6%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	/	>	↓	
Movement	WBL	WBR	NBT	NBR	SBL	SBT	
Lane Configurations	W		ĵ∍			4	
Traffic Volume (veh/h)	5	0	2	3	0	2	
Future Volume (Veh/h)	5	0	2	3	0	2	
Sign Control	Stop		Free			Free	
Grade	0%		0%			0%	
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50	
Hourly flow rate (vph)	10	0	4	6	0	4	
Pedestrians	3						
Lane Width (m)	3.6						
Walking Speed (m/s)	1.2						
Percent Blockage	0						
Right turn flare (veh)							
Median type			None			None	
Median storage veh)							
Upstream signal (m)							
pX, platoon unblocked							
vC, conflicting volume	14	10			13		
vC1, stage 1 conf vol							
vC2, stage 2 conf vol							
vCu, unblocked vol	14	10			13		
tC, single (s)	6.4	6.2			4.1		
tC, 2 stage (s)							
tF (s)	3.5	3.3			2.2		
p0 queue free %	99	100			100		
cM capacity (veh/h)	1008	1075			1615		
Direction, Lane #	WB 1	NB 1	SB 1				
Volume Total	10	10	4				
Volume Left	10	0	0				
Volume Right	0	6	0				
cSH	1008	1700	1615				
Volume to Capacity	0.01	0.01	0.00				
Queue Length 95th (m)	0.2	0.0	0.0				
Control Delay (s)	8.6	0.0	0.0				
Lane LOS	A	0.0	0.0				
Approach Delay (s)	8.6	0.0	0.0				
Approach LOS	A	0.0	<u> </u>				
Intersection Summary							
			3.6				
Average Delay	ration			10	ا ا ا میرما د	of Consider	
Intersection Capacity Utiliz	2a(10f1		14.3%	iC	O Level (of Service	
Analysis Period (min)			15				

	→	\rightarrow	•	•	•	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1 >		ሻ	*	¥#	
Traffic Volume (veh/h)	449	20	21	365	26	28
Future Volume (Veh/h)	449	20	21	365	26	28
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	522	23	24	424	30	33
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume			545		1006	534
vC1, stage 1 conf vol			<u> </u>			
vC2, stage 2 conf vol						
vCu, unblocked vol			545		1006	534
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)					J. 1	
tF (s)			2.2		3.5	3.3
p0 queue free %			98		89	94
cM capacity (veh/h)			1024		261	546
	ED 4	MD 4		ND 4	_••	
Direction, Lane # Volume Total	EB 1 545	WB 1	WB 2 424	NB 1 63		
		24 24		30		
Volume Left	0 23	0	0	33		
Volume Right			0			
cSH	1700	1024	1700	359		
Volume to Capacity	0.32	0.02	0.25	0.18		
Queue Length 95th (m)	0.0	0.6	0.0	5.0		
Control Delay (s)	0.0	8.6	0.0	17.1		
Lane LOS		A		C		
Approach Delay (s)	0.0	0.5		17.1		
Approach LOS				С		
Intersection Summary						
Average Delay			1.2			
Intersection Capacity Utiliza	ation		34.8%	IC	U Level o	f Service
Analysis Period (min)			15			

	•	→	+	4	/	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		ર્ન	ĵ»		W	
Traffic Volume (veh/h)	1	7	5	1	3	3
Future Volume (Veh/h)	1	7	5	1	3	3
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	1	8	6	1	3	3
Pedestrians		-		-		
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)		110110	140110			
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	7				16	6
vC1, stage 1 conf vol	'				10	U U
vC2, stage 2 conf vol						
vCu, unblocked vol	7				16	6
tC, single (s)	4.1				6.4	6.2
tC, 2 stage (s)	7.1				0.7	0.2
tF (s)	2.2				3.5	3.3
p0 queue free %	100				100	100
cM capacity (veh/h)	1614				1001	1076
					1001	1070
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	9	7	6			
Volume Left	1	0	3			
Volume Right	0	1	3			
cSH	1614	1700	1037			
Volume to Capacity	0.00	0.00	0.01			
Queue Length 95th (m)	0.0	0.0	0.1			
Control Delay (s)	0.8	0.0	8.5			
Lane LOS	Α		Α			
Approach Delay (s)	0.8	0.0	8.5			
Approach LOS			Α			
Intersection Summary						
Average Delay			2.6			
Intersection Capacity Utiliza	ation		13.3%	IC	Ulevelo	of Service
Analysis Period (min)	ation		15.570	10	O LOVOI C	JI OCI VICC
Alialysis i cliou (Illill)			10			

	۶	-	•	•	—	•	1	†	<i>></i>	/	ţ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		7	f)			4			4	
Traffic Volume (veh/h)	4	503	18	29	618	7	26	4	28	11	7	13
Future Volume (Veh/h)	4	503	18	29	618	7	26	4	28	11	7	13
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	4	529	19	31	651	7	27	4	29	12	7	14
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	658			548			1279	1266	538	1284	1272	656
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	658			548			1279	1266	538	1284	1272	656
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			97			79	98	94	91	96	97
cM capacity (veh/h)	939			1032			132	165	518	129	163	468
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	4	548	31	658	60	33						
Volume Left	4	0	31	0	27	12						
Volume Right	0	19	0	7	29	14						
cSH	939	1700	1032	1700	210	199						
Volume to Capacity	0.00	0.32	0.03	0.39	0.29	0.17						
Queue Length 95th (m)	0.1	0.0	0.7	0.0	9.0	4.6						
Control Delay (s)	8.8	0.0	8.6	0.0	28.8	26.6						
Lane LOS	Α		Α		D	D						
Approach Delay (s)	0.1		0.4		28.8	26.6						
Approach LOS					D	D						
Intersection Summary												
Average Delay			2.2									
Intersection Capacity Utilization	า		44.5%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

C.F Crozier & Associates

Synchro 11 Light Report

Page 1

	۶	→	•	•	+	•	•	†	/	/	↓	-√
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	16	0	7	0	0	1	8	32	0	0	33	21
Future Volume (Veh/h)	16	0	7	0	0	1	8	32	0	0	33	21
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	22	0	10	0	0	1	11	44	0	0	45	29
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	128	132	62	140	147	49	76			49		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	128	132	62	140	147	49	76			49		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	97	100	99	100	100	100	99			100		
cM capacity (veh/h)	834	748	1002	814	735	1021	1520			1551		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	32	1	55	74								
Volume Left	22	0	11	0								
Volume Right	10	1	0	29								
cSH	880	1021	1520	1551								
Volume to Capacity	0.04	0.00	0.01	0.00								
Queue Length 95th (m)	0.04	0.00	0.01	0.00								
	9.2	8.5	1.5	0.0								
Control Delay (s)				0.0								
Lane LOS	A	Α ο ε	A 1.5	0.0								
Approach LOS	9.2	8.5	1.5	0.0								
Approach LOS	А	Α										
Intersection Summary												
Average Delay			2.4									
Intersection Capacity Utilizat	ion		24.0%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	•	•	•	†	<i>></i>	\	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	2	0	9	7	12	0	39	4	13	49	3
Future Volume (vph)	2	2	0	9	7	12	0	39	4	13	49	3
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	2	2	0	10	8	13	0	44	4	15	55	3
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	4	31	48	73								
Volume Left (vph)	2	10	0	15								
Volume Right (vph)	0	13	4	3								
Hadj (s)	0.13	-0.15	-0.02	0.05								
Departure Headway (s)	4.3	4.0	4.0	4.1								
Degree Utilization, x	0.00	0.03	0.05	0.08								
Capacity (veh/h)	804	868	871	871								
Control Delay (s)	7.3	7.2	7.3	7.4								
Approach Delay (s)	7.3	7.2	7.3	7.4								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.3									
Level of Service			Α									
Intersection Capacity Utilization	n		22.7%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	4	†	<i>></i>	/	
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		î,			4
Traffic Volume (veh/h)	5	0	4	4	0	4
Future Volume (Veh/h)	5	0	4	4	0	4
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56
Hourly flow rate (vph)	9	0	7	7	0	7
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	18	10			14	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	18	10			14	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	99	100			100	
cM capacity (veh/h)	1006	1077			1617	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	9	14	7			
Volume Left	9	0	0			
Volume Right	0	7	0			
cSH	1006	1700	1617			
Volume to Capacity	0.01	0.01	0.00			
Queue Length 95th (m)	0.2	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	Α					
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	А					
Intersection Summary						
Average Delay			2.6			
Intersection Capacity Utiliz	zation		13.3%	IC	U Level o	of Service
Analysis Period (min)			15			

	-	•	•	←	4	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	f		ሻ	†	¥#	
Traffic Volume (veh/h)	491	40	41	616	31	33
Future Volume (Veh/h)	491	40	41	616	31	33
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	517	42	43	648	33	35
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume			559		1272	538
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			559		1272	538
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			96		81	94
cM capacity (veh/h)			1012		177	543
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	559	43	648	68		
Volume Left	0	43	0	33		
Volume Right	42	0	0	35		
cSH	1700	1012	1700	271		
Volume to Capacity	0.33	0.04	0.38	0.25		
Queue Length 95th (m)	0.0	1.1	0.0	7.7		
Control Delay (s)	0.0	8.7	0.0	22.7		
Lane LOS		Α		С		
Approach Delay (s)	0.0	0.5		22.7		
Approach LOS				С		
Intersection Summary						
Average Delay			1.5			
Intersection Capacity Utiliza	ition		44.5%	IC	U Level c	f Service
Analysis Period (min)			15			

	•	→	+	•	\	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		ર્ન	ĵ»		W	
Traffic Volume (veh/h)	2	3	8	2	1	1
Future Volume (Veh/h)	2	3	8	2	1	1
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	2	3	8	2	1	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)		140110	140110			
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	10				16	9
vC1, stage 1 conf vol	10				10	3
vC2, stage 2 conf vol						
vCu, unblocked vol	10				16	9
tC, single (s)	4.1				6.4	6.2
	4.1				0.4	0.2
tC, 2 stage (s)	2.2				3.5	3.3
tF (s)	100				100	100
p0 queue free %						
cM capacity (veh/h)	1610				1001	1073
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	5	10	2			
Volume Left	2	0	1			
Volume Right	0	2	1			
cSH	1610	1700	1036			
Volume to Capacity	0.00	0.01	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	2.9	0.0	8.5			
Lane LOS	Α		Α			
Approach Delay (s)	2.9	0.0	8.5			
Approach LOS			Α			
Intersection Summary						
Average Delay			1.9			
Intersection Capacity Utiliza	ation		13.3%	IC		of Service
Analysis Period (min)	ation		15.5 / 15	10	O Level C	JI OCI VICE
Alialysis Fellou (IIIIII)			13			

	۶	→	•	•	—	4	1	†	~	/	+	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		7	₽			4			4	
Traffic Volume (veh/h)	6	561	9	18	441	9	15	9	17	6	3	9
Future Volume (Veh/h)	6	561	9	18	441	9	15	9	17	6	3	9
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	7	652	10	21	513	10	17	10	20	7	3	10
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	523			662			1238	1236	659	1253	1236	518
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	523			662			1238	1236	659	1253	1236	518
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												0.=
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			98			88	94	96	95	98	98
cM capacity (veh/h)	1054			859			146	172	466	134	172	562
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	<u> </u>	662	21	523	47	20						
Volume Left	7	002	21	0	17	7						
	0	10	0	10	20	10						
Volume Right cSH			859	1700	216	229						
	1054	1700 0.39		0.31		0.09						
Volume to Capacity	0.01	0.09	0.02	0.0	0.22 6.4	2.3						
Queue Length 95th (m)	8.4											
Control Delay (s)		0.0	9.3	0.0	26.2	22.2						
Lane LOS	Α		A		D	C						
Approach LOS	0.1		0.4		26.2	22.2						
Approach LOS					D	С						
Intersection Summary												
Average Delay			1.5									
Intersection Capacity Utiliza	ation		40.7%	IC	CU Level of	of Service			Α			
Analysis Period (min)			15									

C.F Crozier & Associates

Synchro 11 Light Report

Page 1

	۶	→	•	•	—	•	•	†	<i>></i>	/	↓	-√
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	18	0	6	4	0	0	4	20	1	0	15	11
Future Volume (Veh/h)	18	0	6	4	0	0	4	20	1	0	15	11
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	26	0	9	6	0	0	6	29	1	0	22	16
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	72	76	31	84	84	32	39			33		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	72	76	31	84	84	32	39			33		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	97	100	99	99	100	100	100			100		
cM capacity (veh/h)	913	809	1042	701	801	1044	1583			1588		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	35	6	36	38								
Volume Left	26	6	6	0								
Volume Right	9	0	1	16								
cSH	943	701	1583	1588								
Volume to Capacity	0.04	0.01	0.00	0.00								
Queue Length 95th (m)	0.9	0.2	0.1	0.0								
Control Delay (s)	9.0	10.2	1.2	0.0								
Lane LOS	A	В	Α									
Approach Delay (s)	9.0	10.2	1.2	0.0								
Approach LOS	Α	В										
Intersection Summary												
Average Delay			3.6									
Intersection Capacity Utiliza	ation		15.4%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	←	•	4	†	/	>	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	6	3	3	4	5	0	21	10	13	26	2
Future Volume (vph)	2	6	3	3	4	5	0	21	10	13	26	2
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	2	7	3	3	5	6	0	24	11	15	30	2
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	12	14	35	47								
Volume Left (vph)	2	3	0	15								
Volume Right (vph)	3	6	11	2								
Hadj (s)	-0.08	-0.18	-0.15	0.07								
Departure Headway (s)	4.0	3.9	3.8	4.1								
Degree Utilization, x	0.01	0.02	0.04	0.05								
Capacity (veh/h)	875	898	915	875								
Control Delay (s)	7.1	7.0	7.0	7.3								
Approach Delay (s)	7.1	7.0	7.0	7.3								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.1									
Level of Service			Α									
Intersection Capacity Utilizati	ion		21.0%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	~	-	
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	W		f)			4
Traffic Volume (veh/h)	5	0	3	3	0	3
Future Volume (Veh/h)	5	0	3	3	0	3
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50
Hourly flow rate (vph)	10	0	6	6	0	6
Pedestrians	3					
Lane Width (m)	3.6					
Walking Speed (m/s)	1.2					
Percent Blockage	0					
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	18	12			15	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	18	12			15	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	99	100			100	
cM capacity (veh/h)	1002	1072			1612	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	10	12	6			
Volume Left	10	0	0			
Volume Right	0	6	0			
cSH	1002	1700	1612			
Volume to Capacity	0.01	0.01	0.00			
Queue Length 95th (m)	0.2	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	Α					
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	А					
Intersection Summary						
Average Delay			3.1			
Intersection Capacity Utiliz	zation		14.3%	IC	U Level	of Service
Analysis Period (min)			15			
.,,						

	→	\rightarrow	•	←	•	~
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1>		ሻ	*	¥#	
Traffic Volume (veh/h)	547	20	21	444	26	28
Future Volume (Veh/h)	547	20	21	444	26	28
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	636	23	24	516	30	33
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume			659		1212	648
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			659		1212	648
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			97		85	93
cM capacity (veh/h)			929		196	471
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	659	24	516	63		
Volume Left	0	24	0	30		
Volume Right	23	0	0	33		
cSH	1700	929	1700	282		
Volume to Capacity	0.39	0.03	0.30	0.22		
Queue Length 95th (m)	0.0	0.6	0.0	6.7		
Control Delay (s)	0.0	9.0	0.0	21.4		
Lane LOS	3.0	A	0.0	C		
Approach Delay (s)	0.0	0.4		21.4		
Approach LOS	0.0	<u> </u>		С		
Intersection Summary						
Average Delay			1.2			
Intersection Capacity Utiliza	ation		40.0%	IC	U Level o	f Service
Analysis Period (min)	auOH		15	10	O LEVEI U	I OCIVICE
Analysis Period (min)			15			

	٦	→	•	4	-	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		4	1>		W	
Traffic Volume (veh/h)	1	8	5	1	3	3
Future Volume (Veh/h)	1	8	5	1	3	3
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	1	9	6	1	3	3
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	7				18	6
vC1, stage 1 conf vol	,					
vC2, stage 2 conf vol						
vCu, unblocked vol	7				18	6
tC, single (s)	4.1				6.4	6.2
tC, 2 stage (s)					0.1	0.2
tF (s)	2.2				3.5	3.3
p0 queue free %	100				100	100
cM capacity (veh/h)	1614				1000	1076
		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	00.4		1000	1070
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	10	7	6			
Volume Left	1	0	3			
Volume Right	0	1	3			
cSH	1614	1700	1037			
Volume to Capacity	0.00	0.00	0.01			
Queue Length 95th (m)	0.0	0.0	0.1			
Control Delay (s)	0.7	0.0	8.5			
Lane LOS	А		Α			
Approach Delay (s)	0.7	0.0	8.5			
Approach LOS			Α			
Intersection Summary						
Average Delay			2.5			
Intersection Capacity Utiliz	zation		13.3%	IC	U Level o	of Service
Analysis Period (min)			15	.0	0 2010. 0	
raidiyələ i onou (min)			10			

	۶	-	•	•	—	•	•	†	~	/	Ţ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	¥	f)		7	f)			4			4	
Traffic Volume (veh/h)	4	608	20	32	747	9	30	4	31	13	9	16
Future Volume (Veh/h)	4	608	20	32	747	9	30	4	31	13	9	16
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	4	640	21	34	786	9	32	4	33	14	9	17
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	795			661			1536	1522	650	1542	1528	792
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	795			661			1536	1522	650	1542	1528	792
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			96			62	97	93	83	92	96
cM capacity (veh/h)	835			937			83	115	447	83	114	391
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	4	661	34	795	69	40						
Volume Left	4	0	34	0	32	14						
Volume Right	0	21	0	9	33	17						
cSH	835	1700	937	1700	140	137						
Volume to Capacity	0.00	0.39	0.04	0.47	0.49	0.29						
Queue Length 95th (m)	0.1	0.0	0.9	0.0	18.5	9.0						
Control Delay (s)	9.3	0.0	9.0	0.0	53.5	41.7						
Lane LOS	Α		Α		F	Е						
Approach Delay (s)	0.1		0.4		53.5	41.7						
Approach LOS					F	Е						
Intersection Summary												
Average Delay			3.6									
Intersection Capacity Utilization	1		52.1%	IC	CU Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	+	•	•	†	/	/	↓	-√
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	16	0	7	0	0	1	8	38	0	0	38	21
Future Volume (Veh/h)	16	0	7	0	0	1	8	38	0	0	38	21
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	22	0	10	0	0	1	11	52	0	0	52	29
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	144	148	68	156	162	57	83			57		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	144	148	68	156	162	57	83			57		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)												
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	97	100	99	100	100	100	99			100		
cM capacity (veh/h)	815	734	993	796	721	1011	1512			1541		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	32	1	63	81								
Volume Left	22	0	11	0								
Volume Right	10	1	0	29								
cSH	864	1011	1512	1541								
Volume to Capacity	0.04	0.00	0.01	0.00								
Queue Length 95th (m)	0.04	0.00	0.01	0.00								
	9.3	8.6	1.3	0.0								
Control Delay (s)				0.0								
Lane LOS	9.3	A	A 1.3	0.0								
Approach LOC		8.6	1.3	0.0								
Approach LOS	А	Α										
Intersection Summary												
Average Delay			2.2									
Intersection Capacity Utilizati	ion		24.2%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	۶	→	\rightarrow	•	←	•	4	†	/	>	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	2	0	10	8	14	0	47	4	15	59	3
Future Volume (vph)	2	2	0	10	8	14	0	47	4	15	59	3
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	2	2	0	11	9	16	0	53	4	17	66	3
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	4	36	57	86								
Volume Left (vph)	2	11	0	17								
Volume Right (vph)	0	16	4	3								
Hadj (s)	0.13	-0.17	-0.01	0.05								
Departure Headway (s)	4.4	4.0	4.1	4.1								
Degree Utilization, x	0.00	0.04	0.06	0.10								
Capacity (veh/h)	790	858	863	865								
Control Delay (s)	7.4	7.2	7.3	7.5								
Approach Delay (s)	7.4	7.2	7.3	7.5								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.4									
Level of Service			Α									
Intersection Capacity Utilization	n		23.4%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	<i>></i>	>	ļ
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations	¥		f)			ર્ન
Traffic Volume (veh/h)	6	0	4	4	0	4
Future Volume (Veh/h)	6	0	4	4	0	4
Sign Control	Stop		Free			Free
Grade	0%		0%			0%
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56
Hourly flow rate (vph)	11	0	7	7	0	7
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type			None			None
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	18	10			14	
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	18	10			14	
tC, single (s)	6.4	6.2			4.1	
tC, 2 stage (s)						
tF (s)	3.5	3.3			2.2	
p0 queue free %	99	100			100	
cM capacity (veh/h)	1006	1077			1617	
Direction, Lane #	WB 1	NB 1	SB 1			
Volume Total	11	14	7			
Volume Left	11	0	0			
Volume Right	0	7	0			
cSH	1006	1700	1617			
Volume to Capacity	0.01	0.01	0.00			
Queue Length 95th (m)	0.3	0.0	0.0			
Control Delay (s)	8.6	0.0	0.0			
Lane LOS	0.0 A	0.0	0.0			
Approach Delay (s)	8.6	0.0	0.0			
Approach LOS	0.0 A	0.0	0.0			
••	A					
Intersection Summary						
Average Delay			3.0			
Intersection Capacity Utiliz	zation		13.3%	IC	U Level o	f Service
Analysis Period (min)			15			

	•	→	+	4	/	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		र्स	f)		W	
Traffic Volume (veh/h)	2	3	9	2	1	1
Future Volume (Veh/h)	2	3	9	2	1	1
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	2	3	9	2	1	1
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	11				17	10
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol	11				17	10
tC, single (s)	4.1				6.4	6.2
tC, 2 stage (s)						
tF (s)	2.2				3.5	3.3
p0 queue free %	100				100	100
cM capacity (veh/h)	1608				1000	1071
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	5	11	2			
Volume Left	2	0	1			
Volume Right	0	2	1			
cSH	1608	1700	1034			
Volume to Capacity	0.00	0.01	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	2.9	0.0	8.5			
Lane LOS	Α		Α			
Approach Delay (s)	2.9	0.0	8.5			
Approach LOS			Α			
Intersection Summary						
Average Delay			1.7			
Intersection Capacity Utiliza	ation		13.3%	IC	U Level o	of Service
Analysis Period (min)			15			
rulalyolo i olloa (Illili)			10			

	۶	→	•	•	—	4	1	†	~	/	+	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	7	f)		7	₽			4			4	
Traffic Volume (veh/h)	6	576	8	11	449	9	10	9	7	6	3	9
Future Volume (Veh/h)	6	576	8	11	449	9	10	9	7	6	3	9
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	7	670	9	13	522	10	12	10	8	7	3	10
Pedestrians					2							
Lane Width (m)					3.6							
Walking Speed (m/s)					1.2							
Percent Blockage					0							
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	532			679			1248	1246	676	1252	1246	527
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	532			679			1248	1246	676	1252	1246	527
tC, single (s)	4.1			4.3			7.1	6.5	6.2	7.1	6.5	6.2
tC, 2 stage (s)												0.=
tF (s)	2.2			2.4			3.5	4.0	3.3	3.5	4.0	3.3
p0 queue free %	99			98			92	94	98	95	98	98
cM capacity (veh/h)	1046			847			144	171	456	139	171	555
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	7	679	13	532	30	20						
Volume Left	7	0/9	13	0	12	7						
	0	9	0	10	8	10						
Volume Right cSH	1046		847	1700	189	233						
		1700 0.40	0.02	0.31		0.09						
Volume to Capacity	0.01				0.16 4.4	2.2						
Queue Length 95th (m)		0.0	0.4	0.0								
Control Delay (s)	8.5	0.0	9.3	0.0	27.7	21.9						
Lane LOS	Α		A		D	C						
Approach Delay (s)	0.1		0.2		27.7	21.9						
Approach LOS					D	С						
Intersection Summary												
Average Delay			1.1									
Intersection Capacity Utiliza	ation		41.4%	IC	CU Level of	of Service			Α			
Analysis Period (min)			15									

	۶	→	•	•	+	•	1	†	<i>></i>	\	 	√
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	4	0	0	0	23	1	0	18	0
Future Volume (Veh/h)	0	0	0	4	0	0	0	23	1	0	18	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69	0.69
Hourly flow rate (vph)	0	0	0	6	0	0	0	33	1	0	26	0
Pedestrians		1			3							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	60	64	27	62	64	36	27			37		
vC1, stage 1 conf vol		<u> </u>		<u> </u>	<u> </u>					<u> </u>		
vC2, stage 2 conf vol												
vCu, unblocked vol	60	64	27	62	64	36	27			37		
tC, single (s)	7.1	6.5	6.2	8.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)	, , ,	0.0	0.2	0.1	0.0	0.2				1.1		
tF (s)	3.5	4.0	3.3	4.4	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	99	100	100	100			100		
cM capacity (veh/h)	932	824	1048	735	825	1039	1599			1583		
					020	1000	1000			1000		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	6	34	26								
Volume Left	0	6	0	0								
Volume Right	0	0	1	0								
cSH	1700	735	1599	1583								
Volume to Capacity	0.04	0.01	0.00	0.00								
Queue Length 95th (m)	0.0	0.2	0.0	0.0								
Control Delay (s)	0.0	9.9	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	9.9	0.0	0.0								
Approach LOS	Α	Α										
Intersection Summary												
Average Delay			0.9									
Intersection Capacity Utiliza	ation		14.3%	IC	U Level	of Service			Α			
Analysis Period (min)			15									

C. F. Crozier & Associates

Synchro 11 Light Report
Page 2

	۶	→	•	•	←	•	4	†	/	/	ļ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	3	3	3	3	5	0	20	10	13	23	2
Future Volume (vph)	2	3	3	3	3	5	0	20	10	13	23	2
Peak Hour Factor	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88	0.88
Hourly flow rate (vph)	2	3	3	3	3	6	0	23	11	15	26	2
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	8	12	34	43								
Volume Left (vph)	2	3	0	15								
Volume Right (vph)	3	6	11	2								
Hadj (s)	-0.14	-0.22	-0.16	0.08								
Departure Headway (s)	3.9	3.9	3.8	4.0								
Degree Utilization, x	0.01	0.01	0.04	0.05								
Capacity (veh/h)	892	911	922	879								
Control Delay (s)	7.0	6.9	7.0	7.3								
Approach Delay (s)	7.0	6.9	7.0	7.3								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.1									
Level of Service			Α									
Intersection Capacity Utilizati	on		20.8%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

	•	•	†	/	/	+	•
Movement	WBL	WBR	NBT	NBR	SBL	SBT	
Lane Configurations	¥		₽			सी	_
Traffic Volume (veh/h)	2	0	3	2	0	3	
Future Volume (Veh/h)	2	0	3	2	0	3	
Sign Control	Stop		Free			Free	
Grade	0%		0%			0%	
Peak Hour Factor	0.50	0.50	0.50	0.50	0.50	0.50	
Hourly flow rate (vph)	4	0	6	4	0	6	
Pedestrians	3						
Lane Width (m)	3.6						
Walking Speed (m/s)	1.2						
Percent Blockage	0						
Right turn flare (veh)	•						
Median type			None			None	
Median storage veh)							
Upstream signal (m)							
pX, platoon unblocked							
vC, conflicting volume	17	11			13		
vC1, stage 1 conf vol							
vC2, stage 2 conf vol							
vCu, unblocked vol	17	11			13		
tC, single (s)	6.4	6.2			4.1		
tC, 2 stage (s)	.						
tF (s)	3.5	3.3			2.2		
p0 queue free %	100	100			100		
cM capacity (veh/h)	1004	1073			1615		
	WB 1	NB 1	SB 1				
Direction, Lane # Volume Total							
	4	10	6				
Volume Left	4	0	0				
Volume Right	0	4	0				
cSH	1004	1700	1615				
Volume to Capacity	0.00	0.01	0.00				
Queue Length 95th (m)	0.1	0.0	0.0				
Control Delay (s)	8.6	0.0	0.0				
Lane LOS	A	0.0	0.0				
Approach Delay (s)	8.6	0.0	0.0				
Approach LOS	Α						
Intersection Summary							
Average Delay			1.7				
Intersection Capacity Utiliza	ation		14.3%	IC	U Level o	of Service	
Analysis Period (min)			15				

	-	•	•	←	•	<i>></i>
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1		ሻ	<u> </u>	W	
Traffic Volume (veh/h)	543	26	32	436	38	46
Future Volume (Veh/h)	543	26	32	436	38	46
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	631	30	37	507	44	53
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume			661		1227	646
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			661		1227	646
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			96		77	89
cM capacity (veh/h)			927		189	472
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	661	37	507	97		
Volume Left	0	37	0	44		
Volume Right	30	0	0	53		
cSH	1700	927	1700	281		
Volume to Capacity	0.39	0.04	0.30	0.35		
Queue Length 95th (m)	0.0	1.0	0.0	11.9		
Control Delay (s)	0.0	9.0	0.0	24.4		
Lane LOS		Α		С		
Approach Delay (s)	0.0	0.6		24.4		
Approach LOS				С		
Intersection Summary						
Average Delay			2.1			
Intersection Capacity Utiliza	tion		41.7%	IC	U Level c	f Service
Analysis Period (min)			15			

	۶	→	+	4	/	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		4	1>		W	
Traffic Volume (veh/h)	0	8	5	0	0	0
Future Volume (Veh/h)	0	8	5	0	0	0
Sign Control		Free	Free		Stop	•
Grade		0%	0%		0%	
Peak Hour Factor	0.86	0.86	0.86	0.86	0.86	0.86
Hourly flow rate (vph)	0	9	6	0	0	0
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
		NOHE	NOHE			
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked	6				4.5	c
vC, conflicting volume	6				15	6
vC1, stage 1 conf vol						
vC2, stage 2 conf vol	^				45	•
vCu, unblocked vol	6				15	6
tC, single (s)	4.1				6.4	6.2
tC, 2 stage (s)						
tF (s)	2.2				3.5	3.3
p0 queue free %	100				100	100
cM capacity (veh/h)	1615				1004	1077
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	9	6	0			
Volume Left	0	0	0			
Volume Right	0	0	0			
cSH	1615	1700	1700			
Volume to Capacity	0.00	0.00	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	0.0	0.0	0.0			
Lane LOS			Α			
Approach Delay (s)	0.0	0.0	0.0			
Approach LOS			Α			
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliza	ition		6.7%	IC	U Level	of Service
Analysis Period (min)			15	.0		

	٠	-	*	•	+	•	1	†	1	-	ļ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations	*	1		7	f			4			4	
Traffic Volume (veh/h)	4	616	18	19	762	9	29	4	22	13	9	16
Future Volume (Veh/h)	4	616	18	19	762	9	29	4	22	13	9	16
Sign Control		Free			Free			Stop			Stop	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	4	648	19	20	802	9	31	4	23	14	9	17
Pedestrians		2										
Lane Width (m)		3.6										
Walking Speed (m/s)		1.2										
Percent Blockage		0										
Right turn flare (veh)												
Median type		None			None							
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	811			667			1531	1516	658	1528	1522	808
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	811			667			1531	1516	658	1528	1522	808
tC, single (s)	4.1			4.1			7.1	6.5	6.4	7.1	6.5	6.2
tC, 2 stage (s)												
tF (s)	2.2			2.2			3.5	4.0	3.4	3.5	4.0	3.3
p0 queue free %	100			98			64	97	95	84	92	96
cM capacity (veh/h)	824			932			85	117	442	88	116	383
Direction, Lane #	EB 1	EB 2	WB 1	WB 2	NB 1	SB 1						
Volume Total	4	667	20	811	58	40						
Volume Left	4	0	20	0	31	14						
Volume Right	0	19	0	9	23	17						
cSH	824	1700	932	1700	129	142						
Volume to Capacity	0.00	0.39	0.02	0.48	0.45	0.28						
Queue Length 95th (m)	0.1	0.0	0.5	0.0	16.1	8.6						
Control Delay (s)	9.4	0.0	8.9	0.0	54.2	39.9						
Lane LOS	Α		Α		F	Е						
Approach Delay (s)	0.1		0.2		54.2	39.9						
Approach LOS					F	Е						
Intersection Summary												
Average Delay			3.1									
Intersection Capacity Utiliza	ation		52.4%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

C. F. Crozier & Associates

Synchro 11 Light Report
Page 1

	۶	→	*	•	←	•	1	†	~	1	Ţ	4
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Traffic Volume (veh/h)	0	0	0	0	0	1	0	44	0	0	44	0
Future Volume (Veh/h)	0	0	0	0	0	1	0	44	0	0	44	0
Sign Control		Stop			Stop			Free			Free	
Grade		0%			0%			0%			0%	
Peak Hour Factor	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73	0.73
Hourly flow rate (vph)	0	0	0	0	0	1	0	60	0	0	60	0
Pedestrians		2			5							
Lane Width (m)		3.6			3.6							
Walking Speed (m/s)		1.2			1.2							
Percent Blockage		0			0							
Right turn flare (veh)												
Median type								None			None	
Median storage veh)												
Upstream signal (m)												
pX, platoon unblocked												
vC, conflicting volume	123	127	62	125	127	65	62			65		
vC1, stage 1 conf vol												
vC2, stage 2 conf vol												
vCu, unblocked vol	123	127	62	125	127	65	62			65		
tC, single (s)	7.1	6.5	6.2	7.1	6.5	6.2	4.1			4.1		
tC, 2 stage (s)	• • • • • • • • • • • • • • • • • • • •	0.0	0.2	• • • •	0.0	0.2						
tF (s)	3.5	4.0	3.3	3.5	4.0	3.3	2.2			2.2		
p0 queue free %	100	100	100	100	100	100	100			100		
cM capacity (veh/h)	845	759	1001	846	759	1001	1538			1531		
					700	1001	1000			1001		
Direction, Lane #	EB 1	WB 1	NB 1	SB 1								
Volume Total	0	1	60	60								
Volume Left	0	0	0	0								
Volume Right	0	1	0	0								
cSH	1700	1001	1538	1531								
Volume to Capacity	0.04	0.00	0.00	0.00								
Queue Length 95th (m)	0.0	0.0	0.0	0.0								
Control Delay (s)	0.0	8.6	0.0	0.0								
Lane LOS	Α	Α										
Approach Delay (s)	0.0	8.6	0.0	0.0								
Approach LOS	Α	Α										
Intersection Summary												
Average Delay			0.1									
Intersection Capacity Utiliza	ition		14.9%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									
,												

	۶	→	*	1	+	1	4	†	-	-	ļ	1
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		4			4			4			4	
Sign Control		Stop			Stop			Stop			Stop	
Traffic Volume (vph)	2	1	0	10	6	14	0	45	4	15	58	3
Future Volume (vph)	2	1	0	10	6	14	0	45	4	15	58	3
Peak Hour Factor	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89	0.89
Hourly flow rate (vph)	2	1	0	11	7	16	0	51	4	17	65	3
Direction, Lane#	EB 1	WB 1	NB 1	SB 1								
Volume Total (vph)	3	34	55	85								
Volume Left (vph)	2	11	0	17								
Volume Right (vph)	0	16	4	3								
Hadj (s)	0.17	-0.18	-0.01	0.05								
Departure Headway (s)	4.4	4.0	4.1	4.1								
Degree Utilization, x	0.00	0.04	0.06	0.10								
Capacity (veh/h)	787	862	866	868								
Control Delay (s)	7.4	7.2	7.3	7.5								
Approach Delay (s)	7.4	7.2	7.3	7.5								
Approach LOS	Α	Α	Α	Α								
Intersection Summary												
Delay			7.4									
Level of Service			Α									
Intersection Capacity Utilization	on		23.3%	IC	U Level o	of Service			Α			
Analysis Period (min)			15									

Synchro 11 Light Report Page 3 C. F. Crozier & Associates

	•	•	†	~	1	↓	
Movement	WBL	WBR	NBT	NBR	SBL	SBT	
Lane Configurations	W		₽			र्स	_
Traffic Volume (veh/h)	5	0	4	2	0	4	
Future Volume (Veh/h)	5	0	4	2	0	4	
Sign Control	Stop		Free			Free	
Grade	0%		0%			0%	
Peak Hour Factor	0.56	0.56	0.56	0.56	0.56	0.56	
Hourly flow rate (vph)	9	0	7	4	0	7	
Pedestrians							
Lane Width (m)							
Walking Speed (m/s)							
Percent Blockage							
Right turn flare (veh)							
Median type			None			None	
Median storage veh)							
Upstream signal (m)							
pX, platoon unblocked							
vC, conflicting volume	16	9			11		
vC1, stage 1 conf vol							
vC2, stage 2 conf vol							
vCu, unblocked vol	16	9			11		
tC, single (s)	6.4	6.2			4.1		
tC, 2 stage (s)							
tF (s)	3.5	3.3			2.2		
p0 queue free %	99	100			100		
cM capacity (veh/h)	1008	1079			1621		
Direction, Lane #	WB 1	NB 1	SB 1				
Volume Total	9	11	7				
Volume Left	9	0	0				
Volume Right	0	4	0				
cSH	1008	1700	1621				
Volume to Capacity	0.01	0.01	0.00				
Queue Length 95th (m)	0.2	0.0	0.0				
Control Delay (s)	8.6	0.0	0.0				
Lane LOS	А						
Approach Delay (s)	8.6	0.0	0.0				
Approach LOS	А						
Intersection Summary							
Average Delay			2.9				
Intersection Capacity Utiliza	ation		13.3%	IC	U Level o	of Service	
Analysis Period (min)			15.070	.0	2 23107		
ranaryolo i onou (illiii)			10				

Synchro 11 Light Report C. F. Crozier & Associates Page 4

	-	*	•	←	1	1
Movement	EBT	EBR	WBL	WBT	NBL	NBR
Lane Configurations	1>		7	^	N/	
Traffic Volume (veh/h)	592	50	62	745	40	47
Future Volume (Veh/h)	592	50	62	745	40	47
Sign Control	Free			Free	Stop	
Grade	0%			0%	0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	623	53	65	784	42	49
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type	None			None		
Median storage veh)						
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume			676		1564	650
vC1, stage 1 conf vol						
vC2, stage 2 conf vol						
vCu, unblocked vol			676		1564	650
tC, single (s)			4.1		6.4	6.2
tC, 2 stage (s)						
tF (s)			2.2		3.5	3.3
p0 queue free %			93		63	90
cM capacity (veh/h)			915		114	469
Direction, Lane #	EB 1	WB 1	WB 2	NB 1		
Volume Total	676	65	784	91		
Volume Left	0	65	0	42		
Volume Right	53	0	0	49		
cSH	1700	915	1700	193		
Volume to Capacity	0.40	0.07	0.46	0.47		
Queue Length 95th (m)	0.0	1.8	0.0	18.2		
Control Delay (s)	0.0	9.2	0.0	39.4		
Lane LOS		Α		Е		
Approach Delay (s)	0.0	0.7		39.4		
Approach LOS				Е		
Intersection Summary						
Average Delay			2.6			
Intersection Capacity Utilizat	tion		52.7%	IC	U Level o	f Service
Analysis Period (min)			15			

Synchro 11 Light Report Page 5 C. F. Crozier & Associates

	۶	→	←	4	/	4
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations		र्स	1€		W	
Traffic Volume (veh/h)	0	3	9	0	0	0
Future Volume (Veh/h)	0	3	9	0	0	0
Sign Control		Free	Free		Stop	
Grade		0%	0%		0%	
Peak Hour Factor	0.95	0.95	0.95	0.95	0.95	0.95
Hourly flow rate (vph)	0	3	9	0	0	0
Pedestrians						
Lane Width (m)						
Walking Speed (m/s)						
Percent Blockage						
Right turn flare (veh)						
Median type		None	None			
Median storage veh)		110110	. 13110			
Upstream signal (m)						
pX, platoon unblocked						
vC, conflicting volume	9				12	9
vC1, stage 1 conf vol	<u> </u>				14	<u> </u>
vC2, stage 2 conf vol						
vCu, unblocked vol	9				12	9
tC, single (s)	4.1				6.4	6.2
tC, 2 stage (s)	7.1				J. T	٥.٢
tF (s)	2.2				3.5	3.3
p0 queue free %	100				100	100
cM capacity (veh/h)	1611				1008	1073
		MD 4	00.4		1000	1073
Direction, Lane #	EB 1	WB 1	SB 1			
Volume Total	3	9	0			
Volume Left	0	0	0			
Volume Right	0	0	0			
cSH	1611	1700	1700			
Volume to Capacity	0.00	0.01	0.00			
Queue Length 95th (m)	0.0	0.0	0.0			
Control Delay (s)	0.0	0.0	0.0			
Lane LOS			Α			
Approach Delay (s)	0.0	0.0	0.0			
Approach LOS			Α			
Intersection Summary						
Average Delay			0.0			
Intersection Capacity Utiliza	ation		6.7%	IC	U Level	of Service
Analysis Period (min)			15	.0		
raidiyolo i ollou (ililii)			10			

Synchro 11 Light Report C. F. Crozier & Associates Page 6

Traffic Impact Study February 2022

APPENDIX H

Roadway Improvement Information

This document can be made available in other accessible formats as soon as practicable and upon request



Report To: Committee of the Whole

Meeting Date: June 15, 2021 Report Number: CSOPS.21.044

Title: Beaver Street Stop Up and Close and Addition of Beaver and Louisa

to Thornbury West Phase 1

Prepared by: Michael Campbell, Construction Coordinator

A. Recommendations

THAT Council receive Staff Report CSOPS.21.044, entitled "Beaver Street Stop Up and Close and Addition of Beaver and Louisa to Thornbury West Phase 1";

AND THAT Council receive the Victoria and Louisa Streets Area Reconstruction Traffic Study, Attachment 1;

AND THAT Council direct Staff to initiate a public process for the stop-up and closure of Beaver Street between Victoria Street and Louisa Street as shown on Attachment #2;

AND THAT Council direct Staff to add the reconstruction of Beaver Street between Victoria Street and Alice Street and Louisa Street between Victoria Street and Beaver Street to the Thornbury West Phase 1 Reconstruction Project;


AND THAT Council increase the Thornbury West Road Reconstruction project budget by \$1,130,000 to fund the additional works.

B. Overview

The Town has a unique opportunity to enhance or eliminate 3 existing that have been recently identified by staff through the work being completed Thornbury West works as outlined in this report.

C. Background

The preliminary engineering for the Victoria and Louisa Streets Area Reconstruction included a traffic study that can be found as Attachment #1 as noted above. The study was undertaken because 2 of the intersections would be reconstructed by the Victoria & Louisa project and the requirements of the intersections needed to be understood. Therefore, the study was mostly for work outside the intended construction limits of the major project now known as Thornbury West Phase 1. The Study recommends:






TOWN OF THE BLUE MOUNTAINS ELMA & ALICE ST. AREA RECONSTRUCTION

BEAVER STREET CLOSURE

SCALE: 1:1,000 DATE: MAY/21 DWG. No. FIG. 2





TOWN OF THE BLUE MOUNTAINS ELMA & ALICE ST. AREA RECONSTRUCTION

BEAVER STREET TURN AROUND

SCALE: 1:1,000 DATE: MAY/21 DWG. No. FIG. 1

Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX I

Background Development Excerpts



Staff Report - REVISED

Planning and Development Services

Report To: Committee of the Whole

Date: June 2, 2020 Report Number: PDS.20.52

Subject: Towns of Thornbury Site Plan Approval

Prepared by: Denise Whaley, Planner II

A. Recommendations

THAT Council receive Staff Report PDS.20.52 entitled "Towns of Thornbury Site Plan Approval" for the lands known as RP 16R-1213, Part of Park Lot 10, Town Plot of Thornbury;

AND THAT Council grant Site Plan approval for these lands, subject to the following conditions:

- 1. That the final Plans and Drawings be received and accepted for Approved for Construction stamping by the Town;
- 2. That the Owner of the lands enter into a site plan agreement with the Town to satisfy all financial, legal, planning, engineering, and landscaping requirements; and
- 3. That this conditional approval is valid for a period of 90 days, after which, should the conditions not be met, the approval shall expire (*September 14, 2020*).

B. Overview

The purpose of this report is to make a recommendation on a Site Plan Application for a 23-unit condominium Townhouse project known as "Towns of Thornbury". The subject property is located on the corner of Lansdowne, Louisa and Beaver Streets. This Site Plan Application is required to return to Council for approval, rather than delegated to Town staff. Staff completed the review of the Site Plan Application and are now prepared to recommend approval of the Site Plan subject to conditions outlined in the recommendations section in this report.

C. Executive Summary


Application File #: P2784 (Site Plan Application)


Application Received: August 1, 2019


Application Deemed Complete: August 13, 2019

Official Plan Designation: Community Living Area (CLA)

Zoning Bylaw Category: R2-111-h33-h4a








ELECTRICAL LAYOUT NOTES:

- PROVIDE FISH ROPE IN EACH EMPTY DUCT

 INSTALL SPACERS EVERY 1524mm TO ASSEMBLY DUCTBANK. OFFSET OR STAGGER SPACER
- PROVIDE LARGE UTILITY "SWEEP" FITTINGS FOR ALL DUCT BENDS AS FOLLOWS:

 1220mm RADIUS FOR PRIMARY LOOOP AND EXPRESS FEEDERS.

 915mm RADIUS FOR SECONDARY SERVICES AND STREETLIGHTING
- BELL AND ROGERS DUCTS ARE BETWEEN NORTH CURB AND TURN TOWARDS UNIT 22. PRIMARY HYDRO DUCTS ARE BETWEEN NORTH AND SOUTH CURB. SECONDARY HYDRO DUCTS ARE BETWEEN SOUTH CURB AND TURN TOWARDS UNIT 22. SEE DETAIL 2/E1.



RC04 % RC05 PLAN VIEW DETAIL

DISCLAIMER AND COPYRIGHT

1. This drawing is the exclusive property of Runge & Associates Inc. and the reproduction of any part without prior written consent of this office is strictly prohibited.

2. The contractor shall verify all dimensions, levels, and datums on site and report any discrepancies or omissions to this office prior to construction.

3. This drawing is to be read and understood in conjunction with all other plans and documents

4. Drawing revision must be note "Issued For

Construction" before any work commences

applicable to this project.

BENCHMARKS
TBM 1 ELEV. 194.89
BOLT IN HYDRO POLE

BOLT IN HYDRO POLE LOCATED ON THE WEST SIDE OF LANSDOWNE STREET, APPROXIMATELY 47m SOUTHWEST OF THE INTERSECTION OF LANSDOWNE STREET AND LOUISA STREET

TBM 2 ELEY. 191.80
BOLT IN HYDRO POLE LOCATED ON THE SOUTH SIDE OF BEAVER STREET, APPROXIMATELY 85m SOUTHWEST OF THE INTERSECTION OF LOUISA STREET AND BEAVER STREET



THE TOWNS OF THORNBURY TOWN OF THE BLUE MOUNTAINS

UTILITY DESIGN LAYOUT

RUNGE ENGINEERI

CHECK: GGR

DESIGN: AD FILE: 19106T

DRAWN: AD DATE: OCTOBER 2019

SCALE: AS NOTED

E1

Runge & Associates Inc. 864 Hurontario Street P.O. Box 387 Collingwood, ON L9Y 3Z7 b: (705) 446-3590

f: (705) 446-3588 www.raiengineers.ca Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX J

ITE 11th Edition Trip Generation Excerpts

Land Use: 210 Single-Family Detached Housing

Description

A single-family detached housing site includes any single-family detached home on an individual lot. A typical site surveyed is a suburban subdivision.

Specialized Land Use

Data have been submitted for several single-family detached housing developments with homes that are commonly referred to as patio homes. A patio home is a detached housing unit that is located on a small lot with little (or no) front or back yard. In some subdivisions, communal maintenance of outside grounds is provided for the patio homes. The three patio home sites total 299 dwelling units with overall weighted average trip generation rates of 5.35 vehicle trips per dwelling unit for weekday, 0.26 for the AM adjacent street peak hour, and 0.47 for the PM adjacent street peak hour. These patio home rates based on a small sample of sites are lower than those for single-family detached housing (Land Use 210), lower than those for single-family attached housing (Land Use 251), and higher than those for senior adult housing -- single-family (Land Use 251). Further analysis of this housing type will be conducted in a future edition of Trip Generation Manual.

Additional Data

The technical appendices provide supporting information on time-of-day distributions for this land use. The appendices can be accessed through either the ITETripGen web app or the trip generation resource page on the ITE website (https://www.ite.org/technical-resources/topics/tripand-parking-generation/).

For 30 of the study sites, data on the number of residents and number of household vehicles are available. The overall averages for the 30 sites are 3.6 residents per dwelling unit and 1.5 vehicles per dwelling unit.

The sites were surveyed in the 1980s, the 1990s, the 2000s, and the 2010s in Arizona, California, Connecticut, Delaware, Illinois, Indiana, Kentucky, Maryland, Massachusetts, Minnesota, Montana, New Jersey, North Carolina, Ohio, Ontario (CAN), Oregon, Pennsylvania, South Carolina, South Dakota, Tennessee, Vermont, Virginia, and West Virginia.

Source Numbers

100, 105, 114, 126, 157, 167, 177, 197, 207, 211, 217, 267, 275, 293, 300, 319, 320, 356, 357, 367, 384, 387, 407, 435, 522, 550, 552, 579, 598, 601, 603, 614, 637, 711, 716, 720, 728, 735, 868, 869, 903, 925, 936, 1005, 1007, 1008, 1010, 1033, 1066, 1077,1078, 1079



Single-Family Detached Housing (210)

Vehicle Trip Ends vs: Dwelling Units

On a: Weekday,

Peak Hour of Adjacent Street Traffic,

One Hour Between 7 and 9 a.m.

Setting/Location: General Urban/Suburban


Number of Studies: 192 Avg. Num. of Dwelling Units: 226

Directional Distribution: 26% entering, 74% exiting

Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
0.70	0.27 - 2.27	0.24

Data Plot and Equation





Single-Family Detached Housing (210)

Vehicle Trip Ends vs: Dwelling Units

On a: Weekday,

Peak Hour of Adjacent Street Traffic,

One Hour Between 4 and 6 p.m.

Setting/Location: General Urban/Suburban


Number of Studies: 208 Avg. Num. of Dwelling Units: 248

Directional Distribution: 63% entering, 37% exiting

Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
0.94	0.35 - 2.98	0.31

Data Plot and Equation





Land Use: 220 **Multifamily Housing (Low-Rise)**

Description

Low-rise multifamily housing includes apartments, townhouses, and condominiums located within the same building with at least three other dwelling units and that have two or three floors (levels). Various configurations fit this description, including walkup apartment, mansion apartment, and stacked townhouse.

- A walkup apartment typically is two or three floors in height with dwelling units that are accessed by a single or multiple entrances with stairways and hallways.
- A mansion apartment is a single structure that contains several apartments within what appears to be a single-family dwelling unit.
- A fourplex is a single two-story structure with two matching dwelling units on the ground and second floors. Access to the individual units is typically internal to the structure and provided through a central entry and stairway.
- A stacked townhouse is designed to match the external appearance of a townhouse. But, unlike a townhouse dwelling unit that only shares walls with an adjoining unit, the stacked townhouse units share both floors and walls. Access to the individual units is typically internal to the structure and provided through a central entry and stairway.

Multifamily housing (mid-rise) (Land Use 221), multifamily housing (high-rise) (Land Use 222), affordable housing (Land Use 223), and off-campus student apartment (low-rise) (Land Use 225) are related land uses.

Land Use Subcategory

Data are presented for two subcategories for this land use: (1) not close to rail transit and (2) close to rail transit. A site is considered close to rail transit if the walking distance between the residential site entrance and the closest rail transit station entrance is 1/2 mile or less.

Additional Data

For the three sites for which both the number of residents and the number of occupied dwelling units were available, there were an average of 2.72 residents per occupied dwelling unit.

For the two sites for which the numbers of both total dwelling units and occupied dwelling units were available, an average of 96.2 percent of the total dwelling units were occupied.

The technical appendices provide supporting information on time-of-day distributions for this land use. The appendices can be accessed through either the ITETripGen web app or the trip



generation resource page on the ITE website (https://www.ite.org/technical-resources/topics/tripand-parking-generation/).

For the three sites for which data were provided for both occupied dwelling units and residents, there was an average of 2.72 residents per occupied dwelling unit.

It is expected that the number of bedrooms and number of residents are likely correlated to the trips generated by a residential site. To assist in future analysis, trip generation studies of all multifamily housing should attempt to obtain information on occupancy rate and on the mix of residential unit sizes (i.e., number of units by number of bedrooms at the site complex).

The sites were surveyed in the 1980s, the 1990s, the 2000s, the 2010s, and the 2020s in British Columbia (CAN), California, Delaware, Florida, Georgia, Illinois, Indiana, Maine, Maryland, Massachusetts, Minnesota, New Jersey, Ontario (CAN), Oregon, Pennsylvania, South Carolina, South Dakota, Tennessee, Texas, Utah, and Washington.

Source Numbers

188, 204, 237, 300, 305, 306, 320, 321, 357, 390, 412, 525, 530, 579, 583, 638, 864, 866, 896, 901, 903, 904, 936, 939, 944, 946, 947, 948, 963, 964, 966, 967, 1012, 1013, 1014, 1036, 1047, 1056, 1071, 1076



Multifamily Housing (Low-Rise) Not Close to Rail Transit (220)

Vehicle Trip Ends vs: Dwelling Units

On a: Weekday,

Peak Hour of Adjacent Street Traffic,

One Hour Between 7 and 9 a.m.

Setting/Location: General Urban/Suburban


Number of Studies: 49 Avg. Num. of Dwelling Units: 249

Directional Distribution: 24% entering, 76% exiting

Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
0.40	0.13 - 0.73	0.12

Data Plot and Equation





Multifamily Housing (Low-Rise) Not Close to Rail Transit (220)

Vehicle Trip Ends vs: Dwelling Units

On a: Weekday,

Peak Hour of Adjacent Street Traffic,

One Hour Between 4 and 6 p.m.

Setting/Location: General Urban/Suburban


Number of Studies: 59 Avg. Num. of Dwelling Units: 241

Directional Distribution: 63% entering, 37% exiting

Vehicle Trip Generation per Dwelling Unit

Average Rate	Range of Rates	Standard Deviation
0.51	0.08 - 1.04	0.15

Data Plot and Equation





Land Use: 822 Strip Retail Plaza (<40k)

Description

A strip retail plaza is an integrated group of commercial establishments that is planned, developed, owned, and managed as a unit. Each study site in this land use has less than 40,000 square feet of gross leasable area (GLA). Because a strip retail plaza is open-air, the GLA is the same as the gross floor area of the building.

The 40,000 square feet GFA threshold between strip retail plaza and shopping plaza (Land Use 821) was selected based on an examination of the overall shopping center/plaza database. No shopping plaza with a supermarket as its anchor is smaller than 40,000 square feet GLA.

Shopping center (>150k) (Land use 820), shopping plaza (40-150k) (Land Use 821), and factory outlet center (Land Use 823) are related uses.

Additional Data

The technical appendices provide supporting information on time-of-day distributions for this land use. The appendices can be accessed through either the ITETripGen web app or the trip generation resource page on the ITE website (https://www.ite.org/technical-resources/topics/tripand-parking-generation/).

The sites were surveyed in the 1980s, the 1990s, the 2000s, and the 2010s in Alberta (CAN), California, Delaware, Florida, New Jersey, Ontario (CAN), South Dakota, Vermont, Washington, and Wisconsin.

Source Numbers

304, 358, 423, 428, 437, 507, 715, 728, 936, 960, 961, 974, 1009



Strip Retail Plaza (<40k) (822)

Vehicle Trip Ends vs: 1000 Sq. Ft. GLA

On a: Weekday,

Peak Hour of Adjacent Street Traffic,

One Hour Between 7 and 9 a.m.

Setting/Location: General Urban/Suburban


Number of Studies: 5 Avg. 1000 Sq. Ft. GLA: 18

Directional Distribution: 60% entering, 40% exiting

Vehicle Trip Generation per 1000 Sq. Ft. GLA

Average Rate	Range of Rates	Standard Deviation
2.36	1.60 - 3.73	0.94

Data Plot and Equation





Strip Retail Plaza (<40k) (822)

Vehicle Trip Ends vs: 1000 Sq. Ft. GLA

On a: Weekday,

Peak Hour of Adjacent Street Traffic,

One Hour Between 4 and 6 p.m.

Setting/Location: General Urban/Suburban


Number of Studies: 25 Avg. 1000 Sq. Ft. GLA: 21

Directional Distribution: 50% entering, 50% exiting

Vehicle Trip Generation per 1000 Sq. Ft. GLA

Average Rate	Range of Rates	Standard Deviation
6.59	2.81 - 15.20	2.94

Data Plot and Equation






Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022


APPENDIX K


Auxiliary Left-Turn Lane Warrants





TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW

TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS













TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW

TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS













TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW


TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS

















TRAFFIC SIGNALS MAY BE WARRANTED IN RURAL
AREAS OR URBAN AREAS WITH RESTRICTED FLOW

TRAFFIC SIGNALS MAY BE WARRANTED IN "FREE FLOW" URBAN AREAS







Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX L

Signalization Warrants

Justification 1: Minimum Vehicle Volumes

Restricted Flow Urban Conditions

Justification	G	uidance Ap	proach Lan	es	Percentage Warrant								Total	Section Percent
Duotinoution	1 L	anes	2 or More Lanes			Hour Ending								
Flow Condition	FREE FLOW	RESTR. FLOW	FREE FLOW	RESTR. FLOW	7:00	8:00	9:00	12:00	13:00	16:00	17:00	18:00		
44	480	720	600	900	376	900	1,051	1,074	1,415	1,514	1,232	717		
14	1A COMPLIANCE %				52	100	100	100	100	100	100	100	752	94
40	120	170	120	170	33	42	55	47	63	109	40	37		
16	1B COMPLIANCE %				19	25	32	28	37	64	24	22	251	31
						Both 1A and 1B 100% Fullfilled each of 8 hours Yes Nuclesser of 1A or 1B at least 80% fulfilled each of 8 hours Yes No							_	

Justification 2: Delay to Cross Traffic

Restricted Flow Urban Conditions

Justification	G	uidance Ap	proach Lan	es	Percentage Warrant								Total	Section Percent
Custinguisi	1 lanes		2 or More lanes			Hour Ending								
Flow Condition	FREE FLOW	RESTR. FLOW	FREE FLOW	RESTR. FLOW	7:00	8:00	9:00	12:00	13:00	16:00	17:00	18:00		
2A	480	720	600	900	343	858	996	1,027	1,352	1,405	1,192	680		
2A		COMPLI	ANCE %		48	100	100	100	100	100	100	94	742	93
2B	50	75	50	75	14	16	27	30	39	62	25	26		
26		COMPLI	ANCE %		19	21	36	40	52	83	33	35	319	40
				Both 2A and 2B 100% Fullfilled each of 8 hours Lesser of 2A or 2B at least 80% fulfilled each of 8 hours Yes No							~	•		

Justification 3: Combination

Combination Justification 1 and 2

	Justification Satisfied 80% or Mo		Two Justifications Satisfied 80% or More				
Justification 1	Minimun Vehicular Volume	YES	[NO	•	YES		NO 🗸
Justification 2	Delay Cross Traffic	YES	Ī No) •			NOT JUSTIFIED

Justification 4: Four Hour Volume

Justification	Time Period	Total Volume of Both Approaches (Main)	Heaviest Minor Approach Y (actual)	Required Value Y (warrant threshold)	Average % Compliance	Overall % Compliance	
	12:00	1.027	34	07	35 %		
Justification 4	12.00	1,027	J4	31	33 %		
	13:00	1,352	34	80	43 %	52 %	
	16:00	1,405	77	80	96 %	52 /6	
	17:00	1,192	27	80	34 %		

Intersection: Arthur and Lansdowne Summary Results Justification Compliance Signal Justified? YES NO 1. Minimum Vehicular Volume B Crossing Volume 31 % 2. Delay to Cross Traffic B Crossing Road 40 % 3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 %
Justification Compliance Signal Justified? 1. Minimum Vehicular Volume B Crossing Volume B Crossing Volume 94 % 2. Delay to Cross Traffic B Crossing Road 40 % 3. Combination A Justification 1 31 % B Justification 2 40 % 5. Collision Experience 0 %
Justification Compliance Test No 1. Minimum Vehicular Volume B Crossing Volume B Crossing Volume 31 % 2. Delay to Cross Traffic B Crossing Road 40 % 3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 %
1. Minimum Vehicular Volume B Crossing Volume 31 % 2. Delay to Cross Traffic B Crossing Road 40 % 3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 5. Collision Experience 0 %
Vehicular Volume A Total Volume 94 % 2. Delay to Cross Traffic A Main Road 93 % 3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 %
2. Delay to Cross A Main Road 93 % Traffic B Crossing Road 40 % 3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 %
Cross Traffic B Crossing Road 40 % 3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 %
3. Combination A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 %
A Justification 1 31 % B Justification 2 40 % 4. 4-Hr Volume 52 % 5. Collision Experience 0 %
B Justification 2 40 % 4. 4-Hr Volume 52 % 5. Collision Experience 0 %
5. Collision Experience 0 %
6. Pedestrians A Volume Justification met
B Delay Justification not met

Intersection: Arthur St. and Lansdowne St.

Count Date: 2041

Justification 1: Minimum Vehicle Volumes

Restricted Flow Urban Conditions

Justification	Gı	iidance Ap	proach Lane	es	Percentage Warrant							Total	Section	
Sustainedition	1 La	nes	2 or Mor	e Lanes				Hour Er	ding				Across	Percent
Flow Condition	FREE FLOW	RESTR. FLOW	FREE FLOW	RESTR. FLOW	7:00	8:00	9:00	10:00	13:00	16:00	17:00	18:00		
4.	480	720	600	900	366	894	1,057	1,076	1,410	1,516	1,239	726		
1A	COMPLIANCE %			51	100	100	100	100	100	100	100	751	94	
1B	120	170	120	170	20	24	42	35	59	101	38	35		
16		COMPL	IANCE %		12	14	25	21	35	59	22	21	208	26
	Restricted Flow Signal Justification 1:				_						No No			

Justification 2: Delay to Cross Traffic

Restricted Flow Urban Conditions

Justification	Gu	uidance Ap	proach Lane	es		Percentage Warrant						Total	Section	
Justincation	1 lanes 2 or More lanes			Hour Ending								Percent		
Flow Condition	FREE FLOW	RESTR. FLOW	FREE FLOW	RESTR. FLOW	7:00	8:00	9:00	10:00	13:00	16:00	17:00	18:00		
2A	480	720	600	900	346	870	1,015	1,041	1,351	1,415	1,201	691		
ZA	COMPLIANCE %			48	100	100	100	100	100	100	96	744	93	
2B	50	75	50	75	11	14	24	24	39	63	26	27		
26		COMPL	IANCE %		15	19	32	32	52	84	35	36	304	38
	Restricted Flow				Both 2A and 2B 100% Fullfilled each of 8 hours Yes No							No		
	Signal Justification 2:				Lesser of 2A o	r 2B at least	80% fulfilled	each of 8 hou	ırs	Yes		No	•	

Justification 3: Combination

Combination Justification 1 and 2

	Justification Satisfied 80% or Mo	Two Justifications Satisfied 80% or More				
Justification 1	Minimun Vehicular Volume	YFS	NO	YES	П	NO 🔽
Justification 2	Delay Cross Traffic	VEC	[NO	 		NOT JUSTIFIED

Justification 4: Four Hour Volume

Justification	Time Period	Total Volume of Both Approaches (Main) X	Heaviest Minor Approach Y (actual)	Required Value Y (warrant threshold)	Average % Compliance	Overall % Compliance
	10:00	1,041	22	94	23 %	
Justification 4	13:00	1,351	30	80	38 %	45.0/
	16:00	1,415	69	80	86 %	45 %
	17:00	1,201	25	80	31 %	

Analysis Sheet

Proposed Collision

Intersection: Arthur St. and Lansdowne St.

Count Date: 2041

Summary Results

Justification		Complian	Compliance		Signal Justified?		
`	Just	incation	Compilan	Compliance		NO	
1. Minimum Vehicular	Α	Total Volume	94	%			
Volume	В	Crossing Volume	26	%			~
2. Delay to Cross	Α	Main Road	93	%			7
Traffic	В	Crossing Road	38	%			~
3. Combination	Α	Justificaton 1	26	%			1
	В	Justification 2	38	%			•
4. 4-Hr Volume			45	%			

5. Collision Experience		0	%		•
-------------------------	--	---	---	--	---

6. Pedestrians	Α	Volume	Justification met		
	В	Delay	Justification not met		•

Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

APPENDIX M TAC GDGCR Excerpts



Stopping sight distance is the sum of the distance travelled during the perception and reaction time and the braking distance.

SSD =
$$0.278Vt + 0.039 \frac{V^2}{a}$$
 (2.5.2)

Where:

SSD = Stopping sight distance (m)

t = Brake reaction time, 2.5 s

V = Design speed (km/h)

a = Deceleration rate (m/s²)

Table 2.5.2 gives the minimum stopping sight distances on level grade, on wet pavement, for a range of design speeds. These values are used for vertical curve design, intersection geometry and the placement of traffic control devices. The stopping sight distances quoted in **Table 2.5.2** may need to be increased for a variety of reasons related to grade and vehicle type as noted below.

Table 2.5.2: Stopping Sight Distance on level roadways for Automobiles⁵⁴

Design speed	Brake reaction	Braking distance	Stopping sight distance		
(km/h)	distance (m)	on level (m)	Calculated (m)	Design (m)	
20	13.9	4.6	18.5	20	
30	20.9	10.3	31.2	35	
40	27.8	18.4	46.2	50	
50	34.8	28.7	63.5	65	
60	41.7	41.3	83.0	85	
70	48.7	56.2	104.9	105	
80	55.6	73.4	129.0	130	
90	62.6	92.9	155.5	160	
100	69.5	114.7	184.2	185	
110	76.5	138.8	215.3	220	
120	83.4	165.2	248.6	250	
130	90.4	193.8	284.2	285	

Note: Brake reaction distance predicated on a time of 2.5 s; deceleration rate of 3.4 m/s² used to determine calculated sight distance.



Table 9.9.4: Design Intersection Sight Distance – Case B1, Left Turn From Stop

Design Speed (km/h)	Stopping Sight	Intersection Sight Distance for Passenger Ca		
	Distance (m)	Calculated (m)	Design (m)	
20	20	41.7	45	
30	35	62.6	65	
40	50	83.4	85	
50	65	104.3	105	
60	85	125.1	130	
70	105	146.0	150	
80	130	166.8	170	
90	160	187.7	190	
100	185	208.5	210	
110	220	229.4	230	
120 250		250.2	255	
130	285	271.1	275	

Note: Intersection sight distance shown is for a stopped passenger car to turn left onto a two-lane highway with no median and grades 3% or less. For other conditions, the time gap should be adjusted and the sight distance recalculated.

Sight distance design for left turns at divided-highway intersections should consider multiple design vehicles and median width. If the design vehicle used to determine sight distance for a divided-highway intersection is larger than a passenger car, then sight distance for left turns will need to be checked for that selected design vehicle and for smaller design vehicles as well. If the divided-highway median is wide enough to store the design vehicle with a clearance to the through lanes of approximately 1 m at both ends of the vehicle, no separate analysis for the departure sight triangle for left turns is needed on the minor-road approach for the near roadway to the left. In most cases, the departure sight triangle for right turns (case B2) will provide sufficient sight distance for a passenger car to cross the near roadway to reach the median. Possible exceptions are addressed in the discussion of case B3.

68 June 2017

Blue Meadows Inc.

125 Arthur Street

Traffic Impact Study
February 2022

List of Figures

Figure 1: Draft Plan (Montgomery Philip King Architect Inc.)

Figure 2: Site Location Plan

Figure 3: Existing Traffic Controls and Lane Configuration

Figure 4: 2021 Traffic Volumes

Figure 5: Towns of Thornbury Trip Assignment

Figure 6: Lora Bay Trip Assignment

Figure 7: Future Background 2026 Traffic Volumes
Figure 8: Future Background 2031 Traffic Volumes
Figure 9: Future Background 2041 Traffic Volumes

Figure 10: Residential Trip Distribution

Figure 11: Commercial Primary Trip Distribution
Figure 12: Commercial Pass-By Trip Distribution

Figure 13: Residential Trip Assignment


Figure 14: Commercial Primary Trip Assignment
Figure 15: Commercial Pass-By Trip Assignment
Figure 16: Future Total 2026 Traffic Volumes
Figure 17: Future Total 2031 Traffic Volumes
Future Total 2041 Traffic Volumes

Figure 19: Sensitivity Analysis Residential Trip Distribution

Figure 20: Sensitivity Analysis Commercial Primary Trip Distribution Sensitivity Analysis Commercial Pass-By Trip Distribution

Figure 22: Sensitivity Analysis Residential Trip Assignment

Figure 23: Sensitivity Analysis Commercial Primary Trip Assignment
Figure 24: Sensitivity Analysis Commercial Pass-By Trip Assignment
Sensitivity Analysis Future Total 2041 Traffic Volume




MONTGOMERY PHILIP KING ARCHITECT Inc.

383 McNABB STREET UNIT 124 SOUTHAMPTON ONTARIO

email: montgomery.king@sympatico.ca

ontroctor must verify all dimensions on the drawings nd report any discrepancies to the architect before roceeding with the work.





9. 22/02/04 N 8. 22/02/02 MF REVISED SITE TRIANGLES & DIMENSIONS 7. 22/01/26 7. 22/01/26 MF 6. 22/01/21 M 5. 22/01/07 M ADDED 15m SETBACK LINE 4. 22/01/05 M 3. 21/12/31 N 2. 21/12/06 MF 1 21/12/02 N No. Date

LANDSDOWNE & ALICE STREET

TOWN OF THE BLUE MOUNTAINS

Date Scale as noted 2021-1000 Drawn by





The Blue Meadows Inc. 125 Arthur Street

Drawing

2021 EXISTING TRAFFIC VOLUMES



D.B.	Design D.B.	Project No.	2142-6059
Date 23/12/2021	Check E.H.	Scale N.T.S	FIG. 4

STOP CONTROL

WEEKDAY AM(PM) PEAK HOUR VOLUMES




The Blue Meadows Inc. 125 Arthur Street

Drawing

LORA BAY HIEGHTS TRIP ASSIGNMENT



D.B.	Design D.B	Project No.	2142-6059
Date 23/12/2021	Check E.H	Scale N.T.S	PlG. 5



LEGEND:

STOP CONTROL

WEEKDAY AM(PM) PEAK HOUR VOLUMES


The Blue Meadows Inc. 125 Arthur Street

Drawing

TOWNS OF THORNBURY TRIP ASSIGNMENT



Drawn D.B.	Design D.B.	Project No.	2142-6	059
Date 23/12/2021	Check E.H.	Scale N.T.S	Dwg. FIG	. 6



2026 FUTURE BACKGROUND VOLUMES



D.B.	Design D.B.	Project No.	2142-6059
Date 23/12/2021	Check E.H.	Scale N.T.S	FIG. 7

Project

The Blue Meadows Inc. 125 Arthur Street

Drawing

2031 FUTURE BACKGROUND VOLUMES



D.B.	Design	D.B.	Project No.	21	42-605	9
Date 23/12/2021	Check	E.H.	Scale N.T.S	Dwg.	FIG.	8

STOP CONTROL

AM(PM) WEEKDAY AM(PM) PEAK HOUR VOLUMES



Project


The Blue Meadows Inc. 125 Arthur Street

Drawing

2041 FUTURE BACKGROUND VOLUMES



Drawn	D.B.	Design	D.B.	Project No.	21	42-60	59
Date 23/12	/2021	Check	E.H.	Scale N.T.S	Dwg.	FIG.	9




 Drawn D.B.
 Design D.B.
 D.B.
 Project No.
 2142-6059

 Date 23/12/2021
 Check E.H.
 E.H.
 N.T.S
 Dwg. FIG. 10

TRIP DISTRIBUTION PRIMAIRY COMMERCIAL

Drawn D.B.	Design D.B.	Project No.	2142-6059
^{Date} 23/12/2021	Check E.H.	Scale N.T.S	^{Dwg.} FIG. 11



TRIP DISTRIBUTION COMMERCIAL PASS-BY

Drawing

Drawn D.B.	Design D.B.	Project No.	2142-6059
Date 23/12/2021	Check E.H.	Scale N.T.S	FIG. 12

WEEKDAY AM(PM) PEAK HOUR VOLUMES




The Blue Meadows Inc. 125 Arthur Street

Drawing

TRIP ASSIGNMENT RESIDENTIAL




D.B.	Design D.B.	Project No.	2142-6059		
Date 23/12/2021	Check E.H.	Scale N.T.S	FIG. 13		



TRIP ASSIGNMENT COMMERCIAL




Drawn	D.B.	Design	D.B.	Project No.	2	142-6059
Date 23/12	2/2021	Check	E.H.	Scale N.T.S	Dwg.	FIG. 14



TRIP ASSIGNMENT COMMERCIAL PASS-BY




Drawn D.B.	Design D.B.	Project No.	2142-6059		
Date 23/12/2021	Check E.H.	Scale N.T.S	pwg. FIG.	15	



2026 FUTURE TOTAL VOLUMES

D.B.	Design D.B.	Project No.	2142-6059		
^{Date} 23/12/2021	Check E.H.	Scale N.T.S	FIG. 16		



2031 FUTURE TOTAL VOLUMES

D.B.	Design D.B.	Project No.	2142-6059		
^{Dete} 23/12/2021	Check E.H.	Scale N.T.S	^{Dwg.} FIG. 17		

Project


The Blue Meadows Inc. 125 Arthur Street


Drawing


2041 FUTURE TOTAL VOLUMES




Drawn	D.B.	Design	D.B.	Project No.	2	142-60	59
Date 23/12	/2021	Check	E.H.	Scale N.T.S	Dwg.	FIG.	18








DISTRIBUTION



ASSIGNMENT



SENSITIVITY ANALYSIS COMMERCIAL PRIMARY TRIP **ASSIGNMENT**



Drawn D.B.	Design D.B.	Project No.	2142-6059
Date 23/12/2021	Check E.H.	Scale N.T.S	^{Dwg.} FIG. 23


THE BLUE MEADOWS INC. 125 ARTHUR STREET

Drawing

SENSITIVITY ANALYSIS COMMERCIAL PASS-BY TRIP ASSIGNMENT



Drawn D.B.	Design D.B.	Project No.	2142-	6059
Date 23/12/2021	Check E.H.	Scale N.T.S	Dwg. FI(G. 24



SENSITIVITY ANALYSIS FUTURE TOTAL 2041 TRAFFIC **VOLUMES**

D.B.	Design D	В.	Project No.	21	42-60	59
Date 23/12/2021	Check E	Н.	Scale N.T.S	Dwg.	FIG.	25